15-163-21465-00-80

CORRECTED ACO-1

TYPE

19 82.

MY COMMISSION EXPIRES

AFFIDAVIT OF COMPLETION FORM

ACO-1 WELL HISTORY

SIDE ONE		~omn+
Two (2) copies of thi	s form shall be filed with the Kansas Corporat	Comption Com-
mission, 200 Colorado Derb	y Building, Wichita, Kansas 67202, within thir	ty (30)
	of a well, regardless of how the well was comp	leted.

F Attach separate letter of request if the information is to be held confidential. If confidential, only file one copy. Information on Side One will be of public record and Side Two will then be held confidential.

Applications must be made on dual completion, commingling, salt water disposal, injection and temporarily abandoned wells.

Attach one copy only wireline logs (i.e. electrical log, sonic log, gamma ray neutron log, etc.). (Rules 82-2-105 & 82-2-125) KCC# (316) 263-3238. LICENSE # 5286 EXPIRATION DATE Horizon Petroleum Corporation API / 163-21,465 OPERATOR ADDRESS Riverfront Place, 833 N. Waco Rooks COUNTY Wichita, Kansas 67203 WC Planny FIELD ** CONTACT PERSON Jerry Hoggatt/Janet Pierce PROD. FORMATION Conglomerate PHONE 316/267-8416 PURCHASER Koch Oil Company Bice LEASE ADDRESS P.O. Box 2256 WELL NO. #1 Wichita, Kansas 67201 WELL LOCATION SE SE NW Ramco Drilling Corporation DRILLING 2310 Ft. from North Line and CONTRACTOR 100 S. Main, 200 Hardage Center 2310 Ft. from West Line of ADDRESS the NW (Qtr.) SEC 16 TWP 10S RGE 17W . <u> Wichita, Kansas 67202</u> PLUGGING WELL PLAT (Office CONTRACTOR Use Only) ADDRESS **KCC** KGS TOTAL DEPTH 3700 SWD/REP **PBTD** 3698 PLG. SPUD DATE 10-19-81 DATE COMPLETED 2-27-82 GR 2120 DF DRILLED WITH (CABLE) (ROTARY) (**ATK**) TOOLS. DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE N/A Amount of surface pipe set and cemented <u>23</u>9' DV Tool Used? THIS AFFIDAVIT APPLIES TO: (Circle ONE) (Oil, Gas, Shut-in Gas, Dry, Disposal, Injection, Temporarily Abandoned, OWWO. Other ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATIONS PROMULGATED TO REGULATE THE OIL AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH. AFFIDAVIT <u>Jerry D. Hoggatt</u> , being of lawful age, hereby certifies that: I am the Affiant, and I am familiar with the contents of the foregoing Affidavit. The statements and allegations contained therein are true and correct. Jerry D. Hogg Name) SUBSCRIBED AND SWORN TO BEFORE ME this 1st _day of _September

** The person who can be reached by phone regarding any questions of this this

JANET L. PIERCE NOTARY PUBLIC STATE OF KANSAS

Appl.Exp. 672

CONSERVATION DIVISION Wichita, Kansas

(NOTARY PUBLIC)
Pierce

OPERATOR Horizon Petroleum Corporations

Bice

SEC, 16 TWP, 10S RGE. 17W

WELL NO. FILL IN WELL INFORMATION AS REQUIRED: SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION. Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, in-cluding depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries. NAME DEPTH BOTTOM FORMATION DESCRIPTION, CONTENTS, ETC. Check if no Drill Stem Tests Run., Topeka 3072 Heebner 3292 Surface soil, Sand, Shale 0 257 Toronto 3313 Sand & Shale 257 1330 Lansing/K.C. 3586 3335 1330 Shale 1719 Conglomerate 3616 Sand & Shale 1719 2119 Arbuckle 3659 Shale & Lime 2119 2439 Shale & Lime 2439 2685 Shale 2685 2768 Logs Shale & Lime 2981 2768 Shale & Lime 2981 3111 CD &DIL Shale & Lime 3360 3111 Shale & Lime 3360 3414 Shale & Lime 3414 3485 Shale & Lime 3485 3600 Shale & Lime 3600 3690 RTD 3700 RECEIVED STATE CORPORATION COMMISSION 1111 1 9 1984 CONSERVATION DIVISION Wichita, Kansas If additional space is needed use Report of all strings set — surface, intermediate, production, etc. CASING RECORD (New) or (Used) Sixe hole drilled Sixe casing set Weight ths/ft. Setting depth Type and percent additives Purpose of string Type cement Sacks Surface 10½" 8-5/8" 23# 251' Common 160 3% jel 415" 200 10% salt Production 7-7/8" 10.5# 3698 Common LINER RECORD PERFORATION RECORD Sacks cament 3618-3620 3561-62, 21-22, 34-3 TUBING RECORD etting depth acker set at _imited Entry 3355, 80, 3489 . 2-3/8" x 4.7# 3671' None ACID, FRACTURE, SHOT, CEMENT SQUEEZE RECORD Amount and kind of material used 250 Gal. 15% mud acid 3634-3638 3669-3664 <u>250 gal. 15% mud acid</u> 250 gal. 15% mud acid & 750 gal. MOD 303 1500 gal. 28% demulsion (NE) acid & 1500 gal 3618-3620 gri ige . <u>3561-62, 3521-22, 35</u>34-35 1500 gal. demulsion 3355, 3380, 3489 Date of first production Producing method (flowing, pumping, ges lift, etc.) Gravity 30.2 2-27-82 Pumping Estimated Gas-oil ratio % -I.P. Production .5bb1/day <u>None</u> CFPB Disposition of gas (vented, used on leas Perforations none