

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

Form ACO-1
September 1999
Form Must Be Typed

WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

ORIGINAL

Operator: License # 33344
Name: Quest Cherokee Oilfield Service, LLC
Address: 211 W. 14th Street
City/State/Zip: Chanute, KS 66720
Purchaser: Bluestem Pipeline, LLC
Operator Contact Person: Richard Marlin
Phone: (620) 431-9500
Contractor: Name: MOKAT Drilling
License: 5831
Wellsite Geologist: Michael L. Ebers

Designate Type of Completion:
 New Well Re-Entry Workover
 Oil SWD SLOW Temp. Abd.
 Gas ENHR SIGW
 Dry Other (Core, WSW, Expl., etc.)

If Workover/Re-entry: Old Well Info as follows:
Operator: _____
Well Name: _____
Original Comp. Date: _____ Original Total Depth: _____
 Deepening Re-perf. Conv. to Enhr./SWD
 Plug Back Plug Back Total Depth
 Commingled Docket No. _____
 Dual Completion Docket No. _____
 Other (SWD or Enhr.?) Docket No. _____

<u>11/3/04</u>	<u>11/4/04</u>	<u>11/12/04</u>
Spud Date or Recompletion Date	Date Reached TD	Completion Date or Recompletion Date

API No. 15 - 205-25902-0000
County: Wilson
_____ ne ne Sec. 16 Twp. 29 S. R. 16 East West
660 feet from S / (circle one) Line of Section
800 feet from (circle one) W (circle one) Line of Section

Footages Calculated from Nearest Outside Section Corner:
(circle one) NE SE NW SW
Lease Name: Wasson, Floyd Well #: 16-1
Field Name: Cherokee Basin CBM
Producing Formation: Summit/Mulky
Elevation: Ground: 816 Kelly Bushing: _____
Total Depth: 897 Plug Back Total Depth: 895.07'
Amount of Surface Pipe Set and Cemented at 20.4' Feet
Multiple Stage Cementing Collar Used? Yes No

If Alternate II completion, cement circulated from 895.07
feet depth to surface w/ 95 sx cmt.
ALT II within 2-22-07

Drilling Fluid Management Plan
(Data must be collected from the Reserve Pit)
Chloride content _____ ppm Fluid volume _____ bbls
Dewatering method used _____
Location of fluid disposal if hauled offsite: _____
Operator Name: _____
Lease Name: _____ License No.: _____
Quarter _____ Sec. _____ Twp. _____ S. R. _____ East West
County: _____ Docket No.: _____

RECEIVED
KANSAS CORPORATION COMMISSION
APR 12 2005
CONSERVATION DIVISION
WICHITA, KS

INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: Richard Marlin
Title: Chief Operating Officer Date: 4/8/05
Subscribed and sworn to before me this 8th day of April, 2005
Notary Public: Jennifer R. Houston
Date Commission Expires: 7/30/05

JENNIFER R. HOUSTON
Notary Public - State of Kansas
My Appt. Expires 7/30/05

KCC Office Use ONLY
 Letter of Confidentiality Received
If Denied, Yes Date: _____
 Wireline Log Received
 Geologist Report Received
 UIC Distribution

Operator Name: Quest Cherokee Oilfield Service, LLC Lease Name: Wasson, Floyd Well #: 16-1
 Sec. 16 Twp. 29 S. R. 16 East West County: Wilson

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken Yes No
 (Attach Additional Sheets)
 Samples Sent to Geological Survey Yes No
 Cores Taken Yes No
 Electric Log Run Yes No
 (Submit Copy)
 List All E. Logs Run:
 Comp Density/Neutron
 Dual Induction
 Gamma Ray/Neutron Log

<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample		
Name	Top	Datum
Lenapah Lime	376	+442
Altamont Lime	415	+403
Pawnee Lime	519	+299
Oswego Lime	588	+230
Verdigris Lime	704-1/2	+113-1/2

CASING RECORD <input type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs./ Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	11"	8-5/8"	24.75#	20.4'	"A"	4sx	
Production	6 3/4"	4 1/2"	10.5#	895.07'	"A"	95sx	

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone				

RECEIVED
KANSAS CORPORATION COMMISSION
APR 12 2005
CONSERVATION DIVISION
WICHITA, KS

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
4	611-614.5 & 625-629	366 bbls gelled water & 15309# 20/40 sand frac	611-614.5 & 625-629

TUBING RECORD		Size	Set At	Packer At	Liner Run
		2-3/8"		n/a	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Date of First, Resumerd Production, SWD or Enhr.		Producing Method			
3/16/05		<input type="checkbox"/> Flowing <input checked="" type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)			
Estimated Production Per 24 Hours	Oil Bbls.	Gas Mcf	Water Bbls.	Gas-Oil Ratio	Gravity
	n/a	0	0		

Disposition of Gas Vented Sold Used on Lease (If vented, Submit ACO-18.)

METHOD OF COMPLETION Open Hole Perf. Dually Comp. Commingled Other (Specify) _____

Production Interval _____

TREATMENT REPORT & FIELD TICKET
CEMENT

DATE	CUSTOMER #	WELL NAME & NUMBER	SECTION	TOWNSHIP	RANGE	COUNTY
11-12-2004		Wasson, Floyd #16-1	16	295	16E	W6

FOREMAN OPERATOR	TIME IN	TIME OUT	LESS LUNCH	TRUCK #	TRUCK HOURS	EMPLOYEE SIGNATURE
John . M	6:34	11:30	No	348	4.5	<i>[Signature]</i>
Wes . T	6:58	11:30	No	197	4	<i>Wesley Thomas</i>
Simmy . H	6:50	11:30	No	103	4	<i>[Signature]</i>
Tim . A	6:57	11:30	No	140	4	<i>[Signature]</i>
Rodney . A	6:50	11:30	No	286	4	<i>Red</i>

3. TYPE Longstring HOLE SIZE 6 3/4 HOLE DEPTH 897 CASING SIZE & WEIGHT 4 1/2 / 10.5
 CASING DEPTH 895 DRILL PIPE _____ TUBING _____ OTHER _____
 SLURRY WEIGHT 13.8 SLURRY VOL _____ WATER gal/sk _____ CEMENT LEFT in CASING 0
 DISPLACEMENT 14.2 DISPLACEMENT PSI 800 MIX PSI 100 RATE _____

REMARKS: Circulate with fresh H₂O. Ran 2 Gel ahead. Ran 9 BB18 Dye with 15 Gallons sodium silicate. Cement until dye return, flush pump, pump plug with t.c.l. water. Set float shoe.
Dozer on location to move crews in, around, and out of location. Muddy & soft pasture.

ACCOUNT CODE	QUANTITY or UNITS	DESCRIPTION of SERVICES or PRODUCT	UNIT PRICE	TOTAL
	# 348	Foreman Pickup		
	# 197	Cement Pump Truck		
	# 103	Bulk Truck		
1110	10 sks	Gilsonite		
1107	1 sks	Flo-Seal		
1118	2 sks	Premium Gel		
1215A	1 gal	KCL		
1111B	15 gals	Sodium Silicate		
1123	5,880 gals	City Water <u>140 BBL</u>		
	# 140	Transport		
	# 286	80 Vac		
	85 sks	Cement <u>95 sks w/additives</u>		
	<u>w/out additives</u>			
				SALES TAX
				ESTIMATED
				TOTAL

Quest Cherokee LLC Cementing Report

Date: 11-12-2004

Well: Wasson, Floyd # 16-1 Legals 16-295-16E Wilson Co.

RE: Run & Cement Longstring-Notified Becke at KCC Office- 11/12/04 @ 8:10 (AM) PM

Time:

- 1 7:30 A.M. Team- G + S oil -on location and rig up
- 2 7:48 A.M. Buckeye on location and spot casing trailer
- 3 8:25 A.M. Team- G + S oil -TIH w/ 895.07 ft of casing
- 4 7:55 A.M. QCOS on location and rig up
- 5 9:10 A.M. Team- G + S oil -Hit fill approx. 55 ft from T.D.
- 6 9:35 A.M. QCOS wash casing to T.D. and circulate 2 sks gel to surface
Wash time 9:10 A.M - 10:00 A.M (50 min) w/ 6al cycle clean Hole
- 7 9:40 A.M. Team- G + S oil -Land casing
- 8 10:15 A.M. Team- G + S oil -Rig down and off location
- 9 10:30 A.M. QCOS- pump- Circulate W/ fresh H2O, run 9 bbl dye with 15 gal sodium silicate, cement until dye return, flush pump, pump plug W/ KCL water, set float shoe

10 11:30 A.M. QCOS Rig down and off location

CEMENT SLURRY:

Total Cement: 95 sks
 Cement blend: OWC, 5# Gilsonite, 1/4# Flo-Seal
 Cement slurry weight: 13.8
 Average Surface Pressure:

Running cement circulation pressure: 100
 Pumping plug circulation pressure: 800
 Circulation during job: Good

RECEIVED
KANSAS CORPORATION COMMISSION

APR 12 2005

CONSERVATION DIVISION
WICHITA, KS

HOLE/CASING/FLOAT EQUIPMENT SUMMARY:

Hole Size & Depth: 6 3/4"- 897'
 Casing Size & Depth: New 4 1/2" 10.5# per/ft. Range 3-plus shoe- 895.07

- 852 Centralizer
- 724 Basket
- 554 Centralizer
- 383 Basket
- 170 Centralizer

1 ea 4 1/2" Latch-Down Float Shoe w/ Notch Collar on bottom & 4 1/2" Latch-Down Plug

Donek on location to move claws in, around, and out of muddy - soft paste, location.