1100 0 0 130C CONSERVATION DIVISION Wichita, Kansas

AFFIDAVIT OF COMPLETION FORM

ACO-1 WELL HISTORY

~00-00

TYPE

SIDE ONE

LICENSE #

 $\frac{\text{Two}}{\text{mission}}$ (2) $\frac{\text{copies}}{\text{Colorado}}$ of this form shall be filed with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within thirty (30) days after the completion of a well, regardless of how the well was completed.

Attach separate letter of request if the information is to be held confidential. If confidential, only file one copy. Information on Side One will be of public

record and Side Two will then be held confidential.

Applications must be made on dual completion, commingling, salt water disposal,

EXPIRATION DATE

injection and temporarily abandoned wells.

Attach one copy only wireline logs (i.e. electrical log, sonic log, gamma ray neutron log, etc.). (Rules 82-2-105 & 82-2-125) KCC# (316) 263-3238.

OPERATOR CHIEF DRILLING CO., INC.	API NO. 15-163-21,611
ADDRESS 905 Century Plaza Wichita	. Ks. COUNTY Rooks
ADDICTION	FIELD
** CONTACT HERSON F.W. SHELTON, JR. PHONE 316-262-3791	PROD. FORMATION
ADDRESS	SHELTON, JR. 316-262-3791 LEASE WHISMAN WELL NO. #1 WELL LOCATION \$\frac{5}{2}\$ SW SE PR DRILLING, INC. Entury Plaza ta, Ks. 67202 WELL PLAT DATE COMPLETED 7-30-82 2036 KB 2039 OTARY) (AIR) TOOLS. R REPRESSURING WELL BEING FROM THIS LEASE et and cemented 280' set @ DV Tool Used? 283' cem. W/170 sx, common Gas, Dry Disposal, bandoned, OWWO. Other STATUTES, RULES AND REGULATIONS PROMULGATED TO REGULATE THE OIL EN FULLY COMPLIED WITH. A F F I D A V I T LTON, JR., VICE PRESIDENT, being of lawful age, hereby certifies and I am familiar with the contents of the foregoing Affidavit. SHELTON, Name, VICE PRESIDENT F.W. SHELTON(Name,) VICE PRESIDENT
CONTRACTOR	Ft. from Line of
ADDRESS 905 Century Plaza	
Wichita, Ks. 67202	WELL PLAT (Office
PLUGGING	
CONTRACTOR ADDRESS Warrior Drilling, Inc.	
905 Century Plaza Wichita, K	KGSKGS
TOTAL DEPTH 3500' PBTD	SWD/REP
SPUD DATE 7-14-82 DATE COMPLETED 7-30-8	
ELEV: GR 2034 DF 2036 KB 2039	
DRILLED WITH (CABLE) (ROTARY) (AIR) TOOLS.	1 1 1B
DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEI USED TO DISPOSE OF WATER FROM THIS LEASE	ING
Amount of surface pipe set and cemented 280' se	t @ DV Tool Used?
THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil, Injection, Temporarily Abandoned, OWWO. Other_	Gas, Shut-in Gas, Dry Disposal,
ALL REQUIREMENTS OF THE STATUTES, RULES AND RECAND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH	GULATIONS PROMULGATED TO REGULATE THE OIL
	$\underline{\text{NT}}$, being of lawful age, hereby certifies
that: I am the Affiant, and I am familiar with	the contents of the foregoing Affidavit.
The statements and allegations contained there	
•	W Mutter
	F.W. SHELTON (NOTE), VICE PRESIDENT
SUBSCRIBED AND SWORN TO BEFORE ME this	2nd day of August, 1982,
19	
A MARTHA E. GUSTIN	Martha & Ulintin
NOTARY PUBLIC STATE OF KANSAS	(NOTARY PUBLIC)
MY COMMISSION EXPIRES 4-15-85	Martha E. Gustin

** The person who can be reached by phone regarding any questions concerning this information.

SEC, 16 TWP, 8S RGE, 19W

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, in-							OR	SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION.				
cluding depth interval	tested, cushion use	d, time tool ope	tool open, flowing and shut-in pressures, and recoveries.					NAME	DEPTH			
DST #1 3181 - 3260 Toronto & top zones of lansing 30-45-60-60 288' muddy wate IBHP: 1107#, FBHP: 1096# FP: 55-164 Running DST #2 3250 - 3293 (35 & 50 zomiss run plugged tool DST #3 3249 - 3327 (35-50-75-90 zones) 30-45-60-60 Rec., 1503' muddy water no oil, IBHP: 1151#, FBHP: 1140#, IFP: 120-382 FFP: 458 - 755							Ba To He To La BI Re	hydrite ase Anhy peka eebner oronto ansing KC eworked onglomer	1469 + 1502 + 2981 - 3186 - 3210 - 3224 - 3445 -			
DST #4 3342 30-45-60-60 1183#, FBHP: 76 -98	Rec., 144'	muddy w	ater IBH									
DST #5 3428 30-45-60-60, oil IBHP: 78 FFP: 132 - 1	Rec. 107' 9#, FBHP:	muddy w	ater, no									
T.D. 3500' D pos mix, 4% o w/80 sx., 2no @ 40', 10 sx p.m. Completo & Carl Goodro	gel, 3% c. d plug 290 . in ratho ed @ 2:00	c, lst p ' w/40 s le start p.m. Den	lug @ 85 x., 10 s ed @ 1:0 nis Hame	p ' · k. D								
Report of all string	s set — surface.	intermediate.	production, etc	c. CASING	RECO	ORD.	(New)	or (Used)			
Purpose of string	Size hole drilled	Size casing set		Setting depth		Type cement		Sacks	_	pe and percent additives		
	12 1/4"	8 5/8"	20#	283'	commo			170	3%	c.c.,	2% ge	
											-	
									 			
	<u> </u>								-			
					سسبيا		المساورة والمساورة والمساورة					
LINER RECORD					PERFORATION RECORD							
Top, ft.	Bottom, ft.	Sacks c	ement	Shots	per ft.		Size	6 type	D	epth interval		
:	TUBING RECO		-					odova naza y zavada y Deliver nazava del	†			
Size	Setting depth	Packer	set at						 		company and a second	
;	J = . ;											
		ACID, FRACT	URE, SHOT,	CEMENT SQ	UEEZ	E RECO	RD					
	Amo	unt and kind of	material used					De	pth inter	val treated		
						-410-00-04-04-04-04-04-04-04-04-04-04-04-04						
							. —					
							gyramy rices with the state of the same					
Date of first production		Produci	ng method (flow	ring, pumping,	gas lift	, etc.)		Gravit	·v			
Oil Gas Water Co												
RATE OF PRODUCTION PER 24 HOURS	Oil	ь	Gas bls.		MCF	water	7	Gas-oil ratio bbis. CI				
Disposition of gas (vented, used on lease or sold)						Perf	oration	ıs		, et		