Notice: Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

Kansas Corporation Commission Oil & Gas Conservation Division

WELL PLUGGING RECORD K.A.R. 82-3-117

Form CP-4 December 2003 Type or Print on this Form Form must be Signed All blanks must be Filled

	Lease Operator: F.G. Holl Company, L.L.C.					API Number:15 - 145-21,282 00 00							
Address: 9431 E Central, Ste 100, Wichita, KS 67206				Lease Name: Per									
Phone: (316) 684 -8481 Operator License #: 5056				3-35 Well Number: Spot Location (QQQQ): E/2 _ SE _ SW 660									
Type of Well: Gas (Oil, Gas D&A, SWD, ENHR, Water Supply Well, Cathodic, Other) The plugging proposal was approved on:													
						CHETOKEE	Depth to Top:	Bott	tom: 4250	T.D	Plugging Commen	6-26-07	
						Depth to Top: Bottom: T.D					Plugging Completed: 6-27-07		
	Depth to Top:	Bott	tom:	T.D	Plugging Complete	ed:							
Show depth and thickn	ness of all water, oil and	gas formations.											
Oil, Gas (or Water Records			Casing Record (S	Surface Conductor & Production)								
Formation	Content	From	То	Size	Put In	Pulled Out							
						·							
				8 5/8	333								
Hooked water truck to	er plugs were used, state to tubing, pumped 80 ba	the character of	of same depth s, pulled tubing	e mud fluid was p placed from (botto g, sand at 4190',	laced and the methodom), to (top) for each bailed 4 sacks ceme	d or methods used in introducing it into the plug set. ent, pulled slips, had 20" stretch,							
hole. If cement or othe Hooked water truck to ripped casing at 24	er plugs were used, state to tubing, pumped 80 ba 160', worked pipe, rip	the character of arrels to kill gas ped casing at	of same depth s, pulled tubing t 2290', cam	e mud fluid was p placed from (botto g, sand at 4190', e free, pulled u	laced and the methodom), to (top) for each bailed 4 sacks cements to 1100', pumpe	d or methods used in introducing it into the plug set. ent, pulled slips, had 20" stretch,							
hole. If cement or othe Hooked water truck to ripped casing at 24	er plugs were used, state to tubing, pumped 80 ba	the character of arrels to kill gas ped casing at	of same depth s, pulled tubing t 2290', cam	e mud fluid was p placed from (botto g, sand at 4190', e free, pulled u	laced and the methodom), to (top) for each bailed 4 sacks cements to 1100', pumpe	d or methods used in introducing it into the plug set. ent, pulled slips, had 20" stretch, and 15 gel, 50 sacks cement, pulled							
hole. If cement or othe Hooked water truck to ripped casing at 24 to 360', pumped 50 s.	er plugs were used, state to tubing, pumped 80 ba 160', worked pipe, rip tacks, pulled to 40', pun	the character of the ch	of same depth s, pulled tubing t 2290', cam	e mud fluid was p placed from (botto g, sand at 4190', e free, pulled u	laced and the methodom), to (top) for each bailed 4 sacks cement to 1100', pumper ed up location.	d or methods used in introducing it into the plug set. ent, pulled slips, had 20" stretch, ed 15 gel, 50 sacks cement, pulled RECEIVED KANSAS CORPORATION COMI							
hole. If cement or othe Hooked water truck to ripped casing at 24 to 360', pumped 50 so Name of Plugging Cont	er plugs were used, state to tubing, pumped 80 bar 160', worked pipe, rip tacks, pulled to 40', pun tractor: Quality Well Ser	the character of the ch	of same depth s, pulled tubing t 2290', came , tore down flo	e mud fluid was p placed from (botto g, sand at 4190', e free, pulled u	laced and the methodom), to (top) for each bailed 4 sacks cements to 1100', pumpe	d or methods used in introducing it into the plug set. ent, pulled slips, had 20" stretch, ed 15 gel, 50 sacks cement, pulled RECEIVED KANSAS CORPORATION COMI							
hole. If cement or othe Hooked water truck to ripped casing at 24 to 360', pumped 50 so Name of Plugging Cont	er plugs were used, state to tubing, pumped 80 ba 160', worked pipe, rip tacks, pulled to 40', pun	the character of the ch	of same depth s, pulled tubing t 2290', came , tore down flo	e mud fluid was p placed from (botto g, sand at 4190', e free, pulled u	laced and the methodom), to (top) for each bailed 4 sacks cement to 1100', pumper ed up location.	d or methods used in introducing it into the plug set. ent, pulled slips, had 20" stretch, ed 15 gel, 50 sacks cement, pulled RECEIVED KANSAS CORPORATION COMI							
hole. If cement or othe Hooked water truck to ripped casing at 24 to 360', pumped 50 s. Name of Plugging Cont Address: 190 US Hig	er plugs were used, state to tubing, pumped 80 base 160', worked pipe, rip tracks, pulled to 40', pun tractor: Quality Well Ser ghway 56, Ellinwoo sible for Plugging Fees:	the character of arrels to kill gas ped casing at nped 15 sacks, vice, Inc. d, KS 67526 F. G. Holl Co	of same depth s, pulled tubing t 2290', cam tore down flo	e mud fluid was p placed from (botto g, sand at 4190', e free, pulled u por and rig, clean	laced and the methodom), to (top) for each bailed 4 sacks cement to 1100', pumper ed up location.	d or methods used in introducing it into the plug set. ent, pulled slips, had 20" stretch, ed 15 gel, 50 sacks cement, pulled RECEIVED KANSAS CORPORATION COMI							
hole. If cement or othe Hooked water truck to ripped casing at 24 to 360', pumped 50 s. Name of Plugging Cont Address: 190 US Hig Name of Party Respons State of Kansas	er plugs were used, state to tubing, pumped 80 ba 160', worked pipe, rip tracks, pulled to 40', pun tractor: Quality Well Ser ghway 56, Ellinwoo sible for Plugging Fees:	the character of arrels to kill gas ped casing at apped 15 sacks, vice, Inc. d, KS 67526 F. G. Holl Co	of same depth s, pulled tubing t 2290', cam tore down flo	e mud fluid was p placed from (botto g, sand at 4190', e free, pulled u por and rig, clean	laced and the methodom), to (top) for each bailed 4 sacks cement to 1100', pumper ed up location.	d or methods used in introducing it into the plug set. ent, pulled slips, had 20" stretch, and 15 gel, 50 sacks cement, pulled RECEIVED KANSAS CORPORATION COMI							
hole. If cement or othe Hooked water truck to ripped casing at 24 to 360', pumped 50 s. Name of Plugging Cont Address: 190 US Hig	er plugs were used, state to tubing, pumped 80 ba 160', worked pipe, rip tracks, pulled to 40', pun tractor: Quality Well Ser ghway 56, Ellinwoo sible for Plugging Fees:	the character of arrels to kill gas ped casing at apped 15 sacks, vice, Inc. d, KS 67526 F. G. Holl Co	of same depth s, pulled tubing t 2290', cam tore down flo	e mud fluid was p placed from (botto g, sand at 4190', e free, pulled u por and rig, clean C	laced and the methodom), to (top) for each bailed 4 sacks cements bailed 4 sacks cements between the to 1100', pumpered up location. License #: 319	d or methods used in introducing it into the plug set. ent, pulled slips, had 20" stretch, ed 15 gel, 50 sacks cement, pulled RECEIVED KANSAS CORPORATION COMI 925 JUL 0 9 2007 CONSERVATION DIVISION							
hole. If cement or othe Hooked water truck to ripped casing at 24 to 360', pumped 50 s. Name of Plugging Cont Address: 190 US Hig Name of Party Respons State of Kansas Loveness Mpar	er plugs were used, state to tubing, pumped 80 base 160', worked pipe, rip tracks, pulled to 40', pun tractor: Quality Well Set ghway 56, Ellinwoo sible for Plugging Fees: County to je nat I have knowledge of the	the character of arrels to kill gas ped casing at apped 15 sacks, vice, Inc. d, KS 67526 F. G. Holl Company at the facts statements to kill gas ped casing at apped 15 sacks, vice, Inc.	of same depth c, pulled tubing t 2290', came tore down flo company, LL ick	e mud fluid was p placed from (botto g, sand at 4190', e free, pulled u por and rig, clean C , ss(Employee of clean contain	laced and the method om), to (top) for each bailed 4 sacks ceme p to 1100', pumpe ed up location. License #: 319	d or methods used in introducing it into the plug set. ent, pulled slips, had 20" stretch, and 15 gel, 50 sacks cement, pulled RECEIVED KANSAS CORPORATION COMI							
hole. If cement or othe Hooked water truck to ripped casing at 24 to 360', pumped 50 s. Name of Plugging Cont Address: 190 US High Name of Party Responsible Kansas Loveness Mpar Sworn on oath, says: The same are true and correspondent.	er plugs were used, state to tubing, pumped 80 base 160', worked pipe, riperacks, pulled to 40', puntractor: Quality Well Set ghway 56, Ellinwoo sible for Plugging Fees: County and I have knowledge of the part I h	the character of arrels to kill gas ped casing at apped 15 sacks, vice, Inc. d, KS 67526 F. G. Holl Company at the facts statement of the company at the facts statement are appeared to the company at the facts statement are appeared to the company at the facts statement are appeared to the company at the facts statement are appeared to the company at the company	of same depth c, pulled tubing t 2290', came tore down flo company, LL ick ents, and matte	ce mud fluid was p placed from (bottog, sand at 4190', e free, pulled u por and rig, clean cor and rig, clean (Employee of ers herein contain Loveness	laced and the method m), to (top) for each bailed 4 sacks cemes p to 1100', pumpe ed up location. License #: 319 Operator) or (Operator ed, and the log of the same same same same same same same sam	d or methods used in introducing it into the plug set. ent, pulled slips, had 20" stretch, and 15 gel, 50 sacks cement, pulled RECEIVED KANSAS CORPORATION COMINGES GONSERVATION DIVISION WICHITA, KS T) on above-described well, being first due above-described well is as filed, and the							
hole. If cement or othe Hooked water truck to ripped casing at 24 to 360', pumped 50 s. Name of Plugging Cont Address: 190 US High Name of Party Respons State of Kansas Loveness Mpar sworn on oath, says: The same are true and correct Notary Pumper BETT	er plugs were used, state to tubing, pumped 80 base 160', worked pipe, riperacks, pulled to 40', puntractor: Quality Well Seinghway 56, Ellinwoomsible for Plugging Fees: County on je and I have knowledge of the ct, so help me God.	the character of arrels to kill gas ped casing at apped 15 sacks, wice, Inc. d, KS 67526 F. G. Holl Company the facts statem (Signature)	of same depth c, pulled tubing t 2290', came tore down flo company, LL ick ents, and matte	ce mud fluid was p placed from (bottog, sand at 4190', e free, pulled u por and rig, clean cor and rig, clean (Employee of ers herein contain Loveness	laced and the method m), to (top) for each bailed 4 sacks cemes p to 1100', pumpe ed up location. License #: 319 Operator) or (Operator ed, and the log of the same same same same same same same sam	d or methods used in introducing it into the plug set. ent, pulled slips, had 20" stretch, and 15 gel, 50 sacks cement, pulled RECEIVED KANSAS CORPORATION COMINGS GONSERVATION DIVISION WICHITA, KS T) on above-described well, being first duled above-described well is as filed, and the shade of the composition of							