

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date 5/15/86 month day year
OPERATOR: License # 4752
Name Source Petroleum
Address 910 Century Plaza Bldg.
City/State/Zip Wichita, KS 67202
Contact Person Steve Murphy
Phone 316-262-7397

API Number 15-163-22,883-00-00
NW SW SW Sec. 4 Twp. 10 S, Rg. 18
990 Ft. from South Line of Section
4950 Ft. from East Line of Section

CONTRACTOR: License # unknown
Name
City/State

(Note: Locate well on Section Plat on reverse side)
Nearest lease or unit boundary line 330 feet
County Rooks
Lease Name Garvert Well # 1
Ground surface elevation unknown 2123.61 feet MSL
Domestic well within 330 feet: yes X no
Municipal well within one mile: yes X no
Depth to bottom of fresh water 200
Depth to bottom of usable water 950
Surface pipe by Alternate: 1 2 X
Surface pipe planned to be set 250
Conductor pipe required None
Projected Total Depth 3750 feet
Formation Arbuckle

Well Drilled For: Well Class: Type Equipment:
X Oil SWD Infield X Mud Rotary
Gas Inj Pool Ext Air Rotary
OWWO Expl X Wildcat Cable

If OWWO: old well info as follows:
Operator
Well Name
Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.
Date 5/21/86 Signature of Operator or Agent Title Partner

For KCC Use:
Conductor Pipe Required feet; Minimum Surface Pipe Required 250 feet per Alt. 4 2
This Authorization Expires 11-5-86 Approved By 5-5-86

Spudding 5/15/86 - PM

Call after Reading Entry for plug review. RCH/KOM

harding - want to tag - he was notified.

NW SW SW Sec. 4 Twp. 10 S, Rg. 18 X West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 40 feet depth with 10 sxs of 60/40 with 6% gel
2nd plug @ 50' below SP feet depth with 40 sxs of
3rd plug @ Base of Dakota feet depth with 100 sxs of
4th plug @ Anhydrite feet depth with 25 sxs of
5th plug @ Arbuckle feet depth with 25 sxs of
(2) Rathole with 15 sxs (b) Mousehole with N/A sxs

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging. In Addition: Call district office after well is either plugged or production casing is cemented in. (Call 7 a.m. to 5 p.m. workdays)

District office use only:
API #15-163-22883
Surface casing of feet set with sxs at hours, 19
Alternate 1 or 2 surface pipe was used.
Alternate 2 cementing was completed @ ft. depth with sxs on, 19
Hole plugged, 19, agent

RECEIVED KCC-KDHE MAY 6 JOINT DIST #6 HAYS, KS

STATE REGULATION COMMISSION JUN 13 1986

REGULATION DIVISION Wichita, Kansas