# STATE OF KANSAS STATE CORPORATION COMMISSION

## 15-163-20049-00-00 Form CP-4

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
212 No. Market

## WELL PLUGGING RECORD

State Corporation Commission 212 No. Market	R	looks	Count	y. Sec <u>∠⊃</u> T	wp. 10S Rge.	18	$\frac{3}{2}(\mathbf{W})$
Wichita, Kansas NORTH	NORTH Location as "NE/CNW%SW%" or footage from lines NW NE NE						
	Lease Owner	<b>~</b> 7	Edmisto	on			
	Lease Name Office Address			-1 Pank P		Well No.	
	Office Address Character of We						
	Date well compl				gust 13.	10	67
	Application for p	olugging filed					67
	Application for p	lugging approv	/ed			19	
i l	Plugging comme	nced		Au	gust 13,	19	67
		ugging completed			August 13, 19		67
	Reason for aband	donment of wel	l or producing	g formation	ary no	le	
	76 7		. 3 . 3				
	If a producing v Was permission			_			
Locate well correctly on above Section Plat	menced?Y		the Conserv	ation Division C	n its agents ber	ore plugging was	
ame of Conservation Agent who supe	ervised plugging of this	well	Leo M	lassey			
roducing formation							Feet
how depth and thickness of all water	, oil and gas formations	5.					
OIL, CAS OR WATER RECORD	os					CASING RECO	RD
	CONTENT	FROM	то	SIZE	PUT IN	PULLED OUT	
FORMATION	DONIENI	rauri		3125	rui iN	FULLED UD!	
Surface Pipe		<b></b> 0 <del></del>	196	8-5/8"	8/5/67	None	
			<del> </del>		<u> </u>		***************************************
			<u> </u>				
Describe in detail the manner in introducing it into the hole. If cen feet for each plug so	nent or other plugs weret.  Set bottom	re used, state the plug at	he character o	of same and dept	th placed, from		feet to
n introducing it into the hole. If cen	nent or other plugs weret.	plug at	800 w/	of same and depth 100 sack 25 sacks	s cement;		feet to
n introducing it into the hole. If cen	nent or other plugs weret.  Set bottom Set middle	plug at	800 w/	of same and depth 100 sack 25 sacks	s cement;		feet to
n introducing it into the hole. If cen	nent or other plugs weret.  Set bottom Set middle	plug at	800 w/	of same and depth 100 sack 25 sacks	s cement;		feet to
n introducing it into the hole. If cen	nent or other plugs weret.  Set bottom Set middle	plug at	800 w/	of same and depth 100 sack 25 sacks	s cement;		feet to
n introducing it into the hole. If cen	nent or other plugs weret.  Set bottom Set middle	plug at	800 w/	of same and depth 100 sack 25 sacks	s cement;		feet to
n introducing it into the hole. If cen	nent or other plugs weret.  Set bottom Set middle	plug at	800 w/	of same and depth 100 sack 25 sacks	s cement;		feet to
introducing it into the hole. If cen	nent or other plugs weret.  Set bottom Set middle	plug at	800 w/	of same and depth 100 sack 25 sacks	s cement;		feet to
introducing it into the hole. If cen	nent or other plugs weret.  Set bottom Set middle	plug at	800 w/	of same and depth 100 sack 25 sacks	s cement;		feet to
n introducing it into the hole. If cen	nent or other plugs weret.  Set bottom Set middle	plug at	800 w/	of same and depth 100 sack 25 sacks	s cement;		feet to
introducing it into the hole. If cen	nent or other plugs weret.  Set bottom Set middle	plug at	800 w/	of same and depth 100 sack 25 sacks	s cement;		feet to
introducing it into the hole. If cen	nent or other plugs weret.  Set bottom Set middle	plug at	800 w/	of same and depth 100 sack 25 sacks	s cement;		feet to
n introducing it into the hole. If cen	nent or other plugs weret.  Set bottom Set middle	plug at	800 w/	of same and depth 100 sack 25 sacks	s cement;		feet to
n introducing it into the hole. If cenfeet for each plug so	set bottom Set middle Set top plu	plug at plug at g at 30 t	800 W/ 190 W/ with 1	of same and depth /100 sack /25 sacks 0 sacks	s cement;		feet to
a introducing it into the hole. If cenfect for each plug so	set bottom Set middle Set top plu  E. K. Edmist	plug at plug at at 30 description is necessary on Drill	800 W/ 190 W/ with 1	of same and depth /100 sack /25 sacks .0 sacks .0 sacks	s cement; cement; cement.	1967 -1967 -1967 -1963 V DIVISION	feet to
introducing it into the hole. If cenfect for each plug so	set bottom Set middle Set top plu	plug at plug at at 30 description is necessary on Drill	800 W/ 190 W/ with 1	of same and depth /100 sack /25 sacks .0 sacks .0 sacks	s cement;	1967 -1967 -1967 -1963 V DIVISION	feet to
Name of Plugging Contractor	set bottom Set middle Set top plu  E. K. Edmist 425 First Na	plug at plug at g at 30 description is necessite on Drill tional B	800 W/ 190 W/ with 1	of same and depth /100 sack /25 sacks .0 sacks .0 sacks .0 sacks	s cement; cement; cement.	1967 -1967 -1967 -1963 V DIVISION	feet to
Jame of Plugging Contractor  Address  TATE OF  Kansas  E. K. Edm	set bottom Set middle Set top plu  E. K. Edmist 425 First Na  , COUI	plug at plug at g at 30 description is necessite on Drill tional B	800 w/ 190 w/ 190 w/ with 1  ssary, use BACF ing Co.	of same and depth of same and depth of same and depth of the sacks of this sheet)  Of this sheet)  Inc.,  Ig., Wich  Ock	AUG 1: O8-15  ita, Kans	1967 1967 1967 VOIVISION Sas	scribed
Name of Plugging Contractor	set bottom Set middle Set top plu  E. K. Edmist 425 First Na  COUL	plug at plug at gat 30 description is nece on Drill tional B	800 W/ 190 W/ with 1  ssary, use BACK ing Co. ank Blo	of same and depth of same and depth of sacks (25 sacks 0 sacks 0 sacks 0 sacks 0 wich or (owners) or (owners) or (owners) or (owners) or (owners) or (owners)	AUG 1: O8-15  ita, Kans	1967 1967 1967 VOIVISION Sas	scribed
Introducing it into the hole. If cenfect for each plug so feet for	set bottom Set middle Set top plu  E. K. Edmist 425 First Na  COUL	plug at plug at gat 30 description is nece on Drill tional B	800 W/ 190 W/ with 1  ssary, use BACK ing Co. ank Blo	of same and depth of same and depth of sacks (25 sacks 0 sacks 0 sacks 0 sacks 0 wich or (owners) or (owners) or (owners) or (owners) or (owners) or (owners)	AUG 1: O8-15  ita, Kans	1967 1967 1967 VOIVISION Sas	scribed
Jame of Plugging Contractor  Address  TATE OF  Kansas  E. K. Edm	set bottom Set middle Set top plu  E. K. Edmist 425 First Na  , COUL	plug at plug at g at 30 description is necessity on Drill tional B	800 W/ 190 W/ with 1  ssary, use BACK ing Co. ank Blo	of same and depth of same and depth of sacks (25 sacks 0 sacks 0 sacks 0 sacks 0 wich or (owners) or (owners) or (owners) or (owners) or (owners) or (owners)	AUG 1: O8-15  ita, Kans	1967 1967 1967 VOIVISION Sas	scribed
Name of Plugging Contractor	set bottom Set middle Set top plu  E. K. Edmist 425 First Na  , COUL	plug at plug at g at 30 description is necessary on Drill tional B	800 w/ 190 w/ with 1  ssary, use BACF ing Co. ank Bld sedgwi	of same and depted 100 sack 25 sacks 0 sacks 10	ita, Kans	ON COMMISSION  1967  1967  1967  OIVISION  COMMISSION  COMMISSION	scribed of the
Introducing it into the hole. If cenfect for each plug so feet for	set bottom Set middle Set top plu  E. K. Edmist 425 First Na  , COUL	plug at plug at glug at 30 description is necession Drill tional B	800 w/ 190 w/ with 1  ssary, use BACF ing Co. ank Bld sedgwi	of same and depth of same and depth of sacks (25 sacks 0 sacks	ita, Kans	1967 1967 1967 VOIVISION Sas	scribed of the
Name of Plugging Contractor	set bottom Set middle Set top plu  E. K. Edmist 425 First Na  , COUL	plug at plug at glug at 30 description is necession Drill tional B	800 w/ 190 w/ with 1  ssary, use BACF ing Co. ank Bld sedgwi	100 sack 25 sacks 0 sacks 0 sacks Wich ck Market) or (owners and market	AUG 1: O8 15  ita, Kans ita, Kans sherein contain	ON COMMISSION  1967  1967  1967  ONVISION  Sas  of the above-dened and the log	scribed of the
Jame of Plugging Contractor  Address  TATE OF  Kansas  E Ke Edm  vell, being first duly sworn on oath, bove-described well as filed and that	set bottom Set middle Set top plu  E. K. Edmist 425 First Na  , COUL	plug at plug at plug at a 30 description is necessary on Drill tional Beauty of the description is necessary of the description	800 w/ 190 w/ with 1  ssary, use BACF ing Co. ank Bld sedgwi	of same and depth of same and depth of sacks (25 sacks 0 sacks	ita, Kans  ita, Kans  ita, Kans  Algae  ita, Kans  ita, Bl  Address)	ON COMMISSION  1967  1967  1967  ONVISION  Sas  of the above-dened and the log	scribed of the

### DRILLER'S LOG

COMPANY:

E. K. Edmiston,

425 First National Bank Building,

Wichita, Kansas 67202.

ROTARY DRILLING COMMENCED:

August 5, 1967

ROTARY DRILLING COMPLETED:

August 13, 1967

WELL NAME:

SHEPARD No. 1

LOCATION:

NW NE NE Sec. 25-10s-18W,

Rooks County, Kansas

CONTRACTOR:

E. K. Edmiston Drilling Co., Inc., 425 First National Bank Building,

Wichita, Kansas.

CASING RECORD:

Set 196° of 8-5/8" surface pipe with 140 sacks 70-30 Posmix Sunset

#### L 0 G

Measurements from top of Kelly Bushing (Elevation 2065' K.B.)

Shale and Clay w/Post Rock Shale Sand Shale Sand Shale and Sand Streaks Shale and Sand Red Bed Anhydrite Shale and Shells Shale and Lime and Shells Lime and Shale	0 - 196 720 780 880 1025 1133 1195 1380 1415 1600 1900 3145	AUG 15 1967 08-15-196-
Lime and Shale	3690 R.T	D.,

The undersigned E. K. Edmiston, President of E. K. Edmiston Drilling Company, Inc., hereby certifies on behalf of said company, that the above log is a true and correct log of the formations encountered in drilling the above well, as reflected by the daily drilling reports.

E. K. Edmiston

STATE OF KANSAS

SS:

COUNTY OF SEDGWICK

BE IT REMEMBERED, that on this 14th day of August, 1967, before me, the undersigned, a Notary Public within and for the county and state aforesaid, came E. K. Edmiston, known to me to be the same person who executed the foregoing instrument on behalf of E. K. Edmiston Drilling Co., Inc., and he duly acknowledged the execution of the same for himself and for said company.

\*\* WITNESS WHEREOF, I have hereunto set my hand and official seal on the day and year last above written.

My Commission Expires:

Marilyn E. Fox, Notary Public