DISTRICT CONSERVATION AGENT'S REPORT

15-163-00436-00-06

TO:

State Corporation Commission Conservation Division 800 Bitting Building Wichita, Kansas

LOCATION SE SE NW SEC. 24 TWP. 8 RGE. 20 M Dry Hole x Abandoned Oil Well Abandoned Gas Well I have today completed supervision of plugging of: Well No. 1 Lease Raynor Operator Murfin Drg Co Address Wichita, Kans Field County Rooks Total Depth 3583 Feet. (Describe briefly the manner in which the well was plugged) 8 5/8" at 157' circulated with cement. Filled with heavy mud to 150'. set cementing plug, 1/2 sack hulls and 15 sax cement, mud to 40', set cementing plug, 1/2 sack hulls and 10 sax cement to bottom cellar.
I have today completed supervision of plugging of: Well No. l Lease Raynor Operator Murfin Drg Co Address Wichita, Kans Field County Rooks Total Depth 3583 Feet. (Describe briefly the manner in which the well was plugged) 8 5/8" at 157' circulated with cement. Filled with heavy mud to 150'. set cementing plug, 1/2 sack hulls and 15 sax cement, mud to 40', set cementing plug.
I have today completed supervision of plugging of: Well No. 1 Lease Raynor Operator Murfin Drg Co Address Wichita, Kans Field County Rooks Total Depth 3583 Feet. (Describe briefly the manner in which the well was plugged) 8 5/8" at 157' circulated with cement. Filled with heavy mud to 150'. set cementing plug, 1/2 sack hulls and 15 sax cement, mud to 40', set cementing plug.
Well No. 1 Lease Raynor Operator Murfin Drg Co Address Wichita, Kans Field County Rooks Total Depth 3583 Feet. (Describe briefly the manner in which the well was plugged) 8 5/8" at 157' circulated with cement. Filled with heavy mud to 150'. set cementing plug, 1/2 sack hulls and 15 sax cement, mud to 40', set cementing plug,
Operator Murfin Drg Co Address Wichita, Kans Field County Rooks Total Depth 3583 Feet. (Describe briefly the manner in which the well was plugged) 8 5/8" at 157' circulated with cement. Filled with heavy mud to 150'. set cementing plug, 1/2 sack hulls and 15 sax cement, mud to 40', set cementing plug.
Operator Murfin Drg Co Address Wichita, Kans Field County Rooks Total Depth 3583 Feet. (Describe briefly the manner in which the well was plugged) 8 5/8" at 157' circulated with cement. Filled with heavy mud to 150'. set cementing plug, 1/2 sack hulls and 15 sax cement, mud to 40', set cementing plug.
Total Depth 3583 Feet. (Describe briefly the manner in which the well was plugged) 8 5/8" at 157' circulated with cement. Filled with heavy mud to 150'. set cementing plug, 1/2 sack hulls and 15 sax cement, mud to 40', set cementing plug.
(Describe briefly the manner in which the well was plugged) 8 5/8" at 157' circulated with cement. Filled with heavy mud to 150'. set cementing plug, 1/2 sack hulls and 15 sax cement, mud to 40', set cementing plug.
8 5/8" at 157' circulated with cement. Filled with heavy mud to 150'. set cementing plug, 1/2 sack hulls and 15 sax cement, mud to 40', set cementing plug.
Filled with heavy mud to 150'. set cementing plug, 1/2 sack hulls and 15 sax cement, mud to 40', set cementing plug.
hulls and lo sax cement, mud to 40', set cementing plug,
hulls and lo sax cement, mud to 40', set cementing plug,
The state of the s
PINGGNG
FILE SEC 24 1 6 222
*OOK PACK LINE 38
District Conservation Weent
Date 5-15-52