

4-050157

L-19

33

R

TO: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API number: 15-163-23,213 -00-00

NE NE SW /4 SEC. 27, 08 S, 18 W  
2310 feet from S section line  
2310 feet from E section line

Operator license# 30722 Lease Fleming well # 1

Operator: Edwin C. Schuett & Sharp Engr County Rooks

Address: 1616 Glenarm Place Suite 1804 Well total depth 3460 feet *112.45*  
Denver, Colorado 80202  
(316)733-5577 Conductor Pipe: \_\_\_\_\_ inch @ \_\_\_\_\_ feet  
Surface pipe 8 5/8 inch @ 236 feet

Aband. oil well \_\_\_\_, Gas well \_\_\_\_, Input well \_\_\_\_, SWD \_\_\_\_, D & A X

Plugging contractor: Emphasis Oil Operations License# 8241

Address: \_\_\_\_\_

Company to plug at: Hour: AM Day: 19 Month: January Year: 1993

Plugging proposal received from: Larry Langhoffer

Company: Emphasis Oil Operations phone: \_\_\_\_\_

Were: Spot plugs through drill pipe w/ heavy mud between all plugs.

1st plug @ 3370 feet with 25 sacks Rat hole: 15 sacks

2nd plug @ 1380 feet " 25 " Mousehole: 10 sacks

3rd plug @ 795 feet " 100 "

4th plug @ 285 feet " 40 "

5th plug @ 40 feet " 10 with 8 5/8" wiper plug

Plugging Proposal Received by: Marvin L. Miller

Plugging operations attended by agent? All[ ], Part[ ], None[ X ]

Completed: Hour: 1:30 AM, Day: 19, Month: January, Year: 1993

Actual plugging report: Hole reported plugged as above. *1-22-93*

Order 225 sx 60/40 pozmix w/ 6% gel and 1/4# celloflake or flowcel perfo  
STATE CORPORATION COMMISSION

Remarks: Elevation: 1995, Anhydrite: 1367-1405 feet, Anhydrite plug: 1200  
Bottom plug (in place): Yes X, Calc \_\_\_\_, No \_\_\_\_ Arbuckle: 342  
RECEIVED JAN 22 1993 CONSERVATION DIVISION STATE CORPORATION COMMISSION

Did penetrate Arbuckle, cemented by Allied Cementing Company

I did  [ ] observe the plugging. Marvin L. Miller

DATE 2-4-93

INV. NO. 37310

Marvin L. Miller P.I.R.T.II (agent)