12

6-041332

TO:	API number: 15-163-20,5944-00-07
STATE CORPORATION COMMISSION	
CONSERVATION DIVISION - PLUGGING	<u>NE NE SE</u> /4 SEC. <u>33</u> , <u>8</u> S, <u>17</u> W
200 COLORADO DERBY BUILDING	2310 feet from S section line
WICHITA, KANSAS 67202	
Operator license# 8714	Lease <u>McMullen</u> well # <u>2</u> 9
THE RESIDENCE OF THE PROPERTY	
Operator: <u>H & C Operating</u>	_ County Rooks 125.84
Address: P.O. Box 86	Well total depth 3872 feet
Plainville, Kansas 67663	Conductor Pipe: O inch a O feet
Aband. oil well, Gas well, In	nput well, SWD _X_, D & A
Plugging contractor: Allied Cementing	License#
Address: <u>Russell, Kansas 67665</u>	
Company to plug at: Hour: <u>9:00A.M</u> Day	: 2 Month: October Year: 91
Plugging proposal received from: Bo	b Plante
Company: H & C Operating	Phone:
Were: <u>5 1/2" casing set at 3610' w</u>	/150 sks. cement. O.H. to 3872'.
<u>rert. 0 2200 circulate cement to sur</u>	face w/450 sks. Ordered 250 sks.
50/40 poz 10% gel. with 1/4 lb. fl	ocele plus 5 sks. hulls, plus
100 sks. common.	
Plugging Proposal Received by: <u>Denn</u>	is L. Hamel
Plugging operations attended by agent	? All[X], Part[], None[]
Completed: Hour: <u>12:00P.M</u> , Day: <u>2</u> , M	
	onth: October . Year: 91
D., J. 3. 3. 3	1
Actual plugging report: Pumped in 5	1/2" casing with 50 sks. cement
<u>vith 1/4 lb. flocele plus pumped in a</u>	1/2" casing with 50 sks. cement
with 1/4 lb. flocele plus pumped in a 1/4 lb. flocele and 500 sks. hulls mi	1/2" casing with 50 sks. cement ddition 250 sks. cement with xed in cement. Max. 800 lb.
with 1/4 lb. flocele plus pumped in a 1/4 lb. flocele and 500 sks. hulls mi 3.I. 300 lb. Pumped in 8 5/8" casing	1/2" casing with 50 sks. cement ddition 250 sks. cement with xed in cement. Max. 800 lb.
with 1/4 lb. flocele plus pumped in a ./4 lb. flocele and 500 sks. hulls mi 3.I. 300 lb. Pumped in 8 5/8" casing	1/2" casing with 50 sks. cement ddition 250 sks. cement with xed in cement. Max. 800 lb.
with 1/4 lb. flocele plus pumped in a 1/4 lb. flocele and 500 sks. hulls mi 3.I. 300 lb. Pumped in 8 5/8" casing	1/2" casing with 50 sks. cement ddition 250 sks. cement with xed in cement. Max. 800 lb.
With 1/4 lb. flocele plus pumped in a 1/4 lb. flocele and 500 sks. hulls mi 3.I. 300 lb. Pumped in 8 5/8" casing	1/2" casing with 50 sks. cement ddition 250 sks. cement with xed in cement. Max. 800 lb.
With 1/4 lb. flocele plus pumped in a L/4 lb. flocele and 500 sks. hulls mi G.I. 300 lb. Pumped in 8 5/8" casing Flocele. Max. 400 lb. S.I. 200 lb.	1/2" casing with 50 sks. cement addition 250 sks. cement with xed in cement. Max. 800 lb. w/500 sks. cement with 1/4 lb. (ANSAS CORPCRATION COMMISSIONA
With 1/4 lb. flocele plus pumped in a L/4 lb. flocele and 500 sks. hulls mi S.I. 300 lb. Pumped in 8 5/8" casing flocele. Max. 400 lb. S.I. 200 lb.	1/2" casing with 50 sks. cement ddition 250 sks. cement with xed in cement. Max. 800 lb. w/500 sks. cement with 1/4 lb. (ANSAS CORPORATION COMMISSION COMISSION COMMISSION COMMISSION COMMISSION COMMISSION COMMISSION COM
With 1/4 lb. flocele plus pumped in a 1/4 lb. flocele and 500 sks. hulls mi S.I. 300 lb. Pumped in 8 5/8" casing flocele. Max. 400 lb. S.I. 200 lb.	1/2" casing with 50 sks. cement addition 250 sks. cement with xed in cement. Max. 800 lb. w/500 sks. cement with 1/4 lb. (ANSAS CORPGRATION COMMISSION COMMISSION PROPERTY 1991 10/8/91
With 1/4 lb. flocele plus pumped in a 1/4 lb. flocele and 500 sks. hulls mi S.I. 300 lb. Pumped in 8 5/8" casing flocele. Max. 400 lb. S.I. 200 lb.	1/2" casing with 50 sks. cement addition 250 sks. cement with xed in cement. Max. 800 lb. w/500 sks. cement with 1/4 lb. (ANSAS CORPGRATION COMMISSION COMMISSION PROPERTY 1991 10/8/91
With 1/4 lb. flocele plus pumped in a 1/4 lb. flocele and 500 sks. hulls mi S.I. 300 lb. Pumped in 8 5/8" casing flocele. Max. 400 lb. S.I. 200 lb.	1/2" casing with 50 sks. cement with addition 250 sks. cement with xed in cement. Max. 800 lb. w/500 sks. cement with 1/4 lb. (ANSAS CORPORATION COMMISSION CONSERVATION DIVISION
Remarks: [NiV(0 C/EdP not[] observe the part of th	1/2" casing with 50 sks. cement with addition 250 sks. cement with xed in cement. Max. 800 lb. w/500 sks. cement with 1/4 lb. (ANSAS CORPORATION COMMISSION CONSERVATION DIVISION
With 1/4 1b. flocele plus pumped in a 1/4 1b. flocele and 500 sks. hulls miss. I. 300 1b. Pumped in 8 5/8" casing flocele. Max. 400 1b. S.I. 200 1b. Remarks: [NiV[O]CEQ not[] observe the process of the second content o	1/2" casing with 50 sks. cement with addition 250 sks. cement with xed in cement. Max. 800 lb. w/500 sks. cement with 1/4 lb. W/500 sks. cement with 1/4 lb. OCT 8 1991 10 8 91 CONSERVATION DIVISION plugging. Newwis J. Hamel
NiVIOICED not[] observe the	1/2" casing with 50 sks. cement with addition 250 sks. cement with xed in cement. Max. 800 lb. w/500 sks. cement with 1/4 lb. KANSAS CORPCRATION COMMISSION CONSERVATION DIVISION