4- <u>03179</u> 7	
и.	163-01762-0000
TO: STATE CORPORATION COMMISSION	API number: 15 1956
CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING	N2 NW NW /4 SEC. 27 , 9 S, 20 W
WICHITA, KANSAS 67202	<u>4950</u> feet from S section line <u>4620</u> feet from E section line
Operator license# 5285	Lease Trible well # 7
Operator: The Dane G. Hansen Trust	County Rooks 33
Address: Box 304	Well total depth 3795 feet 123.33
Logan, Ks. 67646	Conductor Pipe: 0 inch @ 0 feet
	Surface pipe 8 5/8 Inch @ 172 feet
Aband. oil well $\underline{x}$ , Gas well $\underline{\hspace{1cm}}$ , Inp	out well, SWD, D & A
Plugging contractor: Allied Cementing Co. Inc. License#	
Address: Russell, Ks.	
Company to plug at: Hour: A.M. Day:	28 Month: January Year: 93
Plugging proposal received from: Rich Wallgren	
Company: Hansen Phone:	
Were: Order 300 sks 65/35 poz 10% gel 500 lbs. hulls. Hole open to TD.	
Plugging Proposal Received by: <u>Carl Goodrow</u> Plugging operations attended by agent? All[ x ], Part[ ], None[ ]	
Completed: Hour: 11:00AM , Day: 28 , Mo	nth: <u>January</u> , Year: <u>93</u>
Actual plugging report: 8 5/8 set at 172 w/150 sks. 5 1/2" set at	
3792' W/123 SKS. BOTTOM Stage Collar set at 1728! W/450 sks awa	
Squeezed at 1412' - 44' w/50 sks. 2206 - 3087 w/300 sks.  2500' w/100 sks 60/40 poz. Tested 8 5/8" to 500 lbs. cement at surface.	
squeeze 5 1/2" W/260 SKS cement blend	W/500 lbc bullo mirrod in to
max. psi 1300 lbs. Close in psi 500 l	bs. Plug complete. STATE OFFICE INC.
	bs. Plug complete.  STATE COMPORATION COMM
Remarks:	CONSECTO TO 1900
Condition of casing(in hole):GOOD Y B	CONSERVATION DIVISION NO WICHITA KANSAS
Tragged Chiodgh Tobing, CASING_X	Elevation:GL
I dM[k ) bid not[ ] observe the p	lugging. Carl Goodrow Carlos
PATE FEB 2 1993	HO.

10 NO. 373 99 N

(agent)

Form CP-2/3