

6 020530

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- July 18, 1958  
SW NE SE \_\_\_\_\_, SEC. 18, T 9 S, R 21 W/E  
1650 feet from S section line  
990 feet from E section line

TECHNICIAN'S PLUGGING REPORT  
Operator License # 5245  
Operator: Okmar Oil Co.  
Name & Address: Box 723  
Hays, Kansas 67601

Lease Name Sutor Well # B - 10  
County Graham 123.92  
Well Total Depth 3813. CIBP 3760 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 185

Abandoned Oil Well \_\_\_\_\_ x Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ O&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Okmar Oil Co. License Number 5245

Address Same as above

Company to plug at: Hour: 1:00PM Day: 11 Month: May Year: 19 90

Plugging proposal received from Bob Grant

(company name) Okmar Oil Co. (phone) \_\_\_\_\_

were: 3813' of 8 5/8" casing. Shot two holes at 1785. The anhy shot two holes at  
Dakota 1030'. Ordered out 50 sks common cement and 200 sks 65/35 poz 10% gel.  
8 5/8 was cemented to surface and would not take cement. Ran tubing to 2113'.

Plugging Proposal Received by Gilbert Balthazor (TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 6:15 Day: 11 Month: May Year: 19 90

ACTUAL PLUGGING REPORT Pumped down tubing 50 sks 65/35 poz 10% gel w/50 hulls, followed  
w/50 sks common cement w/50 lbs hulls. Pulled tubing to 1100' and pumped down  
tubing. 70 sks 65/35 poz 10% gel w/150 lbs. hulls. Circ to surf. Pulled all tubing  
and pumped down 5 1/2 casing 15 sks 65/35 poz 10% gel cement to max pres of 500 lbs.  
Shut in pres 350 lbs.

Remarks: 90 By Halliburton  
If additional description is necessary, use BACK of this form.)

INVOICED

DATE 6-5-90

INV. NO. 28329

Signed Gilbert Balthazor (TECHNICIAN)