TO:

STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING

130 SOUTH MARKET, SUITE 2078

WICHITA, KANSAS 67202

Operator License No.: 5091

Op Name: HOWELL OIL COMPANY, INC.

Address: 2400 RIVERBIRCH RD

HUTCHINSON, KS 67502

API Well Number: 15-155-20841-00-00

Spot: NWNESW

Sec/Twnshp/Rge: 13-23S-4W

2334 feet from S Section Line,

3672 feet from E Section Line

Lease Name: SABIN

Well #: 1

County: RENO

Total Vertical Depth: 3825 feet

String Size		Pulled (ft)	Comment	,	
CIBP	3300				
CIBP	3335	0	KCC PG		
CIBP	3360	Y	nofer	1011	721
PROD 5.5	3788 é	3600,	110 SX	104	-01
SURF 8.625	602		150 SX		***************************************

Well Type: OIL

UIC Docket No:

**Date/Time to Plug:** 09/25/2007 1:00 PM

Plug Co. License No.: 31529

Plug Co. Name: MIKE'S TESTING & SALVAGE, INC.

Company: HOWELL OIL COMPANY, INC.

Phone: (620) 664-0597

Plugging Method:

Proposed Sand to 3,210' & top with 5 sxs. cement. Ripe 5 1/2" casing & pull to 730'. Circulate cement from 730' to surface.

Plugging Proposal Received By: B. J. HOPE.

Proposal Rcvd. from: LARRY RESSLER

WitnessType: PARTIAL

Date/Time Plugging Completed: 09/25/2007 5:30 PM

KCC Agent: MICHAEL WILSON

**Actual Plugging Report:** 

Sanded to 3,200' & topped with 5 sxs. cement. Ripped 5 1/2" casing @ 2,500'. Pulled casing to 714' & circulated 150 sxs. cement to the surface. Cement fell 100'. Topped off plug with 50 sxs. cement on 10/1/2007- cement at surface.

	_	
$\sim$	me	

Тор	Bot	Thru	Comments
3337	3341		
3314	3324		
3262	3266		

OCT 16 2007

CONSERVATION DIVISION WICHITA, KS

RECEIVED KANSAS CORPORATION COMMISSION

Remarks:

USED 60/40 POSMIX W/4% GEL BY COPELAND ACID & CEMENT. INVOICE #32581 & #32584.

Plugged through: CSG

District: 02

Signed Mechael Revil

(TECHNICIAN)

Form CP-2/3