

15-065-02907-00-00

10-14 4-060593

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15- - 5-23-50

SW SE SW /4 SEC. 17, 09 S, 21 W
330 feet from S section line
3630 feet from E section line

Operator license# 5363

Lease Cooley "A" well # 7

Operator: Berexco, Inc.

County Graham

Address: P.O. Box 723
Hays, Kansas 67601

Well total depth 3817 feet
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 170 feet

124.05

Aband. oil well X, Gas well , Input well , SWD , D & A

Plugging contractor: Co Tools License#

Address:

Company to plug at: Hour: 12:30P.M Day: 14 Month: October Year: 94

Plugging proposal received from: Bob Grant

Company: Berexco, Inc. Phone: 913-628-6101

Were: Order 350 sxs. 60/40 posmix - 10% gel and hulls.
Plug through tubing.
Squeezed at 1402' w/130 sxs. - at 1465' w/280 sxs.
Numerous holes in casing. Decision to P&A.

Plugging Proposal Received by: Herb Deines
Plugging operations attended by agent? All[X], Part[], None[]

Completed: Hour: 2:30P.M., Day: 14, Month: October, Year: 94

Actual plugging report: 8 5/8" to 170' w/170 sxs. 5 1/2" to 3810' w/75
sxs. Perfs. at 200' - 1050' - 1800'. Ran tubing to 3407' and pumped
75 sxs. cement with 100# hulls. Pulled tubing to 2404' and pumped
75 sxs. cement with 100# hulls. Pulled tubing to 1401' and circulated
cement with 90 sxs. w/100# hulls. Pulled tubing. Tied onto production
casing and pumped 60 sxs. cement with cement to surface up annulus.
Minimal pressure due to poor casing.

Remarks: Allied Cementing.
Condition of casing(in hole): GOOD BAD X Anhy.plug: YES X NO
Bottom plug(in place): YES X, CALC , NO Dakota plug: YES X, NO
Plugged through TUBING X, CASING . Elevation: 2301 GL

I did X observe the plugging.

Herb Deines

DA (agent)

Form CP-2/3

10/27/94
OCT 27 1994

INVOICED
DATE 11-2-94
INV. NO. 41556