

4 060069

3-14 15-065-01487-00-01 111

R

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 12-28-43  
SW SW NW, SEC. 23, T 9 S, R 21 ~~W~~

TECHNICIAN'S PLUGGING REPORT

2970 feet from S section line  
4950 feet from E section line

Operator License # 5229

Lease Name Putnam Inv. "A" Well # 2

Operator: Phillips Petroleum Company

County Graham 123.96

Name & Address Rt. 3 Box 20-A

Well Total Depth 3814 feet

Great Bend, KS 67530

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 10 3/4 feet 239

Abandoned Oil Well XXXXXX Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Co Tools License Number \_\_\_\_\_

Address \_\_\_\_\_

Company to plug at: Hour: 10:00AM Day: 14 Month: March Year: 19 90

Plugging proposal received from A.M. Wardell

(company name) Phillips Petroleum Company (phone) 913-434-4638

were: Order 480 sxs. 65/35 pos 10% gel and hulls.

Perf. at 1715' and 1035' with 2 shots each.

Plugging Proposal Received by Herb Deines  
(TECHNICIAN)

Plugging Operations attended by Agent?: All XXXXXXXXXX Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 11:00AM Day: 14 Month: March Year: 19 90

ACTUAL PLUGGING REPORT 10 3/4" set to 239'; 6" set to 3806'. Tied onto 6" casing and pumped

cement until it circulated to surface from the annulus. Shut in annulus and pumped a  
total of 480 sxs. 65/35 pos 10% gel and 300# hulls. Max press. 650# SIP 150#.

3-26-90  
MAR 26 1990

Remarks: Halliburton Cementing  
(If additional description is necessary, use BACK of this form.)

INVOICED  
(If XXXXXX observe this plugging.

DATE 3-28-90

INV. NO. 27754

*Hil.S.*

Signed Herb Deines  
(TECHNICIAN)

Herb Deines