

6-25

4-090562

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API number: 15-065-22,786 -00-00

NE NE SW \_\_\_\_\_ /4 SEC. 30, 09 S, 21 W  
2310 \_\_\_\_\_ feet from S section line  
2970 \_\_\_\_\_ feet from E section line

Operator license# 6622

Lease: Smith "D" Well # 3

Operator: Jason Oil Company

County: Graham 127.95

Address: P.O. Box 701  
Russell, Kansas 67665

Well total depth 3937 feet  
Conductor Pipe: 0 inch @ 0 feet  
Surface pipe 8% Inch @ 205 feet

Aband. oil well \_\_\_\_\_, Gas well \_\_\_\_\_, Input well \_\_\_\_\_, SWD \_\_\_\_\_, D & A

Plugging contractor: Discovery Drilling, Inc. License# 31548

Address: Hays, Kansas 67601

Company to plug at: Hour: P.M. Day: 24 Month: June Year: 1997

Plugging proposal received from: Tom Alm

Company: Discovery Drilling, Inc. Phone: -

Were: Order 215 sxs 60/40 posmix - 6% gel.  
Spot all plugs through drill pipe with heavy mud between all plugs.

7/7/97  
RECEIVED  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION

Plugging Proposal Received by: Ed Schumacher

Plugging operations attended by agent? All[ ], Part[ ], None[ X ]

Completed: Hour: 9:15 A.M., Day: 25, Month: June, Year: 1997

Actual plugging report:

- 1st. Plug at 3875' w/20 sxs cement.
- 2nd. Plug at 1860' w/20 sxs cement.
- 3rd. Plug at 1080 w/100 sxs cement.
- 4rd. Plug at 255' w/40 sxs cement.
- 5th. Plug at 40' w/10 sxs cement.
- 15 sxs in rathole.
- 10 sxs in mousehole.
- Arbuckle - Yes - Anhydrite 1842'.

Remarks: Allied Cementing.

Condition of casing(in hole): GOOD \_\_\_\_\_ BAD \_\_\_\_\_ Anhy.plug: YES  NO \_\_\_\_\_  
Bottom plug(in place): YES \_\_\_\_\_, CALC \_\_\_\_\_, NO \_\_\_\_\_ Dakota plug: YES  NO \_\_\_\_\_  
Plugged through TUBING \_\_\_\_\_, CASING \_\_\_\_\_ Elevation: 2352 GL

I did [ ] / did not [ X ] observe the plugging.

Ed Schumacher  
(agent)

INVOICED  
DATE 7-9-97  
INV. NO. 48517  
6-25