

7-11 15-065-03003-00-00

4-041699

API number: 15- - 1956

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

NW SW SE /4 SEC. 14, 09 S, 22 W
990 feet from S section line
2310 feet from E section line

Operator license# 5310

Lease: Sandzen Well # 5

Operator: Four-Way Operating, Inc.

County: Graham 125.48

Address: Box 698
Great Bend, Kansas 67530

Well total depth 3861 feet
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8% Inch @ 255 feet
W/175 sxs.

Aband. oil well X, Gas well, Input well, SWD, D & A

Plugging contractor: Halliburton Cementing License# -

Address: Oberlin, Kansas 67749

Company to plug at: Hour: 8:30A.M. Day: 11 Month: July Year 1995

Plugging proposal received from: Jim Rockhold

Company: Four-Way Operating, Inc. Phone:

Were: 5 1/2" casing set at 3852' w/150 sxs cement. Perf at 3561' - 3628'
Anhy. @ 1830' - Dakota @ 1060' - Squeeze at 2693' w/200 sxs. - at 1248' w/275 sxs. - at 1202'
w/225 sxs.
Ordered 400 sxs. 60/40 pozmix - 10% gel with 1/4# F.C. plus 500# hulls.

RECEIVED
STATE CORPORATION COMMISSION
7/27/95
JUL 27 1995

Plugging Proposal Received by: Dennis L. Hamel
Plugging operations attended by agent? All [X], Part [], None []

CONSERVATION DIVISION
WICHITA, KANSAS

Completed: Hour: 2:30 P.M., Day: 11, Month: July, Year: 1995

Actual plugging report: Perf anhy and dakota on July 10, 1995. R.I.H. with tubing to 1900'.
Spotted 300 sxs cement with 400# hulls to circulate at surface. P.O.O.H. with tubing. Hook-
up to 5 1/2" casing - spotted 40 sxs cement. Max. P.S.I. 300#. S.I.P. 200#. Hooked-up to
8 5/8" S.P. Squeezed 60 sxs cement with 100# hulls. Max. P.S.I. 300#. S.I.P. 200#.

Remarks:
Condition of casing(in hole): GOOD X BAD
Bottom plug(in place): YES X, CALC X, NO
Plugged through TUBING X, CASING. Elevation: GL

Dennis L. Hamel
(agent)

INVOICED

DATE 7-31-95
INV. NO. 43220

I did [X] did not [] observe the plugging.