

STATE OF KANSAS  
STATE CORPORATION COMMISSION

Give All Information Completely  
Make Required Affidavit  
Mail or Deliver Report to:  
Conservation Division  
State Corporation Commission  
211 No. Broadway  
Wichita, Kansas

15-163-19053-00-00

WELL PLUGGING RECORD

NORTH


Locate well correctly on above  
Section Plat

Rooks County. Sec. 4 Twp. 9 Rge. 19 (E) (W)  
Location as "NE/CNW/SW" or footage from lines \_\_\_\_\_  
Lease Owner Morgenstern & Specter  
Lease Name Frank Rostocil Well No. 5  
Office Address Russell, Kansas  
Character of Well (completed as Oil, Gas or Dry Hole) \_\_\_\_\_  
Date well completed 3-18-49 19\_\_\_\_\_  
Application for plugging filed June 25, 1961 19\_\_\_\_\_  
Application for plugging approved June 26, 1961 19\_\_\_\_\_  
Plugging commenced 6/23/1961 19\_\_\_\_\_  
Plugging completed 6/28/1961 19\_\_\_\_\_  
Reason for abandonment of well or producing formation failure to produce profitably  
If a producing well is abandoned, date of last production \_\_\_\_\_ 19\_\_\_\_\_  
Was permission obtained from the Conservation Division or its agents before plugging was commenced? yes

Name of Conservation Agent who supervised plugging of this well Eldon Petty Hays, Kansas  
Producing formation arbuckle Depth to top 3442 Bottom 3244 Total Depth of Well 3446 Feet  
Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

FORMATION	CONTENT	FROM	TO	SIZE	PUT IN	PULLED OUT
				8 5/8		none
				5 1/2		2600 ft
				13 3/8		none

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from \_\_\_\_\_ feet to \_\_\_\_\_ feet for each plug set.

Sanded back to 3100 feet. Dumped 4 sacks cement.  
Circulated mud at 500 feet. Pumped 20 sacks cement.  
Pumped 20 sacks cement at 180 feet.  
Set a rock bridge at 40 feet. Dumped ten sacks cement.

RECEIVED  
STATE CORPORATION COMMISSION  
7/21/61  
JUL 24 1961  
CONSERVATION DIVISION  
Wichita, Kansas

(If additional description is necessary, use BACK of this sheet)  
Name of Plugging Contractor Lynch Casing Pulling Company No. 457  
Address R. Rt. 4 Great Bend, Kansas

STATE OF Kansas, COUNTY OF Russell, ss.  
Morgenstern-Specter, Inc. (employee of owner) or (owner or operator) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) Morgenstern

(Address)

SUBSCRIBED AND SWORN TO before me this 12th day of July, 1961

My commission expires Dec. 1, 1964

Elsie Coady  
Elsie Coady Notary Public.




15-163-19053-00-00

Company - SKELLY OIL CO.  
Farm - Frank Rostocil No. 5

SEC. 4 T. 9 R. 19W  
SE SE NW  
330' fr EL, 330' fr SL NW/4

Total Depth. 3446  
Comm. 2-19-49 Comp. 3-18-49  
Shot or Treated. Acid  
Contractor. Claude Wentworth  
Issued. 7-16-49

County. Rooks  
KANSAS



Elevation. \_\_\_\_\_

Production. Pot. 140 BO, no wtr.

CASING:

13 3/8" 215' cem w/200 sx.  
8 5/8" 1453' Cem w/925 sx.  
5 1/2" 3470' cem w/200 sx.

Figures Indicate Bottom of Formations.

surface soil	10
sand, clay	40
shale, shells	215
Drilled 17-1/2" hole	
shale	885
shale, sand	1130
shale, shells	1400
shale red, lime	1430
shale, shells	1450
anhydrite	1480
shale	1640
lime, shale	1885
shale	1930
lime, shale	2185
shale	2295
lime	2450
shale	2490
lime, shale	2635
shale	2835
lime, shale	3065
lime	3390
lime, shale	3443
dolomite, coarsely xlyn. RTD	3447

Correction:

3447' SLM Rotary table  
equals 3445' SLM Derrick floor.

SLM	3445
dolo. brwn xlyn	3446
Total Depth	

Tops:

Heebner shale	3161
Toronto lime	3180
Lansing lime	3200
Arbuckle lime	3442 SLM

ACID:

3-18-49, 200 gals, between 3443-3446  
by Dowell.

Production: Initial Prod. before shot  
or acid, 120' OIH in 4 hrs.  
24 Hr SCC Pot. 140 barrels oil, no water.

Producing Formation: Arbuckle lime 3443-3446'.

REMARKS:

3180-86, Slight spotted stain.  
3276-79, Light scattered saturation.  
3441-45, good por. and saturation.  
3445-46, Fair porosity and saturation.  
Ran Schlumberger survey at 3447.