KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

WELL PLUGGING APPLICATION

Please TYPE Form and File ONE Copy

Form CP-1 September 2003 This Form must be Typed Form must be Signed All blanks must be Filled

Well Operator: Black Star 231 Corp		vaa :	f===== #:		
Address: 2300 Main, Suite 900		KCC License #:(Operator's) City: Kansas City			
				560 720	1 0
	Zip Code: 64108				
	Well #:_3		Twp. 27	S. R. <u>9</u>	V East We
ne - nw - sw - ne	_Spot Location / QQQQ C	ounty: Greenwood	······································		
900 Feet (in exact footage) From	✓ North / South (from	nearest outside section corr	er) Line of S	Section (Not Lea	se Line)
1500 Feet (in exact footage) From	✓ East / West (from	nearest outside section corr	er) Line of S	Section (Not Lea	se Line)
Check One: Oil Well Gas Well	✓ D&A Cathodic	Water Supply Well			
SWD Docket #	ENHR Docket #			ther:	
Conductor Casing Size:	Set at:	Cemente	ed with:		Sack
Surface Casing Size: 8 5/8"	Set at: 41'	Cemente	ed with: 40		Sack
Production Casing Size: d&a	Set at:	Cemente	ed with:		Sack
ist (ALL) Perforations and Bridgeplug Sets:0-					
ondition of Well:	ge if additional space is needed):	Junk in Hole	((Stone Corral Forma	,
Condition of Well: ✓ Good Poor Proposed Method of Plugging (attach a separate page drill pipe as follows; 15 sxs @ 2221', 15 sxs (s Well Log attached to this application as required?	Casing Leak ge if additional space is needed): C @ 786', and 90 sxs 250' to surf	Junk in Hole Firculate hole clean with Face.	(,
- Personal Promotory	Casing Leak ge if additional space is needed): C @ 786', and 90 sxs 250' to surf	Junk in Hole Firculate hole clean with Face.	(,
Condition of Well:	Casing Leak Ge if additional space is needed): C 786', and 90 sxs 250' to surf	Junk in Hole irculate hole clean with face. filed? Yes No	heavy drilli	ing mud. Place	cement plugs thru
roposed Method of Plugging (attach a separate pagdrill pipe as follows; 15 sxs @ 2221', 15 sxs @ Well Log attached to this application as required; not explain why?	Casing Leak Ge if additional space is needed): C 786', and 90 sxs 250' to surf Yes No Is ACO-1 with K.S.A. 55-101 et. seq. and	Junk in Hole irculate hole clean with face. filed? Yes No	heavy drilli	ing mud. Place	cement plugs thru
roposed Method of Plugging (attach a separate pagdrill pipe as follows; 15 sxs @ 2221', 15 sxs (as Well Log attached to this application as required? not explain why?	Casing Leak Ge if additional space is needed): C 786', and 90 sxs 250' to surf Yes No Is ACO-1 with K.S.A. 55-101 et. seq. and	Junk in Hole irculate hole clean with face. filed? Yes No	heavy drilli	ing mud. Place	cement plugs thru
roposed Method of Plugging (attach a separate page drill pipe as follows; 15 sxs @ 2221', 15 s	Casing Leak Ge if additional space is needed): C 786', and 90 sxs 250' to surf Yes No Is ACO-1 with K.S.A. 55-101 et. seq. and	Junk in Hole irculate hole clean with face. filed? Yes No the Rules and Regulation ations: David Farthing	heavy drilli	ing mud. Place	cement plugs thru
roposed Method of Plugging (attach a separate page drill pipe as follows; 15 sxs @ 2221', 15 s	Casing Leak ge if additional space is needed): C 786', and 90 sxs 250' to surf Yes No Is ACO-1 with K.S.A. 55-101 et. seq. and to be in charge of plugging opera	Junk in Hole irculate hole clean with ace. filed?	ns of the St	ing mud. Place	cement plugs thru
roposed Method of Plugging (attach a separate page drill pipe as follows; 15 sxs @ 2221', 15 s	Casing Leak Ge if additional space is needed): C 786', and 90 sxs 250' to surf Yes No Is ACO-1 with K.S.A. 55-101 et. seq. and to be in charge of plugging operations.	Junk in Hole irculate hole clean with ace. filed?	ns of the St	ing mud. Place	cement plugs thru
roposed Method of Plugging (attach a separate page drill pipe as follows; 15 sxs @ 2221', 15 s	Casing Leak Ge if additional space is needed): C 786', and 90 sxs 250' to surf Yes No Is ACO-1 with K.S.A. 55-101 et. seq. and to be in charge of plugging operations ice Company Name	Junk in Hole irculate hole clean with face. filed? Yes No the Rules and Regulation ations: Phone: (620	ns of the St	ing mud. Place tate Corporatio - 4548	cement plugs thru
Proposed Method of Plugging (attach a separate page drill pipe as follows; 15 sxs @ 2221', 15 sxs (as Well Log attached to this application as required? In not explain why? Ilugging of this Well will be done in accordance ist Name of Company Representative authorized ist Name of Company Represent	Casing Leak Ge if additional space is needed): C 786', and 90 sxs 250' to surf Yes No Is ACO-1 with K.S.A. 55-101 et. seq. and to be in charge of plugging operations ice Company Name November 19th, 2007 @ 6:00	Junk in Hole irculate hole clean with face. filed? Yes No the Rules and Regulation ations: David Farthing	ns of the St	tate Corporation - 4548	n Commission.
Condition of Well:	Casing Leak ge if additional space is needed): C 786', and 90 sxs 250' to surf Yes No Is ACO-1 with K.S.A. 55-101 et. seq. and to be in charge of plugging operation ice company Name) November 19th, 2007 @ 6:00	Junk in Hole irculate hole clean with face. filed? Yes No the Rules and Regulation ations: David Farthing	ns of the St	tate Corporation - 4548	n Commission.