

6 030861

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 065-20,881-00-00 ¹²

NW SE SW, SEC. 2, T 8 S, R 23 W/E
990 feet from S section line
3639 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 6234

Lease Name Montgomery Well # 2

Operator: The Maurice L. Brown Co

County Graham 121.88

Name & Address: 200 Sutton Place Bldg.

Well Total Depth 3750 feet

Wichita, Kansas 67202

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 251'

Abandoned Oil Well Gas Well Input Well SWD Well D&A

Other well as hereinafter indicated

Plugging Contractor Halliburton Services License Number

Address Oberlin, Ks.

Company to plug at: Hour: P.M Day: 19 Month: March Year: 19 87

Plugging proposal received from Al McFarlane, Don Butcher

(company name) K.G.S. K.C.C. (phone)

were: Order 115 sx 65/35 pox 10% gel 2% Diced Econolite Mix. Cement with 5 sx hulls.
Halliburton Services, John Keith Water Trucks. Mix and pump down 8 5/8 46 bbl cement slurry of 5 sx hulls followed w/wiper plug and 46 bbl fresh water. Spot W.P. @ 1850' from surface. Leave top of hole for monitor well of Dakota

Plugging Proposal Received by Carl Goodrow (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None

Operations Completed: Hour: 4: P.M. Day: 19 Month: March Year: 19 87

ACTUAL PLUGGING REPORT 8 5/8" set at 251' w/190 sks 5 1/2" set at 3747' w/200 sks.

Top perf. at 3548' plugged bottom w/100 sks cement, to 1250' shot pipe NA time & recovered NA. Pumped in NA. D.V. tool @ 1903 CWC to surface. Mixed and pumped 63 bbl cement slurry w/5 sx hulls pushed W.P. to 1250' Pressured to 2800 # PSI Closed in @ 2800 # PST.

STATE CORPORATION COMMISSION
APR 17 1987
CONSERVATION DIVISION
Wichita, Kansas

Remarks: (If additional description is necessary, use BACK of this form.)

INVOICED

DATE 4-21-87

Signed Carl Goodrow (TECHNICIAN)

INV. NO. 16598

Carl Goodrow

3-19

MAY 14 1987

JUL 08 1987