8-11

4-031847

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15-065-21,403 - 00-00

NW SW SE /4 SEC. 06, 08 S, 23 W
990 feet from S section line
2310 feet from E section line

Operator license# 5430

Lease Justus-Wyatt well # 1

Operator: Energy Three, Inc.

County Graham

Address: P.O. Box 1505
Great Bend, Kansas 67530

Well total depth 3780 feet 122.85
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 252 feet

Aband. oil well X, Gas well ___, Input well ___, SWD ___, D & A ___

Plugging contractor: Kelso Casing Pulling, Inc. License# 6050

Address: Chase, Kansas 67524

Company to plug at: Hour: P.M. Day: 11 Month: August Year: 93

Plugging proposal received from: Dave

Company: Kelso Casing Pulling, Inc. Phone: ___

Were: Order 225 sxs. 65/35 pozmix - 10% gel. - 500# Hulls.
Allied Cement Company. Sand and common cement.

Plugging Proposal Received by: Carl Goodrow
Plugging operations attended by agent? All[X], Part[ ], None[ ]

Completed: Hour: 2:00P.M., Day: 11, Month: August, Year: 93

Actual plugging report: 8 5/8" set @ 252' w/200 sxs. 4 1/2" set @ 3779' w/125 sxs. PBTD 3753'. Perfs. 3703' - 3707'. Sand back to 3650' w/4 sxs. common cement on sand with bailer. Shots @ 2500' - 1900' - 1150'. Recovered 1150' of 4 1/2" casing. Mixed and pumped 100 sxs. cement from 1200' to 2500' w/400# P.S.I. Mixed and pumped 75 sxs. @ 1250'. Pulled 4 1/2" to 300' circulated 40 sxs. to surface. Laid down 4 1/2" topped off 8 5/8" with 10 sxs. cement blend into cellar. Plug complete.

RECEIVED
STATE CORPORATION COMMISSION
8-30-1993
AUG 30 1993
CONSERVATION DIVISION
Wichita, Kansas

Remarks:
Condition of casing(in hole): GOOD X BAD ___ Anhy.plug: YES X NO ___
Bottom plug(in place): YES X, CALC ___, NO ___ Dakota plug: YES X, NO ___
Plugged through TUBING ___, CASING X. Elevation: ___ GL

I did [X] did not [ ] observe the plugging. Carl Goodrow

(agent)

INVOICED
DATE 8-30-93
INV. NO. 38508

HD

Form CP-2/3