

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-163-21981-00-00
Spot: S2NWNENE Sec/Twnshp/Rge: 21-7S-19W
3190 feet from N Section Line, 990 feet from E Section Line
Lease Name: SCHNEIDER Well #: 6
County: ROOKS Total Vertical Depth: 3464 feet

Operator License No.: 32819
Op Name: BAIRD OIL COMPANY LLC
Address: 113 W MAIN PO BOX 428
LOGAN, KS 67646

String	Size	Depth (ft)	Pulled (ft)	Comments
PROD	4.5	3456	0	235 SX
SURF	8.625	208	0	160 SX

112.58

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 01/28/2008 9:00 AM
Plug Co. License No.: 32382 Plug Co. Name: SWIFT SERVICES, INC.
Proposal Rcvd. from: ANDREW NOONE Company: BAIRD OIL COMPANY LLC Phone: (785) 689-7456

Proposed Plugging Method: Ordered 255 sxs 60/40 pozmix - 4% gel - 800# hulls - 10 sxs gel spacer. Perf 1500' and 900'.

Plugging Proposal Received By: HERB DEINES Witness Type: COMPLETE (100%)
Date/Time Plugging Completed: 01/28/2008 11:00 AM KCC Agent: PAT BEDORE

Actual Plugging Report:

Swift Services hooked onto 4 1/2" casing - pumped 50 sxs 60/40 pozmix - 4% gel with 300# hulls.
Pumped 10 sxs gel with 100# hulls.
Pumped 10 sxs cement down the annulus.
Hooked back up to 4 1/2" and pumped 140 sxs cement with 300# hulls.

Perfs:

Top	Bot	Thru	Comments
3168	3368		

INVOICED
DATE 2-12-08
INV. NO. 2008061187

RECEIVED
KANSAS CORPORATION COMMISSION
FEB 07 2008

Remarks: SWIFT SERVICES, INC.

Plugged through: CSG

District: 04

PD.

Signed

Pat Bedore

(TECHNICIAN)

Form CP-2/3

JAN 30 2008

[Handwritten signature]

REPLACEMENT CARD


BAIRD OIL COMPANY
 BOX 428
 LOGAN, KS 67646
 CONTR

#6 SCHNEIDER

21-7-19W
 550' FNI &
 990' FEL, SE/4

ABERCROMBIE DRILLING, INC. CTY ROOKS

GEOL _____ FIELD GROVER WEST



ELV 1977 KB SPD 4/8/83 CARD ISSUED 5/19/83 IP P 15 BO & 10 BWPD
 1972 GL LKC 3168-3368 OA

LOG	Tops	Depth Datum	API 15-163-21,981
ANH	1476 + 501		8 5/8 " 208 / 160SX, 4 1/2 " 3456 ' 235SX
B ANH	1510 + 467		DST (1) 3162-3213 (LKC) / 30-45-60-45. 440' GIP, REC 180'
TOP	2926- 949		GSY CL OIL, 207' OIL SPKD MDY WTR, SIP 1215-1160#, FP 82-124 / 138-220#
HEEB	3125-1148		DST (2) 3280-3312 (LKC) / 30-30-30-30, REC 5' OIL SPTD MUD, SIP 649-469#, FP 69-69 / 69-69#
TOR	3148-1171		DST (3) 3308-3330 (LKC) / 45-45-30-45, REC 20' MUD, W LIGHT FILM OF OIL, SIP 814-814#, FP 55-55 / 55-55#
LANS	3165-1188		DST (4) 3328-3354 (LKC) / 45-45-30-45, REC 65' OIL SPTD MUD, SIP 138-220#, FP 82-82 / 82-82#
BKC	3389-1412		DST (5) 3348-3377 (LKC) / 45-45-30-45, REC 5' MUD, SIP 55-55#, FP 55-55 / 55-55#
ARB	ABSENT		
GOR	3457-1480		
LTD	3436-1459		
RTD	3464-1487		

DST (6) 3424-3437 (PENN) 45-45-30-45, REC 5' MUD, W FEW OIL SPKS IN TOOL, SIP 41-41#, FP 41-41 41-41#

MICT - CO, PF (LKC) 3364-68, W 2 SPF, AC 500G (28%) & 1500G (15%) & 6 BBLS OVERFLUSH, SWB DWN, SO, PF (LKC) 3342-48, W 2 SPF, AC 500G (28%) & 2000G (15%) & 6 BBLS OVERFLUSH, SWB DWN, SO, PF (LKC) 1 3330 & 1 3323.5, AC 500G (28%) & 2000G (15%) & 6 BBLS OVERFLUSH, SWB DWN, SO, PF (LKC) 3302-04, W 3 SPF, AC 500G (28%) & 1500G (15%) & 6 BBLS OVERFLUSH, SWB DWN, SO, PF (LKC) 1/3170, RE-PF (LKC) 3328-32 & 3325-28, W 3 SPF, SWB DWN, SO, NAT, POP, P 15 BO & 10 BWPD, (GR 33²), 4/27/83