

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-163-22002-00-00
Spot: NENESE Sec/Twnshp/Rge: 19-7S-19W
2310 feet from S Section Line, 330 feet from E Section Line
Lease Name: SCHOELLER Well #: 5
County: ROOKS Total Vertical Depth: 3456 feet

Operator License No.: 32819
Op Name: BAIRD OIL COMPANY LLC
Address: 113 W MAIN PO BOX 428
LOGAN, KS 67646

String	Size	Depth (ft)	Pulled (ft)	Comments
PROD	5.5	3451	0	250 SX
SURF	8.625	208	0	160 SX

11232

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 01/29/2008 8:00 AM
Plug Co. License No.: 32382 Plug Co. Name: SWIFT SERVICES, INC.
Proposal Rcvd. from: ANDREW NOONE Company: BAIRD OIL COMPANY LLC Phone: (785) 689-7456

Proposed Plugging Method: Ordered 295 sxs 60/40 pozmix - 4% gel - 800# hulls -17 sxs gel spacer.
Perf 1550' and 925'.

Plugging Proposal Received By: HERB DEINES Witness Type: COMPLETE (100%)
Date/Time Plugging Completed: 01/29/2008 12:30 PM KCC Agent: PAT BEDORE

Actual Plugging Report:

Swift Services hooked onto 5 1/2" casing and pumped 40 sxs 60/40 pozmix - 4% gel with 150# hulls.
Pumped 17 sxs gel with 550# hulls.
Pumped 150 sxs cement.
Pumped 70 sxs cement down annulus.
Topped with 90 sxs cement.
Pumped 5 sxs down annulus to top off.

Perfs:

INVOICED
DATE 2-12-08
INV. NO. 2008061187

RECEIVED
KANSAS CORPORATION COMMISSION

FEB 07 2008

CONSERVATION DIVISION
WICHITA, KS

Remarks: SWIFT SERVICES, INC.

Plugged through: CSG

District: 04

Signed

Pat Bedore
(TECHNICIAN)

110-


Handwritten initials/signature

BAIRD OIL COMPANY
 BOX 7
 LOGAN, KS 67646

REPLACEMENT CARD
 #5 SCHOELLER
 19-7-19W
 NE NE SE

CONTR ABERCROMBIE DRILLING, INC. CTY ROOKS

GEOL _____ FIELD VALLEY VIEW



ELV 2005 KB SPD 4/15/83 CARD ISSUED 5/19/83 W P 45 80 & 122 BWPD
 2000 GL LKC 3328-3332
 API 15-163-22,002 ARB 3448-3494 OA

LOG	Tops	Depth/Datum	
ANH	1516+	489	8 5/8" 208/160SX, 5 1/2" 3451/250SX
BV ANH	1549+	456	DST (1) 3148-90 (SHAW) / 30-30-30-30, REC 5' M, W/ SPKS OIL ON TOP OF TOOL, SIP 81-71#, FP 51-51 / 51-51#
TOP	2956-	951	DST (2) 3309-41 (LKC) / 30-45-45-45, 110' GIP, REC 15' FO, 55' SMC0, SIP 602-592#, FP 61-61 / 61-61#
HEEB	3158-	1153	DST (3) 3337-59 (LKC) / 45-45-0-0, REC 6 INCHES FO, 15' OCM, 15' HOCM, ISIP 40#, IFP 40-40#
TOR	3184-	1179	DST (4) 3335-80 (LKC) / 30-45-30-45, REC 10' SOC0M, SIP 91-61#, FP 40-40 / 40-40#
LANS	3200-	1195	DST (5) 3374-3400 (LKC) / 45-45-30-45, REC 5' CL OIL, 20' HOCM, SIP 807-503#, FP 51-51 / 51-51#
SEV SH	3316-	1311	DST (6) 3439-55 (ARB) / 30-45-60-45, 1022' GIP, REC 868' CL GSY OIL, 154' MW, SIP 602-592#, FP 81-234 / 295-397#
BKC	3400-	1395	(over)
ARB	3449-	1444	
RTD	3455-	1450	
LTD	3456-	1451	

MICT - CO, PF (ARB) 3390-94, W/ 3 SPF, AC 500G (28%) & 1500G (15%) & 6 BBLS OVERFLUSH, SWB DWN, GSO, PF (ARB) 3368-72, W/ 3 SPF, AC 500G (28%) & 1500G (15%) & 6 BBLS OVERFLUSH, SWB DWN, SO, PF (ARB) 3348-50, W/ 3 SPF, AC 500G (28%) & 1500G (15%) & 6 BBLS OVERFLUSH, SWB DWN, GSO, PB (DEPTH NA), PF (LKC) 3328-32, W/ 3 SPF, AC 500G (28%) & 1500G (15%) & 6 BBLS OVERFLUSH, SWB DWN, GSO, POP, P 45 80 & 122 BWPD (GR 33) 5/4/83 - COMMINGLED