

state

15-173-00805-00-00

STATE OF KANSAS
STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
800 Bitting Building
Wichita, Kansas

Sedgwick County, Sec. 15 Twp. 26S Rge. 2 (E) (W)

Location as "NE/CNW $\frac{1}{4}$ SW $\frac{1}{4}$ " or footage from lines NE NE SE

Lease Owner Shell Oil Company

Lease Name K. F. FISHER Well No. 1

Office Address Box 744, Great Bend, Kansas

Character of Well (completed as Oil, Gas or Dry Hole) Oil

Date well completed June 23 1929

Application for plugging filed November 11 1950

Application for plugging approved November 14 1950

Plugging commenced November 29 1950

Plugging completed December 15 1950

Reason for abandonment of well or producing formation Oil Depleted

If a producing well is abandoned, date of last production November 7 1950

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well D. C. Lilley

Producing formation Simpson Depth to top 3242 Bottom Total Depth of Well 3338 PB Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Formation	Content	From	To	Size	Put In	Pulled Out
Viola	I.P. 408 oil & 0 wtr 24 hours, pump	3199	3202	16"	116'	None
				8 5/8"	3164'	2007'
				7"	3314	3170'
Simpson	I.P. 175 oil & 0 wtr 24 hours, pump	3326	3334			

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from...feet to...feet for each plug set.

Mudded shot hole from 3338 to 3312 & set plug. Cemented hole with 3 sax at 3312. Mudded hole to 2675. Cemented hole to 2665. Mudded hole to 150'. Set 15' rock bridge & cemented hole with 15 sax. Mudded hole to 15', set 10' rock bridge & capped with 5 sax cement to surface.

(If additional description is necessary, use BACK of this sheet)

Correspondence regarding this well should be addressed to Shell Oil Company
Address c/o S. S. Mabry, Box 744, Great Bend, Kansas

STATE OF KANSAS, COUNTY OF BARTON, ss.
S. S. Mabry (employee of owner)

being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) [Signature]

Box 744, Great Bend, Kansas (Address)

SUBSCRIBED AND SWORN to before me this 20th day of December, 1950.

My commission expires January 24, 1953

22-5133-s 9-48-10M

PLUGGING
FILE SEC 15 T 26 R 2E
BOOK PAGE 411 LINE 30

RECEIVED
STATE CORPORATION COMMISSION
12/21/50
DEC 21 1950
CONSERVATION DIVISION
Wichita, Kansas

SHELL-K. F. FISCHER #1
 NE NE SE Sec. 15-26S-2E
 Greenwich Field
 Sedgwick County, Kansas

Casing Record

0 - 5 surface rock
 75 shale & lime shells
 90 gravel
 92 lime rock
 106 gravel
 110 lime
 117 lime rock
 226 broken lime
 492 shale & shells
 875 shale & lime shells
 1035 shale & shells
 1195 shale & lime shells
 1215 lime
 1350 shale & shells
 1425 lime shells, sandy
 1440 shale
 1545 broken sand & lime
 1555 sand
 1580 shale
 1620 sandy lime & shells broken
 1650 hard sandy shale
 1680 sticky shale
 1725 broken lime
 1750 sandy lime broken
 1755 shale
 1805 shells
 1885 sandy shale
 1910 sticky shale
 1925 shale & lime shells
 2015 shale
 2050 sandy shale
 2100 lime & sand
 2120 sandy lime
 2140 sticky shale
 2180 hard shale & lime shells
 2200 sticky shale
 2255 hard shale
 2295 sticky shale
 2377 lime
 2380 shale
 2425 lime
 2455 shale
 2465 sticky shale
 2500 lime
 2508 shale & shells
 2518 lime
 2568 shale & shells

16" cem 116 w/ 75 sax
 8 5/8" cem 3164 w/ 650 sax
 7" cem 3314 w/ 30 sax

2580 gray shale & lime shells
 2605 lime 261
 2610 gray shale
 2635 lime
 2675 shale & shells
 2681 lime
 2695 lime & shale
 2710 lime
 2726 lime & some shale
 2723 SLC
 2750 lime shells, broken
 2770 shale
 2810 lime
 2840 shale
 2853 shale & shells
 2898 shale, red & green lime shells
 2930 lime & some shale
 2935 shale
 2993 lime & chat
 3010 lime & sand
 3022 hard lime
 2049 lime & sandy lime
 3055 sandy lime
 3113 lime
 3145 broken lime
 3170 slate
 3168 Cable Tool Measure
 3197 black shale
 3200 lime, soft
 3202 SLC
 3202 lime TD
 Drilled deeper:
 3242 lime
 3284 sand
 3310 sandy shale
 3312 shale, black
 3313 sandy shale
 3314 shale
 3316 sandy shale
 3318 sandy w/ green shale streaks
 3321 green sandy shale
 3324 green shale w/ thin sand streaks
 3326 green sandy shale
 3329 sand
 3332 1/2 sand w/ green shale
 3334 sand
 3336 sand, shaly
 3339 dolomite TD
 3359 dolomite TD (deepened)
 3338 PB

Formation Tops

Viola 3199
 3242 Simpson
 3340 Arbuckle

NOV 11 1950

PLUGGING

FILE SEC 15 T 26 S 2E

BOOY 41 LIME 30