

DISTRICT CONSERVATION AGENT'S REPORT

15-065-00363-00-00



TO:

State Corporation Commission  
Conservation Division  
800 Bitting Building  
Wichita, Kansas

FILE NO. \_\_\_\_\_

LOCATION SE SE SW

SEC. 13 TWP. 8 RGE. 25

Dry Hole x Abandoned Oil Well \_\_\_\_\_ Abandoned Gas Well \_\_\_\_\_

I have today completed supervision of plugging of:

Well No. 1 Lease Sand Bar American St. Pauls Bldg.

Operator S.A. Berwick Drg Co Address Great Bend, Kans

Field \_\_\_\_\_ County Graham

Total Depth 3854 Feet.

(Describe briefly the manner in which the well was plugged)

8 5/8" at 100' circulated with cement.

4 1/2" at 3006' with 135 sax cement behind - Top perforations at 3421'

Filled with sand to 3410', set 4 sax cement with dump bailer,

pulled approx 2000' 4 1/2", mudded hole to 160', set rock and 20

sax cement, mud to 35', set rock and 10 sax cement to bottom

cellar.

8-28-52

RECEIVED  
STATE CORPORATION COMMISSION

AUG 28 1952

CONSERVATION DIVISION  
Wichita, Kansas

[Signature]  
District Conservation Agent

Date 8-26-52

PLUGGING

FILE SEC 13 T 8 R 25  
BOOK PAGE 40 LINE 27