

6 020229

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-163 22 620-00-00  
N/2, SEC. 10, T. 10 S, R. 20 (W/E)  
1980 N feet from S section line  
1320 W feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5171  
Operator: T X O, Production Corp  
Name & Address: 200 W Douglas, Suite 300  
Wichita Ks, 67202

Lease Name Hickhouse "B" Well # 1  
County Rooks  
Well Total Depth 3850 <sup>125-13</sup> feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 259

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Mur Fin Drlg Co License Number 6033  
Address Wichita Ks

Company to plug at: Hour: 10:00 PM Day: 18 Month: Feb. Year: 19 85

Plugging proposal received from Alfred Augustine  
(company name) Mur Fin Drlg. (phone) 316-265-9441

were: Cir Heavy Mud + Pump Down, Drillstem 25, 5x @ 1740  
100 5x @ 980, 40 5x @ 260, 10 5x on Solid Bridge Ft. 40' 10 5x PK.  
KB 2945, Msp. 1575 Ashy 1699 to 1735 Arb. Nonv.  
50% Poz 6% Gel, 3% cc 2, 5x, Flo. Cell

Plugging Proposal Received by Jillbut Ballhagen  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 3:00 AM Day: 19 Month: Feb. Year: 19 85

ACTUAL PLUGGING REPORT Cir Heavy Mud, 10. min + Pumped down Drlg Stem  
25 5x @ 1740, 100. 5x @ 980, 40. 5x @ 260. 10 5x on Solid Bridge  
@ 40' 10. 5x in Rathelr. 50% Poz. 6% Gel. 3% cc 2 1/2 5x LMA Cel

Cemented By Dowel.

RECEIVED  
STATE CORPORATION COMMISSION  
03-04-1985  
MAR 04 1985

Remarks: \_\_\_\_\_  
(If additional description is necessary, CONSERVE BACK OF THIS FORM.)

INVOICED  
DATE 3-7-85  
INV. NO. 7260  
2-19

Signed Jillbut Ballhagen  
(TECHNICIAN) 2-28-84  
9