

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-179-20877-00-00
Spot: NWNE Sec/Twnshp/Rge: 11-10S-26W
4950 feet from S Section Line, 990 feet from E Section Line
Lease Name: BITTEL E Well #: 1
County: SHERIDAN Total Vertical Depth: 4070 feet

Operator License No.: 4058
Op Name: AMERICAN WARRIOR, INC.
Address: PO BOX 399
GARDEN CITY, KS 67846

String	Size	Depth (ft)	Pulled (ft)	Comments
PROD	5.5	4066	0	525 SX
SURF	8.625	207	0	150 SX

132.28

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 11/05/2007 10:00 AM
Plug Co. License No.: 6426 Plug Co. Name: EXPRESS WELL SERVICE & SUPPLY INC
Proposal Rcvd. from: JOE SMITH Company: AMERICAN WARRIOR, INC. Phone: (620) 272-1023

Proposed Plugging Method: Ordered 425 sxs 60/40 pozmix - 4% gel - 800# hulls.
Casing leak - high fluid level.

Plugging Proposal Received By: HERB DEINES WitnessType: COMPLETE (100%)
Date/Time Plugging Completed: 11/05/2007 2:00 PM KCC Agent: MARVIN MILLS

Actual Plugging Report:

Ran tubing to 2995' - pumped 85 sxs with 300# hulls.
Pulled tubing to 1900' - pumped 100 sxs with 200# hulls.
Pulled tubing to 1000' - pumped 100 sxs with 200# hulls - no circulation.
Pulled tubing to 500' - waited one hour - pumped 100 sxs - no circulation.
Pulled tubing out - filled from top with 40 sxs - topped off.
Tied onto backside - pumped 8 sxs cement.
Max. P.S.I. 200#. S.I.P. 200#.

Perfs:

Top	Bot	Thru	Comments
3939	3943		
3842	3846		
3829	3833		

INVOICED

DATE 11-14-07
INV. NO. 2008060750

RECEIVED
KANSAS CORPORATION COMMISSION

NOV 09 2007

Remarks: SWIFT CEMENTING COMPANY-TICKET #12927.

Plugged through: TBG

District: 04

Signed _____

(TECHNICIAN)

44117 SW
 44117 SW
 44117 SW

NO. 15-179-20.877
 COUNTY ABERCROMBIE CRILLING CITY SHERIDAN
 3801 WENDELL DEAN FIELD CLUSTER 389 BY
 (DRY HOLES)
 ESTABLISHED 11/15/88 CARD ISSUED 2/5/87 P 150 BOPD. TR WTR
 OPLG COMP 11/15/88 LKO 3829-3943 CA

+	+	+	+
+	+	+	+
+	+	+	+

LOG	Top	Depth	Datum
ANH		2174+	378
SIANH		2207+	340
TOP		3550-	1003
HEEB		3783-	1218
TOP		3784-	1237
LANS		3801-	1254
STARK		3892-	1445
BKC		4034-	1487
RTD		4370-	1523

API 15-179-20.877
 6 5/8 " 207 / 150 SX, 5 1/2 " 4066 / 525 SX
 NO CORES
 DST (1) 3764-3818 (TOR, LANS) / 15-30-60-120, 120' GIP, REC 65' OCM, 60' O & WCM, SIP 757-852#, FP 75-84 / 85-88#
 DST (2) 3818-3841 (LKC) / 15-30-60-120, 1620' GIP, REC 800' FREE GSY OIL, 120' O & OCM, SIP 641-862#, FP 107-118, 223-321#
 DST (3) 3842-3856 (LKC) / 15-30-60-120, 450' GIP, REC 466' FREE GSY OIL, 20' HOOM, SIP 1013-1013#, FP 128-112 / 168-190#
 DST (4) 3868-3894 (LKC) / 15-30-60-120, 180' GIP, REC 70' O & GCM, SIP 935-957#, FP 67-56 / 78-39#
 DST (5) 3920-3952 (LKC) / 15-30-60-120, 960' GIP, REC 360' FREE GSY OIL, 120' O & OCM, SIP 1157-1157#, FP 80-39 / 134-179#

COPYRIGHT 1985
 INDEPENDENT OIL & GAS SERVICE, INC.

(over)
 DST (6) 3954-3994 (LKC) / 15-30-60-30, REC 2, MIP, GIP, 56-56#, EP 56-56 / 56-56#
 MICT - CO. PF (LKC) 3939-3943, 3842-4846 & 3829-3833, W / 2 SPF, SWB 64.7 BF (5% WTR), AC (3939-3943) 250 GAL, SWB LD, LAST 2 PULLS 100% OIL, RE-AC (3939-3943) 1000 GAL, AC (3842-3836) 250 GAL, AC (3829-3833) 2250 GAL, STRADDLE PFS (3829-3833) & 3842-3846, SWB DWN, REC 37.26 BF (TR OIL), STRADDLE PFS (3939-3943), SWB DWN, REC 12 BW & 15 BO, LAST 2 PULLS NW, TST 3939-3943, SWB 28 BO, NW / 6 HRS, REC 15.74 BO (5% WTR) / LAST HR, TST ALL ZNS, SWB 14.78 BO & 14 BW / LAST HR, T&R, POP, P 150 BOPD, TR WTR 1/21/87