

STATE OF KANSAS  
STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

Give All Information Completely  
Make Required Affidavit  
Mail or Deliver Report to:  
Conservation Division  
State Corporation Commission  
212 North Market, Insurance Bldg.  
Wichita, Kansas

Sheridan County, Sec. 32 Twp. 8S Rge. (E) 26W(W)

Location as "NE/CNW/SW" or footage from lines 330' S & 330' W of NE Corner.

Lease Owner Pickrell Drilling Company

Lease Name Hoxie State Bank Well No. "B" # 1

Office Address 2820 Paseo Great Bend, Kansas

Character of Well (completed as Oil, Gas or Dry Hole)

Date well completed 19

Application for plugging filed yes 19

Application for plugging approved yes 19

Plugging commenced 12-12-60 19

Plugging completed 12-14-60 19

Reason for abandonment of well or producing formation

If a producing well is abandoned, date of last production 19

Was permission obtained from the Conservation Division or its agents before plugging was commenced? yes

Name of Conservation Agent who supervised plugging of this well A. D. Fabricius

Producing formation Depth to top Bottom Total Depth of Well 4313' Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

FORMATION	CONTENT	FROM	TO	SIZE	PUT IN	PULLED OUT
				7"		1,025'

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from feet to feet for each plug set.

Plugging commenced 12-12-60. Plugging completed 12-14-60.  
Measured in to total depth: 4313'.  
Plugged off bottom: Sanded back to 3000' and dumped 5 sacks of cement.  
Worked and shot 7" casing free at 1,025'. Built rack and slide. Pulled and layed down casing.  
Plugged well: Mudded hole up to 241' and set 5' rock bridge.  
Dumped 25 sacks of cement. Mudded hole up to 40' and set 10' rock bridge and capped the well with 10 sack of cement.

DEC 28 1960 12-28-1960

(If additional description is necessary, use BACK of this sheet)

Name of Plugging Contractor J. O. Forbes d/b/a Forbes Casing Pulling Company

Address P. O. Box 221 Great Bend, Kansas

STATE OF Kansas, COUNTY OF Barton, ss.

J. O. Forbes (employee of owner) or (owner or operator) of the above-described

well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.


(Signature) J. O. Forbes

Box 221 Great Bend, Kansas (Address)

SUBSCRIBED AND SWORN TO before me this 16th day of December, 1960

Kayann Jenkins Notary Public.

My commission expires December 8th, 1963.



WELL LOG

HOXIE STATE BANK B-1

*B#1  
Missouri Well*

DATE SPUDDED: MAY 28, 1945  
 DRILLING COMPLETED: JUNE 26, 1945  
 POTENTIAL ESTABLISHED: AUGUST 24, 1945

LOG: 330'S AND 330'W OF NE  
 CORNER OF SEC. 32, T88, R26W,  
 SHERIDAN COUNTY, KANSAS

<u>FROM</u>	<u>TO</u>	<u>FORMATION</u>	<u>FROM</u>	<u>TO</u>	<u>FORMATION</u>
0	548	SHALE AND SHELLS	3285	3583	LIME AND SHALE
548	685	SHALE AND LIME	3533	3565	LIME
685	1270	SHALE	3565	3620	LIME AND SHALE
1270	1385	SAND AND SHALE	3620	3937	LIME
1385	1410	SAND	3937	3967	LIME AND SHALE
1410	1470	SHALE	3967	3997	LIME
1470	1630	SHALE AND SHELLS	3997	4021	LIME AND SHALE
1630	1770	SAND AND SHALE	4021	4117	LIME
1770	2030	SHALE	4117	4186	LIME AND SHALE
2030	2085	ANHYDRITE	4186	4202	LIME
2085	2509	SHALE AND SHELLS	4202	4227	CHERT
2509	3145	LIME AND SHALE	4227	4299	LIME AND CHERT
3145	3190	SHALE	4299	4323	LIME
3190	3285	LIME			

ELEVATION 2508'

RAN 240' OF 13 3/8" OD 36# 3 GA. ARMCO SPIRAL WELD CASING; SET AT 241';  
 CEMENTED WITH 250 BAGS OF CEMENT.

TOP OF LANSING LIME 3612'  
 TOP OF MISSISSIPPI LIME 4218'  
 TOP OF ARBUCKLE LIME 4258'

DRILLED TO A TOTAL DEPTH OF 4313' IN ARBUCKLE LIME WITH ROTARY TOOLS. CORED  
 FROM 4313' TO 4323' RECOVERING 3' OF DOLOMITE WITH GOOD POROSITY BUT NO SHOW.

RAN SCHLUMBERGER SURVEY TO A DEPTH OF 4270'. SCHLUMBERGER SURVEY SHOWED  
 FAIR POROSITY FROM 3612' TO 3615', AVERAGE POROSITY FROM 3628' TO 3636',  
 FAIR POROSITY FROM 3665' TO 3673', AVERAGE POROSITY FROM 3679' TO 3685',  
 AVERAGE POROSITY FROM 3708' TO 3713', AVERAGE POROSITY FROM 3718' TO 3726',  
 GOOD POROSITY FROM 3756' TO 3762', GOOD POROSITY FROM 3796' TO 3804', GOOD  
 POROSITY FROM 3816' TO 3822'.

SPOTTED 50 BAGS OF CEMENT ON BOTTOM TO CEMENT OFF CREVICE.

RAN 3854'6" OF 7" OD 24# 10VT J-55 SEAMLESS CASING; RAN 7" OD 10VT MALE AND  
 FEMALE FLOAT COLLAR AND 7" OD 10VT GUIDE SHOE; SET AT 3838'; CEMENTED WITH  
 300 BAGS OF CEMENT.

RECEIVED  
 COMMISSION  
 DEC 23 1960  
 12-28-1960  
 CONSERVATION DIVISION  
 Wichita, Kansas