Notice: Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

ly Appointment Expires __

KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

WELL PLUGGING RECORD

K.A.R. 82-3-117

Form CP-4
December 2003
Type or Print on this Form
Form must be Signed
All blanks must be Filled

LCusc						API Number: _		,,,	
	Operator: F. G. Hol		KS 67206			Lease Name:	Hiskett "B	н	
		•		056		Well Number:	1-23		
	e: <u>(316) 684 -84</u>					well ladiliber	(0000)	NW	. NEN
Type o	of Well: Oil-		Doc	ket #:	/D EN (D)	Spot-Location	(0000):	FD	
	as D&A, SWD, ENHR, W			,	/D or ENHR)	——— Feet	from	North / 📆	South Section L
The pl	ugging proposal was	approved on:			(Date)	Feet	from 💋	East /	West Section L
by: St	teve Durrant			(KCC District	Agent's Name)	Sec. 23 T	wp. <u></u>	_S. R	West Section L
Is ACO	O-1 filed? Yes No If not, is well log attached? Yes No					County: Pratt			
Produc	ucing Formation(s): List All (If needed attach another sheet) Depth to Top: Bottom: T.D					Date Well Com	,		
						Plugging Comn	5	-19-08	
		Depth to Top:			1	Plugging Comi	nenceu: -5-	19-08	
		Depth to Top:			1	Plugging Comp	oleted:	15 00	
				· · · · · · · · · · · · · · · · · · ·		·			
Show o	depth and thickness of		s formations.		2in- D	urfana Candinata- 6	Drodustic		·
<u></u>	Oil, Gas or Wat		From	То	Size	urface Conductor &		Pulled Out	
Forma	ation	Content	Figur	10	0,20				
<u></u>						l l			
	·								
					-8-5/8	-255		ب میب	
hole. If	e in detail the manner f cement or other plug	s were used, state the	e character of s	same depth p	4 1/2 mud fluid was placed from (bottor	aced and the met	530 thod or me	et.	introducing it int
Dug ce	e in detail the manner f cement or other plug ellar out, hooked up to in 50 psi, cut 4 1/2	s were used, state the 4 1/2" casing, pumped	e character of s 100# hulls, 175	same depth p	4 1/2 mud fluid was placed from (bottor	aced and the met	530 thod or me	ethods used in	introducing it int
Dug ce	f cement or other plug ellar out, hooked up to	s were used, state the 4 1/2" casing, pumped	e character of s 100# hulls, 175	same depth p	4 1/2 mud fluid was placed from (bottor	aced and the met	530 thod or me	ethods used in	introducing it int
hole. If	f cement or other plug ellar out, hooked up to	s were used, state the 4 1/2" casing, pumped	e character of s 100# hulls, 175	same depth p	4 1/2 mud fluid was placed from (bottor	aced and the met	530 thod or me	ethods used in	introducing it int
Dug ce	f cement or other plug ellar out, hooked up to in 50 psi, cut 4 1/2	s were used, state the 4 1/2" casing, pumped 2" & 8 5/8" off 4' b	e character of s 100# hulls, 175 below groun	same depth p	4 1/2 mud fluid was placed from (bottor	aced and the mel m), to (top) for ea 00 psi, shut in 100	thod or me ach plug so psi, hooke	ethods used in	introducing it int
bole. If Dug ce shut i	f cement or other plug ellar out, hooked up to in 50 psi, cut 4 1/2 of Plugging Contractor	s were used, state the 4 1/2" casing, pumped 2" & 8 5/8" off 4' b	e character of s 100# hulls, 175 below groun	same depth p	4 1/2 mud fluid was placed from (bottor	aced and the met	thod or me ach plug so psi, hooke	ethods used in	introducing it int
bole. If Dug ce shut i	f cement or other plug ellar out, hooked up to in 50 psi, cut 4 1/2	s were used, state the 4 1/2" casing, pumped 2" & 8 5/8" off 4' b	e character of s 100# hulls, 175 below groun	same depth p	4 1/2 mud fluid was placed from (bottor	aced and the mel m), to (top) for ea 00 psi, shut in 100	thod or me ach plug so psi, hooke	ethods used in	introducing it int
nole. If Dug ce shut i	f cement or other plug ellar out, hooked up to in 50 psi, cut 4 1/2 of Plugging Contractor s: 190 US Highwa	s were used, state the 4 1/2" casing, pumped 2" & 8 5/8" off 4' b Quality Well Servic y 56, Ellinwood,	e character of s 100# hulls, 175 below groun se, Inc.	same depth pi i sacks cemen ad.	4 1/2 mud fluid was placed from (bottort, max pressure 30	aced and the mel m), to (top) for ea 00 psi, shut in 100	thod or me ach plug so psi, hooke	ethods used in	introducing it int
nole. If Dug ce shut i	f cement or other plug ellar out, hooked up to in 50 psi, cut 4 1/2 of Plugging Contractor s: 190 US Highwa of Party Responsible for Kansas	s were used, state the 4 1/2" casing, pumped 2" & 8 5/8" off 4' t Quality Well Servic by 56, Ellinwood, or Plugging Fees: F.C	e character of s 100# hulls, 175 below groun se, Inc.	same depth pi i sacks cemen id.	4 1/2 mud fluid was placed from (bottort, max pressure 30	aced and the mel m), to (top) for ea 00 psi, shut in 100	thod or me ach plug so psi, hooke	ethods used in	introducing it int