RECEIVED SHAVE CORPORATION COMMASS

## KANSAS

STATE CORPORATION COMMISSION

STATE CORPORATION COMMISSION

SEP 3 1959

9-3-59

CONSERVATION DIVISION AGENT'S REPORT CONSERVATION DIVISION Wichita, Kansas

Jewel M. Ogden, Director 500 Insurance Building 212 North Market Wichita 2, Kansas

Remarks:

File No. County: Sedgnuch
Location: NENENE Sec. 12 Twp. 26 Rge. 2 (E) (W)
Name of Field: Seemich. Total Depth: 3/42
I have this date completed supervision of plugging of:
Lease Name: Edson Well No. 2
Operator's Full Name: Bedell- latt plug lo
Complete Address: 701 Petroleum Bedg wichite/Long
Plugging Contractor: Best Self Caring Pulling Co
Address: Nutchison Horrar R 794 License No. 48
Oil Well Gas Well Input Well SWD Well D&A
Other well as hereafter indicated:
Was any delay in plugging operations caused by Conservation Division Agent? Yes No
If yes how long? Reason:
Operation Completed: Hour 1130 ASA Day 25 Month 8 Year 3-9
ammention of a property of the contraction of the c
The above well was plugged as follows:
The above well was plugged as follows:
The above well was plugged as follows:  2854. 55" Piferet with 75 tachs Comment. 140. 85"
The above well was plugged as follows:  2854' 55" Piferet with 75 sach Cemant. 140' 85"  Luface Pife pet with 110 sache cement. top Crepustion
The above well was plugged as follows:  2854' 55" Piferet with 75 sach Cemant. 140' 85"  Luface Pife pet with 110 sache cement. top Crepustion
The above well was plugged as follows:  2854' 55" Piferet with 75 sach Cemant. 140' 85"  Luface Pife pet with 110 sache cement. top Crepustion
The above well was plugged as follows:  2854' 55" Piferet with 75 sach Cemant. 140' 85"  Luface Pife pet with 110 sache cement. top Crepustion
The above well was plugged as follows:  2854' 55" Piferet with 75 sach Cemant. 140' 85"  Luface Pife pet with 110 sache cement. top Crepustion
The above well was plugged as follows:  1854, 55" Pife set with 15 soch cement. 140' 85"  surface Pife set with 110 soch cement. top Prefration en 55" Pife of 2806. Sale filled with soul to 2800' and 5 sache Pement on top afthat, at 180' set 15' Rock Bridge al 15 sache Cement, hale  mudded to 35' st 5' Rock Bridge. and 10 sache  Cement, which filled hale to Plow surface, welded
The above well was plugged as follows:  1854, 55, Pifest with 75 tacks coment. 140'85"  surface Rife set with 1/0 tacks coment. top Crepration en 55, Rife of 2806. Sale filled with toucht  2800' and 5-tacks Pement on top afthat, at  180' set 15' Rock Bridge on 15 tacks Cemat, hale  mudded to 35' set 5' Rock Bridge. and 10 tacks  Cement, which filled hale to Plow surface, welded  Cof on surface Rife, Resonated 2350' 5' & Pofe  Signed: Sele No Stithed
The above well was plugged as follows:  1854, 55" Pife set with 15 soch cement. 140' 85"  surface Pife set with 110 soch cement. top Prefration en 55" Pife of 2806. Sale filled with soul to 2800' and 5 sache Pement on top afthat, at 180' set 15' Rock Bridge al 15 sache Cement, hale  mudded to 35' st 5' Rock Bridge. and 10 sache  Cement, which filled hale to Plow surface, welded