

FOR KCC USE:

Cancelled - <sup>Marked Overnight</sup> WA 19 Not Be Drilled 5/12/08

FORM CB-1 12/93

FORM MUST BE TYPED

FORM MUST BE SIGNED

ALL BLANKS MUST BE FILLED IN

EFFECTIVE DATE: \_\_\_\_\_

State of Kansas

DISTRICT # \_\_\_\_\_

CATHODIC PROTECTION BOREHOLE INTENT

SGA? Yes No

Must be approved by the K.C.C. sixty (60) days prior to commencing well.

Expected Spud (Starting) Date 4 3 2008  
month day year

Spot (Location) 0/0/0  
NW SW SW Sec 13 Twp 25 S Rg 4 East  
4312 feet from South (North) line of Section  
125 feet from East / West line of Section  
(Circle directions from nearest outside corner boundaries)

OPERATOR: License # 33631

IS SECTION REGULAR IRREGULAR?  
(Spot well on the Section Plat on Reverse Side)  
County: Butler

Name: Canaco Phillips

Address: 25760 W. 343rd Street

City/State/Zip: Paola, KS 66071

Lease Name: Berger/Chicago Blue/Gold MP

Contact Person: Joe Garrison

Phone: 913-285-2455

Facility Name: \_\_\_\_\_

Ground Surface Elevation: 1430 MSL

Cathodic Borehole Total Depth: 350 ft.

Depth to Bedrock: \_\_\_\_\_ ft.

CONTRACTOR: License #: 493

Name: Reiserer Well Drilling

Type Drilling Equipment: Mud Rotary Cable  
 Air Rotary Other

CONSTRUCTION FEATURES

Length of Cathodic Surface (Non-Metallic) Casing

Planned to be set: 200' ft.

Length of Conductor pipe (if any?): \_\_\_\_\_ ft.

Size of the borehole (I.D.): 200x11.150x1.0 inches

Cathodic surface casing size: 1.04 inches

Cathodic surface casing centralizers set at depths of: 180;

140; 100; 60; 20; ...

Cathodic surface casing will terminate at:

... Above surface ... Surface Vault ... Below Surface Vault

Pitless casing adaptor will be used: Yes/No at Depth \_\_\_\_\_ft.

Anode installation depths are: 340; 330; 320; 310;

300; 290; ...

WATER INFORMATION:

Aquifer Penetration: None Single Multiple

Depth to bottom of fresh water: \_\_\_\_\_

Depth to bottom of usable water: \_\_\_\_\_

Water well within one-quarter mile: yes no

Public water supply well within one mile: yes no

Water Source for Drilling Operations:

... well ... farm pond ... stream ... other

Water Well Location: \_\_\_\_\_

DWR Permit #: \_\_\_\_\_

Standard Dimension Ratio (SDR) is = 26

(cathodic surface OD csg. in inches / MWT in inches = SDR)

Annular space between borehole and casing will be grouted

with: Concrete Bentonite Cement

Neat cement Bentonite clay

Anode vent pipe will be set at: \_\_\_\_\_ ft. above surface

Anode conductor (backfill) material TYPE: Loresco

Depth to BASE of Backfill installation material: 350

Depth to TOP of Backfill installation material: 210

AFFIDAVIT

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq. It is agreed that the following minimum requirements will be met:

- 1. Notify the appropriate district office prior to spudding of and again before plugging well;
- 2. A copy of the approved notice of intent to drill shall be posted on each drilling rig;
- 3. The minimum amount of cathodic surface casing as specified below shall be set by grouting to the top.
- 4. An agreement between the operator and the district office on plugs and placement is necessary prior to plugging;
- 5. The appropriate district office will be notified before well is either plugged or casing is grouted in;
- 6. IN ALL CASES, NOTIFY DISTRICT OFFICE PRIOR TO ANY CEMENTING.

I hereby certify that the statements made herein are true and to the best of my knowledge and belief.

Date: 4/11/08 Signature of Operator or Agent: Gody Patten Title: Admin. Assist

5/12/08

FOR KCC USE:  
API # 15- 015-23775-0000  
Conductor pipe required NONE feet  
Minimum cathodic surface casing required 200 feet AH3  
Approved by: [Signature]  
This authorization expires: 4/14/09  
(This authorization void if drilling not started within 6 months of effective date.)  
Spud date: \_\_\_\_\_ Agent: \_\_\_\_\_

RECEIVED  
KANSAS CORPORATION COMMISSION

MAY 16 2008

CONSERVATION DIVISION  
WICHITA, KS

- REMEMBER TO:  
- File Drill Pit Application (form CDP-1) with Intent to Install;
- File Completion Form CB-2 within 30 days of spud date;
- Notify appropriate district office 48 hours prior to workover or re-entry;
- Submit plugging report (CB-4) within 30 days after plugging is completed.

Mail to: KCC - Conservation Division, 130 S. Market - Room 2078, Wichita, Kansas 67202-1286.

Attn: Rick Hesterman

Wed, 8/1/2007 9:00