STATE OF KANSAS STATE CORPORATION COMMISSION CONSERVATION DIVISION 200 Colorado Derby Building Wichita, Kansas 67202

WELL PLUGGING APPLICATION FORM File One Copy

API NUMBER 15-141-20,229~00 (of this well) (This must be listed; if no API# was issued, please	
LEASE OPERATOR Black Petroleum Company	OPERATORS LIČENSE NO. 5068
ADDRESS 527 Union Center Building, Wichita, Ks. 67202	
LEASE (FARM NAME) Beisner	WELL NO. 1
WELL LOCATION C N/2 SW/4 SE/4 SEC. 9	TWP. 9S RGE. 15W (Éhor(W)
COUNTY Osborne TOTAL DEPTH 3,6	665' FIELD NAME
check one: OIL WELL GAS WELL INPUT WELL SWD WEL	LD&AXX
IS WELL LOG ATTACHED TO THIS APPLICATION AS REQUIRED?	ves IS ACO-1 FILED? yes
DATE AND HOUR PLUGGING IS DESIRED TO BEGIN October 24	, 1986 @ 4:00 P.M.
PLUGGING OF THIS WELL WILL BE DONE IN ACCORDANCE WITH K REGULATIONS OF THE STATE CORPORATION COMMISSION.	.S.A. 55-128 OF THE RULES AND
NAME OF COMPANY REPRESENTATIVE AUTHORIZED TO BE IN CHAR	GE OF PLUGGING OPERATIONS:
ADDRESS	
PHONE # ()	
PLUGGING CONTRACTOR Red Tiger Drilling Company	LICENSE NO. 5302
ADDRESS 1720 KSB Building, Wichita, Kansas 67202 P	HONE # (316) 263-2371
INVOICE COVERING ASSESSMENT FOR PLUGGING THIS WELL SHOU	LD BE SENT TO:
NAMEBlack Petroleum Company	
ADDRESS 527 Union Center Building, Wichita, Kansas 672)2 HONE # (316) 264-9342
AND PAYMENT WILL BE GUARANTEED BY APPLICANT OR ACTING A SIGNED:	Shoras E. Black
NOV 6 1800 DATE:	pplicant or Acting Agent) 10/19/86

7\	CARD MUST BE TYPED	State of Kansas - NOTICE OF INTENTION TO DRILL -		CARD MUST BE SENE	
	•			DI IIOO 温度的	
	Starting DateOctober 2, 19	(see rules on revo	API Number 15— / 4/-	20,229.000	
	OPERATOR: License #	, , , C	N/2 SW SE sec9.	г _{wp} 9 s, _{Rg} .15	
	Address 527 Union Center Blo	dg.	.1900.	Ft. from South Line of S	
A material and the	City/State/Zip Wichita, Kansas	6/202	(Note: Locate well on S	ection Plat on reverse side)	
Party - Character of the Control of	Contact Person. Thomas E. Black Phone. 316-264-9342	K	Nearest lease or unit boundary		
V · ·	Phone		CountyOsborne Lease NameBEISNER		
	Name Red Tiger Drilling (Co. (Ground surface elevation $ {\cal A}\emptyset$		
	* · · · · · · · · · · · · · · · · · · ·	700 VO	Domestic well within 330 feet:	yes	
		ass: Type Equipment: Neld X Mud Rotary I	Municipal well within one mile Depth to bottom of fresh water. Depth to bottom of usable water	yes	
		l Ext Air Rotary I	Depth to bottom of usable water	800	
401	OwwoExpl _X wild	dent Coble S	Surface nine by Alternates		
AND THE PERSON NAMED IN	If OWWO: old well info as follows:	S	Surface pipe planned to be set.	(280)	
	Operator		Conductor pipe required		
	Well Name		Projected Total Depth	3/00	
	Comp Date Old Total D		Formation Cong. Sand		
	I certify that well will comply with K.S.A. Date Signature of O	perator or Agent	plugging holo jok CC specification. Title	tions. Owner	
	For KCC Use:	fact. Minit of the			
	Conductor Pipe Required	teet; Minimum Surface Pipe F 2んよう	Required	······feet per Alt.	
** ** ***	This Authorization Expires	.т Ар	pproved By		
	18/16/86 1:40PM 10/1	Ken Tyle	Hauling	for/fac/	
. •	1:40PM 101	15/01	\mathcal{O}	XXX	
	, , , , , , , , , , , , , , , , , , , ,	C E	1/2. SW. SE Sec9	Twp9s, Rg. 15	
				La Car Selve Asimentaly, Miller Control of the Cont	
	PLUGGING PROPOSAL IF ABOVE IS D & A				
·	This plugging proposal will be reviewed as	nd approved or revised at the time	the district office is called prior	o setting surface casing (call 7	
	5 p.m. workdays).	t. circ)			
	lst plug @ . 3700* (If Cong., sai		c. sys of 60	-40 w 6% gel	
a	2nd plug @ .1300 Anhy.	feet depth with20 .SX	sxs of	-40 w/6%gel	
	3rd plug @ 840' base dolite	feet depth with 100 .SX	. 60		
	3rd plug @ 9.79 Super . MYH+S.Y.	leet depth with		-40 w/6% gel	
	4th plug @ 320;	feet depth with40 . SX	c	-40.w/6%.gel	
	4th plug @ 320; 5th plug @ 40;	feet depth with40.5X	sxs of60.	-40.w/6%.gel -40.w/6%.gel	
	4th plug @ 320;	feet depth with40.5X	c	-40.w/6%.gel -40.w/6%.gel	
	4th plug @ 320; 5th plug @ 40! (2) Rathole with 10	feet depth with40. SX feet depth with10. SX sxs	sxs of 60 sxs of 60 (b) Mouseho	-40 w/6% gel -40 w/6% gel le with10	
	4th plug @ 320; 5th plug @ 40! (2) Rathole with 10 NOTE: Agreement between operator and	feet depth with40.5X feet depth with10.5Xsxs district office on plug placement.	sxs of 60. 60. 60. 60. 60. 60. 60. 60. 60.	-40 w/6% gel -40 w/6% gel le with10	
	4th plug @ 320; 5th plug @ 40! (2) Rathole with 10	feet depth with40.5X feet depth with10.5Xsxs district office on plug placement.	sxs of 60. sxs of 60. (b) Mousehor and the amount of cement to be a casing is cemented in.	-40 w/6% gel -40 w/6% gel le with	
	4th plug @ 320; 5th plug @ 40! (2) Rathole with 10 NOTE: Agreement between operator and	feet depth with40. SX feet depth with10. SXsxs district office on plug placement	sxs of 60. sxs of 60. (b) Mousehor and the amount of cement to be a casing is cemented in.	-40 w/6% gel -40 w/6% gel le with10	
in from the state in state that	4th plug @ 320; 5th plug @ 40! (2) Rathole with 10. NOTE: Agreement between operator and In Addition: Call district office after well	feet depth with40. SX feet depth with10. SXsxs district office on plug placement	sxs of 60. sxs of 60. (b) Mousehor and the amount of cement to be a casing is cemented in.	-40 w/6% gel -40 w/6% gel le with	
i kun in steinindestä	4th plug @ 320; 5th plug @ 40! (2) Rathole with 10. NOTE: Agreement between operator and In Addition: Call district office after well District office use only:	feet depth with40. SX feet depth with10. SX feet depth with10. SX district office on plug placement li is either plugged or production (Call 7 a.m. to 5 p.n	sxs of 60. (b) Mousehold and the amount of cement to be a casing is cemented in. n. workdays)	-40 w/6% gel -40 w/6% gel le withl0	
i d'un Bestini della di	4th plug @ 320; 5th plug @ 40! (2) Rathole with 10	feet depth with	sxs of60. (b) Mousehold and the amount of cement to be a casing is cemented in. m. workdays)	-40 w/6% gel -40 w/6% gel le with 10 used is necessary prior to plughous to plughou	
	4th plug @ 320; 5th plug @ 40! (2) Rathole with 10 NOTE: Agreement between operator and In Addition: Call district office after well bistrict office use only: API #15— / 4/ -2 Surface casing of	feet depth with	sxs of 60. (b) Mousehold and the amount of cement to be a casing is cemented in. n. workdays)	-40 w/6% gel -40 w/6% gel le with 10 used is necessary prior to plughous to plughou	
1 t. sain.ide 	4th plug @ 320; 5th plug @ 40! (2) Rathole with 10	feet depth with	sxs of 60. (b) Mousehold and the amount of cement to be a casing is cemented in. n. workdays)	-40 w/6% gel -40 w/6% gel le with 10 used is necessary prior to plughous to plughou	
. <u> } t. cain de la </u>	4th plug @ 320; 5th plug @ 40! (2) Rathole with 10 NOTE: Agreement between operator and In Addition: Call district office after well bistrict office use only: API #15— / 4/ -2 Surface casing of	feet depth with	sxs of 60. (b) Mousehold and the amount of cement to be a casing is cemented in. n. workdays)	-40 w/6% gel -40 w/6% gel le with 10 used is necessary prior to plus hours 16 ys 15 sxs on 19	
. <u> </u>	4th plug @ 320; 5th plug @ 40! (2) Rathole with 10 NOTE: Agreement between operator and In Addition: Call district office after well bistrict office use only: API #15— / 4/ -2 Surface casing of	feet depth with	sxs of 60. (b) Mousehold and the amount of cement to be a casing is cemented in. n. workdays)	-40 w/6% gel -40 w/6% gel le with 10 used is necessary prior to plug hours 16 ys 15	
in the annia destated in the second s	4th plug @ 320; 5th plug @ 40! (2) Rathole with 10 NOTE: Agreement between operator and In Addition: Call district office after well bistrict office use only: API #15— / 4/ -2 Surface casing of	feet depth with	sxs of 60. (b) Mousehold and the amount of cement to be a casing is cemented in. n. workdays)	-40 w/6% gel -40 w/6% gel le with 10 used is necessary prior to plus hours 16 ys 18 sxs on 19	