R	2

TO:	API number: 15-065-20,394-00-00
STATE CORPORATION COMMISSION	
CONSERVATION DIVISION - PLUGGING	NW SE NE /4 SEC. 31 , 09 S, 24 W
200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	3630 feet from S section line
WICHITA, RANSAS 0/202	990 feet from E section line
Operator license# <u>5131</u>	Lease_Dreiling well #_A-4
Operator: Thunderbird Drilling, Inc.	County Graham /33.90
Address: Box 97	Well total depth 4120 feet
Ellinwood, Kansas 67526	Conductor Pipe: 0 inch @ 0 feet
	Surface pipe 8 5/8 Inch @ 250 feet
Aband. oil well <u>X</u> , Gas well, Inp	
Plugging contractor: Great Bend Casing	Pullers, Inc. License#4635 CP
Address: Great Bend, Kansas 67530	
Company to plug at: Hour: P.M. Day:	13 Month: April Year: 92
Plugging proposal received from: Gary	Burke
Company: Great Bend Casing Pullers, In	C. Phone:
Were: <u>Order 350 sx. 65/35 pozmix -</u>	10% gel 500# hulls.
Allied Cement Company. Rods	stubing pulled from well - hole
open to production perf's. D	.V. tool @ 2208' cwc and squeezed.
Plugging Proposal Received by: <u>Carl</u>	Goodrow
Plugging operations attended by agent?	All[X], Part[], None[]
Completed: Hour: <u>3:45P.M.</u> , Day: <u>13</u> , Mo	onth: April , Year: 92
Actual plugging report: 8 5/8" set 25	0' W/190 sx. 5 1/2" set @ 4116'
w/125 sx. Top perf. 3877'. Squeeze 5	1/2" W/350 SX. cement blend
W/500# hulls. Mixed in to Max. P.S.I.	600#. Close in P.S.1. 300#.
<u>Pumped on 8 5/8" annulus - blew out he</u> Plug complete.	ad - cement at surface.
irug comprete.	
	5/2
Remarks:	BADAnhy.plug:YES_X_NO
Condition of casing(in hole):GOOD X B	Anhy.plug:YES X NO MOCKET
Bottom plug(in place):YES_x_,CALC	Anhy.plug:YES_X_NO
Plugged through TUBING, CASING	GL CONSO
I did(X)	
i did(x) / did not[] observe the p	rugging. Carl Noodlous Chilles
\	(A) (4 2 / 1 / 70 ·
ATE	(agent)
V NO 35263	(agent)