6-16 4-050163

TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	API number: 15-065-22,712-00-00 NW NE NW /4 SEC. 07 , 09 S, 24 W 4950 feet from S section line 3630 feet from E section line
Operator license#_6037_	Lease Minium well # 1
Operator: Staab Oil Company	County Graham Well total depth 4056 feet
Address: 1960 280 Avenue Hays, Kansas 67601 913-625-3013	Conductor Pipe: inch @ feet
Aband. oil well, Gas well, Input well, SWD, D & A _X	
Plugging contractor: Shields Drilling Company License# 5655	
Address:	
Company to plug at: Hour: AM Day:	16 Month: June Year: 1993
Plugging proposal received from: <u>Burton Berry</u>	
Company: Shields Drilling Company	phone:
Were: Spot plugs through drill pipe w/ heavy mud between all plugs.	
1st plug @ 2190 feet with 25 sacks	Rat hole: 15 sacks
2nd plug @ 1015 feet " 100 "	Mousehole: 10 sacks
3rd plug @ 300 feet " 40 "	
4th plug @ 40 feet " 10 "	with 8 5/8" wiper plug
Plugging Proposal Received by: <u>Marvin L. Miller</u>	
Plugging operations attended by agent?	All[], Part[], None[X]
Completed: Hour: 4:45 AM , Day: 16 , Month: June , Year: 1993	
Actual plugging report: <u>Hole reported plugged as above.</u> Order sx 60/40 pozmix w/ 6% gel and 1/4# celloflake or flowcel per sk	
Order Sk 00/40 pozmik w/ 0% ger an	1/14 CELIOTIANE OF FLOWDER PET SK
Remarks:Elevation:2488, Anhydrite:2175-2211feet, Anhydrite plug:2190	
Bottom plug (in place): Yes X , Calc , No Arbuckle: NONE PROPRIED MANAGEMENT APPROPRIED APPROPRIED NO ARBUCKLE: NONE OF THE PROPRIED APPROPRIED	
Remarks: Elevation: 2488, Anhydrite: 2175-2211 feet, Anhydrite plug: 2190 Bottom plug (in place): Yes_X_, Calc, No Arbuckle: NONE PLUED NONE OF THE DESCRIPTION OF THE PLUE OF THE P	
I did [V] Adid fiet [X] observe the plugging. Mawn L. m. law 18-19-19-19-19-19-19-19-19-19-19-19-19-19-	
JUL 1 3 1993	Marvin L. Miller P. D. Wicker II. (agent)
W. M. 38103-	Form CP-2/3
· ·	