

15-163-03203-00 00

R

DISTRICT CONSERVATION AGENT'S REPORT

TO:

State Corporation Commission  
Conservation Division  
800 Bitting Building  
Wichita, Kansas

FILE NO. \_\_\_\_\_

LOCATION SW-SW

SEC. 5 TWP. 9 RGE. 17-W

Dry Hole X Abandoned Oil Well \_\_\_\_\_ Abandoned Gas Well \_\_\_\_\_

I have today completed supervision of plugging of:

Well No. 1 Lease J. H. <sup>KCC</sup> <sub>248</sub> Thompson

Operator Horton Drilling Co Address Box #24 - Wichita - Kansas

Field \_\_\_\_\_ County Booth

Total Depth 3472 Feet.

(Describe briefly the manner in which the well was plugged)

Surface Pipe 10 3/4 - 2415 - Circulated with Cement  
5 1/2" casing set at 3472 & cemented with 100 Sacks  
Cement - Filled hole back down bottom to 3410 ft  
Put in 10 sacks of cement at 3410 ft with bludge  
Boiler - Shot off & reworked 2765 ft & 5 1/2" casing.  
Filled hole with mud to 2405 - Plus 20 sacks cement  
at 2405 - Surface Plug 235 ft below the surface & 10 sacks  
of Cement - Mud between plugs

Frank Carroll  
Pipe Puller & Plugger

C. M. Stovall  
District Conservation Agent

Date 10 - 19 - 1947

**PLUGGING**  
FILE SEC. 5 T. 9 R. 17 W  
BOOK PAGE 14 LINE 31

OCT 22 1947  
10/22/47