

DISTRICT CONSERVATION AGENT'S REPORT

BOOK PAGE 32 LINE 31  
FILE SEC 16 TWP 9 R 20  
PLUGGING

TO:

State Corporation Commission  
Conservation Division  
800 Bitting Building  
Wichita, Kansas

15-163-00442-00-00

FILE NO. \_\_\_\_\_

LOCATION NW NW NW

SEC. 16 TWP. 9 RGE. 20 W

Dry Hole  Abandoned Oil Well \_\_\_\_\_ Abandoned Gas Well \_\_\_\_\_

I have today completed supervision of plugging of:

Well No. 1 Lease Morris 400 Brown Bldg

Operator Harry Gore Address Wichita, Kans

Field \_\_\_\_\_ County Rooks

Total Depth 3778 Feet.

(Describe briefly the manner in which the well was plugged)

8 5/8" at 256' circulated with cement.

Circulated hole with heavy mud, pushed cementing plug

to 240', displaced 15 sax cement through drill pipe,

mud to 40', set cementing plug, 1/2 sack hulls

and 10 sax cement to bottom cellar.

RECEIVED  
STATE CORPORATION COMMISSION  
07-26-1952  
JUL 26 1952

Edward J. Kelly  
District Conservation Agent

Date 7-22-52

CONSERVATION DIVISION  
Wichita, Kansas  
PLUGGING  
FILE SEC 16 TWP 9 R 20  
BOOK PAGE 32 LINE 31