

4-032270

11-25

API Number: 15-179-20852-00-00

TO: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

SE NE NW \_\_\_\_\_ / 4 SEC. 32, 09, 26 W  
4290 \_\_\_\_\_ feet from S section line  
2970 \_\_\_\_\_ feet from E section line

Operator license# 9067

Lease: Minium Well # 1

Operator: DaMar Resources, Inc.

County: Sheridan 133.22

Address: P.O. Box 70  
Hays, Kansas 67601

Well total depth 4099 feet  
Conductor Pipe: 0 inch @ 0 feet  
Surface pipe 8 5/8 Inch @ 261 feet

Aband. oil well X, Gas well, Input well, SWD, D & A

Plugging contractor: Co Tools License# 9067

Address: P.O. Box 70 - Hays, Kansas 67601

Company to plug at: Hour: P.M. Day: 25 Month: November Year: 1997

Plugging proposal received from: Dean Ives

Company: DaMar Resources, Inc. Phone: -

Were: Order 300 sxs 60/40 pozmix - 10% gel - 500# hulls.

RECEIVED  
STATE CORPORATION COMMISSION

DEC 18 1997  
12-18-1997  
CONSERVATION DIVISION  
Wichita, Kansas

Plugging Proposal Received by: Carl Goodrow

Plugging operations attended by agent? All [ X ], Part [ ], None [ ]

Completed: Hour: 3:30 P.M., Day: 25 Month: November Year: 1997

Actual plugging report: 8 5/8" set at 261' cwc. 5 1/2" set at 4099'.  
Prod. Perfs 3876' - 4050'. Port collar at 2280' cwc. P.B.T.D. 4074'. Squeezed 5 1/2" with 300  
sxs cement blend with 500# hulls mixed in. Max. P.S.I. 500#. S.I.P. 200#. Cement at  
surface in 8 5/8".

Remarks: Allied Cement Company - Oakley, Kansas

Condition of casing(in hole): GOOD \_\_\_\_\_ BAD \_\_\_\_\_ Anhy.plug: YES X NO \_\_\_\_\_

Bottom plug(in place): YES \_\_\_\_\_, CALC \_\_\_\_\_, NO \_\_\_\_\_ Dakota plug: YES X, NO \_\_\_\_\_

Plugged through TUBING \_\_\_\_\_, CASING \_\_\_\_\_. Elevation: \_\_\_\_\_ GL

I [aid] x / did not [ ] observe the plugging.

Carl Goodrow  
(agent)

INVOICED

DATE DEC 12 1997

INV. NO. 49668