

15-065-61330-00-00

BARNETT Oil Co

Elev. 2356.

Lyons #3

~~E 5 1/2 N E 1/4 S 2 NESE~~

~~2-8-24 Graham Co.
Drillers log of Lyons~~

| | |
|-----------|--|
| 0-35 | Surface clay |
| 35-40 | Sand. |
| 40-65 | Shale |
| 65-80 | sand |
| 80-145 | Shale blue. Ran. 146.6' 8 3/8 Cemented 125 sax CIRC. |
| 145-610 | Shale |
| 610-1300 | Shale |
| 1300-1520 | Shale & shells |
| 1520-1725 | sand & shale |
| 1725-1780 | Shale & shells. |
| 1780-2000 | Red Rock. |
| 2000-2035 | Anhydrite |
| 2035-2130 | Shale & shells. |
| 2130-2370 | shale & shells |
| 2370-2505 | lime & shale |
| 2505-2660 | lime & shale |
| 2660-2710 | lime & shale |
| 2710-2825 | lime & shale |
| 2825-2940 | lime & shale |
| 2940-3040 | lime & shale |
| 3040-3095 | lime & shale |
| 3095-3210 | lime & shale |
| 3210-3320 | lime & shale |
| 3320-3405 | shale & lime |
| 3405-3490 | lime & shale |
| 3490-3555 | lime & shale |
| 3555-3620 | lime |
| 3620-3660 | lime |
| 3660-3705 | lime |
| 3705-3750 | lime |
| 3750-3800 | lime |
| 3800-3808 | lime. |

RECEIVED
STATE CORPORATION COMMISSION
JAN 27 1970
CONSERVATION DIVISION
Wichita, Kansas

1/27/70

Paul O. Harbo

Ran 3820 of 5 1/2 14" casing set at 3807
10' off bottom cemented w/ 125 sax. 108-1500