

T. L. SMITH NO. 5

SHEET 1

OWNER The Texas Company DIVISION Oklahoma DATE MADE July 24, 1956
 DISTRICT Kansas LEASE T. L. Smith WELL NO. 5
 STATE Kansas COUNTY OR PARISH Graham TWP. 8S RANGE 24W SEC. 30
 LOCATION OF WELL SW NE SW

COMMENCED RIGGING UP 7-1-56 COMMENCED DRILLING 7-1-56 COMPLETED DRILLING 7-20-56
 DAY DRILLER _____ NIGHT DRILLER _____ CONTRACTOR Powell Drlg. Co.
 CABLE FROM _____ TO _____ ROTARY FROM 0' TO 3985' COMPANY RIG NO. _____
 TOTAL DEPTH 3985' MEASURED BY M. C. Harrell ELEVATION KB - 2468
PBTD 3975' DF - 2466
GL - 2463

CASING RECORD

SIZE	WEIGHT	PUT IN WELL		PULLED OUT		LOST IN WELL		SHOES		PACKERS		
		FEET	INS.	FEET	INS.	FEET	INS.	LENGTH	MAKE	KIND	LENGTH	SET AT
10-3/4"	29#	310'										FT.
7"	20#	2612'										FT.
7"	20#	1365'										FT.
		27??										FT.
												FT.

10-3/4" casing set at 318' with 210 sacks cement, 200# CC. Cement circulated.
 7" casing set at 3981' with 100 sacks cement, 3% gel around shoe and 150
 barrels kenpack thru stage collar at 2207', had slight returns.

WAS CASING CEMENTED? _____ IF SO, HOW MANY SACKS OF CEMENT USED? _____
 LINER: STATE SIZE AND WEIGHT _____ WHERE SET _____ FT. AND INS. BLANK _____ FT. AND INS. PERFORATED _____
 HOW PUT TOGETHER _____ COUPLING _____ FLUSH-JOINT _____ INSERTED _____
 REMARKS: _____

EQUIPMENT RECORD

TUBING				SUCKER RODS			PUMPING OUTFIT
SIZE	WEIGHT	FEET	INS.	FEET	INS.	SIZE AND KIND	DESCRIPTION, KIND, SIZE, ETC.

Completed Testing 7-20-56 43-1/2 BO & 1-1/2 BW in 8 hrs.

FLOWING, PUMPING, GASER OR DRY Pumping PRODUCTION FIRST 24 HOURS _____ PRODUCTION SETTLED _____
 IF GAS WELL, OPEN FLOW CAPACITY _____ SHUT IN PRESSURE _____ ROCK PRESSURE _____
 KIND OF SHOT _____ SIZE OF SHOT, QUARTS _____
 NUMBER OF SHELLS _____ SIZE OF SHELLS _____ INCHES, DIAMETER _____
 LENGTH OF SHELLS _____ FEET _____ INCHES _____ TOP OF SHOT _____
 BOTTOM OF SHOT _____ ANCHOR _____ WELL BRIDGED TO _____
 TOTAL DEPTH OF WELL _____ NUMBER OF SHOT _____ PRODUCTION BEFORE SHOT _____ BBL. PER DAY _____
 PRODUCTION AFTER SHOT _____ BBL. PER DAY. SHOT FURNISHED BY _____
 NAME OF SHOOTER _____ SHOT INSPECTED _____ BY _____ (COMPANY EMPLOYEE) _____
 COMMENCED DRILLING DEEPER _____ COMPLETED _____ DRILLING DEEPER _____
 TOTAL DEPTH _____ PRODUCTION FIRST 24 HOURS _____ PRODUCTION SETTLED _____

REMARKS: T. L. Smith #5
Holley Pool
TD 3985' - PBTD 3975'
Completed Drilling 7-20-56
Completed Testing 7-20-56

RECEIVED
 STATE CORPORATION COMMISSION
7-6-1956
 JUL 6 1956

NOTE: IF WELL WAS DRY, STATE UNDER REMARKS, WHEN, HOW, AND BY WHOM PLUGGED.
 STATE UNDER REMARKS ANYTHING OF INTEREST NOT COVERED IN LOG.
 CONSERVATION DIVISION PROVIDED FOR REMARKS IS NOT SUFFICIENT WRITE ON BOTTOM OF LAST SHEET OF LOG.
 Wichita, Kansas

15-0652 02717-00-00

LOG OF WELL

SHEET No. 2

District **Kansas**

Owner **The Texas Company Farm T. L. Smith**

Well No. **5**

FORMATION	AMOUNT	COLOR	HARD OR SOFT	DEPTH CORES TAKEN	REMARKS
REMARKS:					
7-10-56					Ran Halliburton Electric Log to 3985'.
7-15-56					Moved in cable tools. Drilled DV tool and stage collar and bailed to 3866'.
7-16-56					Drilled cement and cleaned out to bottom. Bailed 8 gallons salt water per hour for 8 hours.
7-17-56					Plugged back from 3985' to 3979' with cement. Set bridge plug at 3975'. Perforated 3960-66' with 22 jets.
7-18-56					Bailed 2-1/2 gallons oil and 8 gallons water per hour for 5 hours. Acidized perforations 3960-66' with 500 gallons 15% acid, maximum pressure 550#, no break, 1 minute pressure drop 50#, 5 minute pressure drop 100#. Swabbed back 150 barrels load oil then swabbed 8 barrels new oil and 1 barrel water in 5 hours, last 2 hours swabbed 1 barrel oil with trace water.
7-19-56					Re-acidized perforations 3960-66' with 2000 gallons 15% acid, maximum pressure 700#, no break. One minute pressure drop 50#, 5 minute pressure drop 125#. Treating time 25 minutes. Swabbed back load oil then swabbed 40 barrels oil with trace water in 7 hours. Ran tubing and rods.
7-20-56					Pumped 43-1/2 barrels oil and 1-1/2 barrels water in 8 hours from perforations 3960-66'. Producing formation Lansing topped at 3805'.
CASING REMARKS:					
Measurement from BH-KB 6.8', BH-GL 2.5'					
Centralizers:					
3979', 3900', 3811', 2210', 1490', 980'					
TOPS:					
Cimarron Dolomite-212					
Topeka-----350					
Heebner-----370					
Toronto-----370					
Lansing-----380					

RECEIVED
STATE CORPORATION COMMISSION
7-6-1973
JUL 6 1973
CONSERVATION DIVISION
Wichita, Kansas