

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-065-20529-00-01
Spot: NEM/WSW Sec/Twnshp/Rge: 36-9S-22W
2310 feet from S Section Line, 4290 feet from E Section Line
Lease/Unit Name: WOLFE Well Number: 4
County: GRAHAM Total Vertical Depth: 3822 feet

Operator License No.: 9854
Op Name: MARMAC PETROLEUM COMPANY
Address: 2120 S. HOLLY STREET, STE 207
DENVER, CO 80222

Conductor Pipe: Size feet:
Surface Casing: Size 8.625 feet: 208 w/150 sxs cmt
Production: Size 5.5 feet: 3822 w/225 sxs cmt
Liner: Size feet:

Well Type: EOR UIC Docket No: E17942.1 Date/Time to Plug: 04/03/2002 9:30 AM

Plug Co. License No.: 31925 Plug Co. Name: QUALITY WELL SERVICE, INC.

Proposal Rcvd. from: RICHARD MCINTYRE Company: QUALITY WELL SERVICE, INC. Phone: (620) 727-3410

Proposed Plugging Method: According to KCC Rules & Regulations.
Perforate at 1125' and 1825'.

Plugging Proposal Received By: JAY PFEIFER

Witness Type: Plugging Operations 100% Witnessed (Complete)

Date/Time Plugging Completed: 04/03/2002 2:00 PM

KCC Agent: ROGER MOSES

Actual Plugging Report:

8 5/8" S.P. at 208' w/150 sxs cement. 5 1/2" casing at 3822' w/225 sxs cement.
Ran tubing to 2500' - pumped 200 sxs cement with 500# hulls to circulate.
Pulled all tubing and topped off with 45 sxs cement.
Tied to annulus and squeezed 50 sxs cement to Max. P.S.I. 200#.
Total of 295 sxs 60/40 pozmix - 10% gel.

THIS IS A KCC FEE FUND PLUGGING.

RECEIVED

APR 19 2002

KCC WICHITA

Remarks: ALLIED CEMENTING COMPANY. QUALITY WELL SERVICE-WATER.

Plugged through: TBG

District: 04

Signed

Roger L. Moses

(TECHNICIAN)

APR 16 2002

MUFRIN DRILLING CO.

#4

WOLFE

36-9-22W
NE NW SW

WICHITA, KANSAS

CONTR. CO. TOOLS

CTY

GRAHAM

GEOL. ROGER WELTY

FIELD

BRASSFIELD NE

E 2348 KB CM 2/23/72 ^{CARD} ISSUED 5/11/72 IP WJW/LKC 3668-3713

API 15-065-20,529

LOG TOPS DEPTH DATUM 8 5/8" 208/150sx; 5 1/2" 3022/225sx

LOG	TOPS	DEPTH	DATUM	
SC	1826	+ 522		DST(1) 3566-85/1', 90' MW, BHP 708-685#/ 30", FP 46-92#
BT SC	1863	+ 485		
TOP	3303	- 955		DST(2) 3602-70/1', 70' MW/SP OIL, BHP 652-629#/30", FP 69-104#
HEEB	3528	-1180		
TOR	3552	-1204		DST(3) 3696-3745/1', 60' GIP, 85' OCM, BHP 369-357#/30", FP 35-58#
LANS	3568	-1220		
BKC	3795	-1447		
TD	3822	-1474		
				MICT, PF 10/3732-36, 10/3709 1/2-13 1/2, NO FILL UP, 4500 ACID, SWB LD & SWB 2.75 BF 1ST HR 54% WTR, 3.50BF 2ND HR 50% W 2.75 BF 3RD HR, 60% W, 2.50BF 4TH HR, 60%W, PF 12/3668-71, SET PB 3770, 750 ACID, SWB LD, & SWB 4.70BFPH 72%W, PUL- LED PLG & CO TO 3784, SWB AVG 2.58FPH. 72%W, RE-AC, 2000GALS SWB LD & SWB AVG 8 8BFPH, -90%W.

INDEPENDENT OIL & GAS SERVICE
WICHITA, KANSAS

Vertical handwritten notes on the left margin.