isposition of Gas: Vented Sold (If vented, subs	Used on L	COMPLETION COMPLETION Open	Hole Perf.	Production Interval F. Dually Comp. Commingled			
Estimated Production Per 24 Hours	Oil	Bbls. Gas	Ncf Vate	r Bbls.	Ges-01 i	Ratio	Gravity
when approved by	 	SLD or inj. Produ 2/2000	ucing Hethod	lowing Dpu	mping Gas L	ift O	
TUBING RECORD	2 7/8	Set At 3140	Packer At	Liner Run	☐ _{Yes} 区		
0/4	3/63	- 3307				·	- -
Shots Per Foot !	Specify Footage of Each Interval Perforated 3/65 - 3302				d Kind of Nater		Depth
	PERFORATION	RECORD - Bridge Plu	ugs Set/Type	Acid.	Fracture, Shot,	Cement Sc	weeze Record
Perforate Protect Casing Plug Back TD X Plug Off Zone	-		1	J. 6 2.	:		r
	2652/2660		75	Type and Percent Additives			
Purpose:	Depth Top Sottom Type of Cement		#Sacks Used	The and Barrers Additions			
<u> </u>	ADDITIONAL C	EMENTING/SQUEEZE REC	ORD	<u> </u>	<u> </u>	1	<u> </u>
LONG STRING	7 1/2	5 1/2	15#	3165	60/40 POZ	153	2/0UEL
SURFACE LONG STRING	12-1/4"	8 5/8	20#	229	CLASS A	134	3%CC,2%GE 2%GEL
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs./Ft.	Setting Depth	Type of Coment	# Sacks Used	Type and Percent Additives
	Report al	CASING RECORD		sed ntermediate,	production, et	c	
	: :		RTD			<u>~</u>	-1857
			MISSIS	SIPPI	2728 - 3 30	j .	-1283
List All E.Logs Run:				LESVILLE	2654		-1209
Electric Log Run (Submit Copy,)		TO THE THE	CHERO		2474	•	-1029
Cores Takımı	i	Yes Ki No	K. C.		2019		-574
deples Sent to Geological Survey		☐ yes ☐ No ☐ yes ☐ No	LANSIN	G	1708		-263
Drill Stem Tests Taken (Attach Additional Sneets.)		yes 🗵 No	Log	Formatio	n (Top), Depth :	end Datums	Sample Detum
INSTRUCTIONS: Show interval tested, time hydrostatic pressures, if more space is need	e tool open a bottom hole te	nd closed, flowing a properature, fluid reco	and shut-in oce	seures, whet	her shut-in pre	ssure read	ched static level
		West					
15 Tup. 27		CX _{East}	County B	UTLER			
perator Name	CAMBERN	T ~	Lesse Name		<u>, , , , , , , , , , , , , , , , , , , </u>	Well # .	5
	: :^^		SIDE THO				_
		•	į				