

6 031533

API NUMBER 15- 179-20,953-00-00

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

C S/2 NW SW SEC. 5, T 10 S, R 26 W&E  
1650 feet from S section line  
4620 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 9482

Lease Name Jones Well # 1  
County Sheridan 142.35

Operator: National Pet. Reserves Inc.  
Name & Address: 250 N. Rock Rd. Suite 340  
Wichita, Ks. 67206

Well Total Depth 4380 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 268

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Halliburton License Number \_\_\_\_\_

Address Oberlin, Ks.

Company to plug at: Hour: PM Day: 2 Month: May Year: 19 91

Plugging proposal received from Ted

(company name) National Pet. Res. Inc. (phone) \_\_\_\_\_

were: 8 5/8 set at 268 w/175 sks. 4 1/2 set at 4140 w/100 sks. Second stage w/350 sks  
cwc. Perf 4062 - 65; 3997 - 4001. Order 300 sks 65/35 poz 10% gel 500 lbs. hulls.  
Halliburton Cement Co.

Hole in working order when stripped of equipment and open to perms.

Plugging Proposal Received by Carl Goodrow  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None

Operations Completed: Hour: 3:10P Day: 2 Month: May Year: 19 91

ACTUAL PLUGGING REPORT Sq 4 1/2 w/250 sks cement blend w/150 sks hulls mixed into max  
psi 400 lbs. Close in psi 400 lbs. Sq 8 5/8 w/25 sks cement blend to max psi 400 lbs. Close  
in psi 400 lbs.

RECEIVED  
STATE CORPORATION COMMISSION  
06-07-1991  
JUN 07 1991

Remarks: (If additional description is necessary, use BACK of this form.)

INVOICED

(If not observed, observe this plugging.)

DATE 6-17-91

INV. NO. 32165

J.S.

Signed Carl Goodrow  
(TECHNICIAN)  
Carl Goodrow