, <u>, , , , , , , , , , , , , , , , , , </u>	
TO:	API number: 15-193-20,627-00-00
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING;	SW SE SE /4 SEC 10 10 S 22 W
200 COLORADO DERBY BUILDING	330 feet from S section line
WICHITA, KANSAS 67202	990 feet from E section line
Operator license# 3988	Lease Price "A" well # 1
Operator: Slawson Exploration, Co., In	
Address: 621 N. Robinson #490	Well total depth 4700 feet 152.75
	OULGO OF LIPC. O THOM & O LCCC
Oklahoma City, Ok 73102	Surface pipe 8 5/8 Inch @ 336 feet
Aband. oil well, Gas well, Inpu	ut well, SWD, D & A _x_
Plugging contractor: Abercrombie RTD,	Inc. License# 30684
Address: Wichita, Kansas 67202	AND STATE OF THE S
Company to plug at: Hour: P.M. Day:	15 Month: November Year: 94
Plugging proposal received from: Tony	
Company: Abercrombie RTD, Inc.	Phone:
Were:Order 190 sxs. 60/40 pozmix -	6° gol = 2° g g = 1/4# flogolo
ner, gack	0% del - 3% C.C 1/4# 110ce1e
Allied Cement Company.	
Plugging Proposal Received by: Carl Goo	5
Plugging operations attended by agent?	All Part None(Y)
Completed: Hour: 5:00P.M., Day: 15, Mon	th: November , Year: 94
Actual plugging report: 8 5/8" set @ 3	36' cwc. 200 sxs. Condition hole
with heavy mud. Spot cement plugs with	D.P.
1st. plug at 2600' w/25 sxs.	
2nd. plug at 1825' w/100 sxs. 3rd. plug at 390' w/40 sxs.	
4th. plug at 40' w/10 sxs. W.P.	
Circulated 15 sxs. in rathole.	1/4>
CL's reserve - 2800'. Anhy. 2596' - 264	491.
Remarks:	10 34 5 V
Condition of casing(in hole):GOOD X BAI	Anhy.plug:YES X NO CON SO
Bottom plug(in place):YES,CALC	NO Dakota plug: YES X NO 0, 190%
I did[N / did not[X] observe the plu	
	(agent)
DATE 1-31-95 INV. NO. 42114	Form CP-2/3
NV. MQ 4311 T	