RECEIVED JUL 18 2005 KCCWICHITA

KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

Form ACO-1 September 1999 Form Must Be Typed

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

(100 WEED 1110 10111 DE001	
Operator: License # 5488	API No. 15 - 001-29199-00-00 URIGINAL
Name: TWM Production Company	County: Allen
Address: 1150 Highway 39	SE -NE - SE - NW Sec. 27 Twp. 26 S. R. 18
City/State/Zip: Chanute, Kansas 66720	3580 feet from (S) / N (circle one) Line of Section
Purchaser: CMI	2700 feet from E) / W (circle one) Line of Section
Operator Contact Person: Michael Or Carol Wimsett	Footages Calculated from Nearest Outside Section Corner:
Phone: (620) 431-4137	(circle one) NE SE NW SW
Contractor: Name: W & W Production Company	Lease Name: Casper/Solomon Well #: C-1
License: 5491	Field Name: HUMBOLDT/CHANUTE
Wellsite Geologist:	Producing Formation: BARTLESVILLE
Designate Type of Completion:	Elevation: Ground: N/A Kelly Bushing: NONE
New Well Re-Entry Workover	Total Depth: 885 Plug Back Total Depth:
✓ Oil SWD Temp. Abd.	Amount of Surface Pipe Set and Cemented at 20' Feet
Gas ENHR SIGW	Multiple Stage Cementing Collar Used?
Dry Other (Core, WSW, Expl., Cathodic, etc)	If yes, show depth setFeet
If Workover/Re-entry: Old Well Info as follows:	If Alternate II completion, cement circulated from 824
Operator:	feet depth to TOP w/ 108 sx cmt-
	sx cmc-
Well Name: Original Total Depth:	Drilling Fluid Management Plan AI+ II N(R 8-1)-0
	(Data must be collected from the Reserve Pit)
Deepening Re-perf Conv. to Enhr./SWD Plug Back Plug Back Total Depth	Chloride content ppm Fluid volume bbis
	Dewatering method used
Commingled Docket No Dual Completion Docket No	Location of fluid disposal if hauled offsite:
·	Operator Name:
Other (SWD or Enhr.?) Docket No	Lease Name: License No.:
6/6/05 610/05 7/9/05	Quarter Sec Twp S. R
Spud Date or Date Reached TD Completion Date or Recompletion Date	County: Docket No.:
	Joseph Jo
Kansas 67202, within 120 days of the spud date, recompletion, workov Information of side two of this form will be held confidential for a period of	th the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, ver or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. 12 months if requested in writing and submitted with the form (see rule 82-3-s and geologist well report shall be attached with this form. ALL CEMENTING s. Submit CP-111 form with all temporarily abandoned wells.
All requirements of the statutes, rules and regulations promulgated to regul herein are complete and correct to the best of my knowledge.	late the oil and gas industry have been fully complied with and the statements
Signature: and Cy While	KCC Office Use ONLY
Title: Office Manager Date: 07/14/05	Letter of Confidentiality Received
yist \	If Denied, Yes Date:
Subscribed and sworn to before me this 14 day of	, Wireline Log Received
20 65.	Geologist Report Received
Notary Public: (May Dulman	UIC Distribution
Date Commission Expires:	
A MOTARY PURITY State of Kansas	

CINDY L. SPILMAN My Appt. Exp. 9/62006

ORIGINAL

Operator Name: TW	/M Production Co	mpany		Lease	Name:	Casper/Solom	ion	_ Well #: <u>C-1</u>		
Sec. 27 Twp. 2	²⁶ S. R. 18	. 📝 Eas	st West	County:	Allen					
INSTRUCTIONS: Stested, time tool oper temperature, fluid re Electric Wireline Log	en and closed, flowin covery, and flow rate	g and shu s if gas to	t-in pressures, so surface test, a	whether shi long with fir	ut-in pr	essure reached	static level, hydro	static pressur	res, botto	m hole
Drill Stem Tests Taken (Attach Additional Sheets) ✓ Yes		∕es			og Formation	on (Top), Depth a	and Datum		Sample	
Samples Sent to Geological Survey		∕es		Name			Top Datum		Datum	
Cores Taken		□ Y	∕es ✓ No							
Electric Log Run (Submit Copy)		√ Y	es No							
List All E. Logs Run:										
			CASING	PECOPO.		ew Used				
		Repo			_	ew Used ermediate, product	ion, etc.			
Purpose of String	Size Hole Drilled		ze Casing et (In O.D.)	Weigl Lbs./		Setting Depth	Type of Cement	# Sacks Used		and Percent
SURFACE	7"					20'	portland	4		
CASING		2-7/8"				824	Portland	108	2 SAC	CKS GEL
			ADDITIONAL	CEMENTIN	G / SQI	JEEZE RECORD				
Purpose: Perforate Protect Casing Plug Back TD	Depth Top Bottom	Туре	e of Cement	#Sacks Used		Type and Percent Additives				
Plug Off Zone										
Shots Per Foot PERFORATION RECORD - Bridge Plugs Specify Footage of Each Interval Perfor						Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)				Depth
2 825 to 831						frac with 35 sacks				
					· · · · · · ·					
	·						. A top			
TUBING RECORD	Size	Set At		Packer At		Liner Run				
2-	7/8"	824				_	Yes No			
Date of First, Resumer 7-9-05	d Production, SWD or E	nhr.	Producing Meth] Flowing	J ✓ Pumpin	g Gas Lift	Othe	er (Explain))
Estimated Production Per 24 Hours	Oil 6	Bbis.	Gas 1	Vicf	Wate	er Bt	ols. G	as-Oil Ratio		Gravity
Disposition of Gas	METHOD OF C	OMPLETIC	DN .			Production Interv	/al	· · · · · · · · · · · · · · · · · · ·		
Vented Sold	Used on Lease		Open Hole	✓ Perf.		ually Comp.	Commingled		,	
,,	· · /		Other (Specif	y)				· · · · · · · · · · · · · · · · · · ·		

RECEIVED
JUL 18 2005
KCC WICHITA

W & W PRODUCTION COMPANY 1150 HIGHWAY 39 CHANUTE, KANSAS 66720

PHONE: Office 620-431-4137 Mobile: 620-431-5970

TWM Production Company

Casper/Solomon # C- 1 SE NE SE NW SEC. 27-26S-RGE. 18E ALLEN COUNTY KANSAS API 15-001-29,199-00-00

JUNE 10, 2005 CEMENTED 2-7/8" WITH 108 SACKS OF CEMENT 2 SACKS GEL

RECEIVED
JUL 18 2005
KCC WICHITA

W & W PRODUCTION COMPANY 1150 HIGHWAY 39

CHANUTE, KANSAS 66720

PHONE: Office 620-431-4137 Mobile: 620-431-5970

July 11, 2005

TWM Production Co

Casper/Solomon # C-1 SE NE SE NW Sec. 27-26S-18E Allen County Kansas API 15-001-29,199

4'	dirt	000	004		3'	Sand	820	823			
32'	Lime	004	036		3'	Shale	823	826			
26'	Shale	036	040		9,	Sand	826	835			
20'	Lime	062	082		50 '	Shale	835	885			
26'	Shale		- 108		30	Silaic	033	003			
99'	Lime	108	207	•		•	•				
4'	Shale	207	211								
9,					T-4-1	D 4L 00					
2'	Lime	211	220		Total Depth 885'						
	Shale	220	222		Seating nipple 818"						
36'	Lime	222	258		Set 20' of surface pipe 6/6/05						
164'	Shale	258	422								
11'	Lime	422	433		Cemented long string 6/10/05 w/110 sack						
54'	Shale	433	487		Portland cement						
2'	Lime	487	489		Perforate 7/5/05 825 to 831						
47'	Shale	489	536		Frac with 40 sacks 7-9-05						
25'	Lime	536	561		Put to	pump 7-9	9-05				
28'	Shale	561	589								
14'	Lime	589	603								
9'	Shale	603	612								
5'	Lime	612	617								
5'	Shale	617	622								
2'	Lime	622	624								
29'	Shale	624	653								
1'	Lime	653	654								
50'	Shale	654	704								
3'	Lime	704	707								
68'	Shale	707	775								
4'	sand	775	779								
41'	Shale	779	820								
	JIIIII	,,,	020								

RECEIVED
JUL 1 8 2005
KCC WICHITA