

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

Form ACO-1
September 1999
Form Must Be Typed

WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

ORIGINAL

Operator: License # 31396
Name: Mark Farthing
Address: 219 N. 3rd.
City/State/Zip: Burlington KS. 66839
Purchaser: Plains
Operator Contact Person: Mark Farthing
Phone: (316) 364-2644
Contractor: Name: Don Farthing
License: 09417
Wellsite Geologist: None Used

API No. 15 - 207- 26716 0000
County: Woodson
SE NE NE Sec. 30 Twp. 25 S. R. 14 East West
992 feet from S / (circle one) Line of Section
371 feet from E / (circle one) Line of Section
Footages Calculated from Nearest Outside Section Corner:
(circle one) NE SE NW SW
Lease Name: Nordmeyer Well #: 7
Field Name: Quincy
Producing Formation: Cattlemans

Designate Type of Completion:
 New Well Re-Entry Workover
 Oil SWD SIOW Temp. Abd.
 Gas ENHR SIGW
 Dry Other (Core, WSW, Expl., Cathodic, etc)

Elevation: Ground: _____ Kelly Bushing: _____
Total Depth: _____ Plug Back Total Depth: _____
Amount of Surface Pipe Set and Cemented at 40.5 Feet
Multiple Stage Cementing Collar Used? Yes No
If yes, show depth set _____ Feet
Alternate II completion, cement circulated from 1438
feet depth to Surface w/ 165 sx cmt.

If Workover/Re-entry: Old Well Info as follows:
Operator: _____
Well Name: _____
Original Comp. Date: _____ Original Total Depth: _____
 Deepening Re-perf. Conv. to Enhr./SWD
 Plug Back Plug Back Total Depth
 Commingled Docket No. _____
 Dual Completion Docket No. _____
 Other (SWD or Enhr.?) Docket No. _____
9-2-2000 9-12-2000 9-30-2000
Spud Date or Date Reached TD Completion Date or Recompletion Date

Drilling Fluid Management Plan alt. 2 KJR 7/18/07
(Data must be collected from the Reserve Pit)
Chloride content _____ ppm Fluid volume _____ bbls
Dewatering method used _____
Location of fluid disposal if hauled offsite: _____
Operator Name: _____
Lease Name: _____ License No.: _____
Quarter _____ Sec. _____ Twp. _____ S. R. _____ East West
County: _____ Docket No.: _____

RECEIVED
KANSAS CORPORATION COMMISSION
DEC 07 2000
CONSERVATION DIVISION
WICHITA, KS

INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: [Signature]
Title: Owner Date: 11-30-00
Subscribed and sworn to before me this 30 day of Nov.
+9 2000.
Notary Public: [Signature]
Date Commission Expires: 1-8-02

KCC Office Use ONLY
Letter of Confidentiality Attached
If Denied, Yes | Date: _____
Wireline Log Received
Geologist Report Received
UIC Distribution

TERRY ANDERSON
State of Kansas
My Appt. Exp. 1-8-02

Operator Name: Mark Farthing Lease Name: Nordmeyer Well #: 7
 Sec. 30 Twp. 25 S. R. 14 East West County: Woodson

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <i>(Attach Additional Sheets)</i>	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Log Formation (Top), Depth and Datum	<input type="checkbox"/> Sample
Samples Sent to Geological Survey	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Name	Top Datum
Cores Taken	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Cattlemans	
Electric Log Run <i>(Submit Copy)</i>	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
List All E. Logs Run:			

CASING RECORD <input type="checkbox"/> New <input checked="" type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacs Used	Type and Percent Additives
Surface	12 1/2 "	8 5/8 "		41 '	Portland	14	
Long String	6 3/4	4 1/2		1438'		165	

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone				

RECEIVED
KANSAS CORPORATION COMMISSION

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
One	24 feet of sand Opened 10 feet	500 gal. 15% Mud Acid Pumped in the formation 12000 lbs. Water Sand Fracture	

DEC 01 2000
CONSERVATION DIVISION
WICHITA, KS

TUBING RECORD	Size <u>2 3/8</u>	Set At	Packer At	Liner Run <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Date of First, Resumerd Production, SWD or Enhr.	Producing Method <input type="checkbox"/> Flowing <input checked="" type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)			
Estimated Production Per 24 Hours =	Oil Bbls. <u>10</u>	Gas Mcf <u>Very Little</u>	Water Bbls. <u>15</u>	Gas-Oil Ratio <u>40</u>

Disposition of Gas Vented Sold Used on Lease *(If vented, Sumit ACO-18.)*

METHOD OF COMPLETION Open Hole Perf. Dually Comp. Commingled

Production Interval Other (Specify) _____

**BLUE STAR
ACID SERVICE, INC.**

PO Box 103
Eureka, Kansas 67045

Cementing Ticket
and Invoice Number

ORIGINAL
N^o 2375

Date 9-12-00	Customer Order No.	Sect. 30	Twp. 25S	Range 14E	Truck Called Out 5:00 pm	On Location 7:30 pm	Job Began 8:15 pm	Job Completed 9:00 pm
Owner MARK FARTHING		Contractor DAVE FARTHING			Charge To MARK FARTHING			
Mailing Address 29 N. Third		City Burlington			State KS 66839			
Well No. & Form Nordmeyer # 7		Place WOODSON			County KS			
Depth of Well 1446'	Depth of Job 1438'	Casing <input checked="" type="radio"/> New <input type="radio"/> Used	Size 4 1/2	Weight 10.5	Size of Hole Amt. and Kind of Cement 6 3/4 165 SKS	Cement Left in casing by	Request (Necessity) 9'	feet
Kind of Job Longstring					Drillpipe	<input checked="" type="radio"/> Rotary <input type="radio"/> Cable		Truck No. UNIT # 2

Price Reference No. # 1

Price of Job 665.00

Second Stage

Mileage 15.7 31.50

Other Charges

Total Charges 696.50

Remarks: Rig up to 4 1/2 casing. Break circulation with 10 bbls fresh water. MIXED 165 SKS Regular Cement with 4% Gel, 2% Calc, 4" Gilsonite per/sk 1/4" Flocele per/sk. Shut down. Wash out Pump & Lines. Release Plug. Displace with 23.0 bbls fresh water. FINAL Pumping Pressure 500 PSI. Bump Plug to 1000 PSI. Check float. float held shut in @ 0 PSI. Good Cement Returns

Cementor: Kevin McCoy
Helper: Brad - Mike

District: EUREKA

State: KS

The above job was done under supervision of the owner, operator, or his agent whose signature appears below.

"Thank You"

x *[Signature]*
Agent of contractor or operator

Sales Ticket for Materials Only

Quantity Sacks	BRAND AND TYPE	PRICE	TOTAL
165 SKS	Regular CLASS "A" Cement	6.75	1113.75
620 #	Gel 4%	9.50	58.90
310 #	Calc 2%	.35	108.50
650 #	Gilsonite 4" per/sk	.30	195.00
40 #	Flocele 1/4" per/sk	1.00	40.00
<p>RECEIVED KANSAS CORPORATION COMMISSION DEC 07 2000 CONSERVATION DIVISION WICHITA, KS</p>			
3	4 1/2 x 6 3/4 Centralizers	26.00	78.00
1	4 1/2 Guide Shoe	65.00	65.00
1	4 1/2 AFU INSERT float	84.00	84.00
1	4 1/2 Cement Basket	100.00	100.00
1	4 1/2 Top Rubber Plug	35.00	35.00
	165 SKS Handling & Dumping	.50	82.50
	7.75 TMS Mileage 15	.70	81.37
	Sub Total		2738.52
	Delivered by Truck No. # 4	Discount	
	Delivered from EUREKA	Sales Tax	5.9%
	Signature of operator: Kevin McCoy	Total	2900.09