4-050121

TO:	API number: 15-193-20,582-0000
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING	<u>SW NW NW</u> /4 SEC. <u>28</u> , <u>10</u> S, <u>31</u> W
200 COLORADO DERBY BUILDING	4290 feet from S section line
WICHITA, KANSAS 67202	<u>5100</u> feet from E section line
Operator license# <u>5669</u>	Lease <u>HERBERT C. TEETER</u> well # 1
Operator: <u>HELBERG OIL COMPANY</u>	County THOMAS /39.58
Address: P.O. BOX 32  MORLAND, KANSAS 67650	Well total depth <u>4295</u> feet
MORLAND, KANSAS 67650	Conductor Pipe: inch @ feet Surface pipe 8 5/8 inch @_329 feet
(313) 627 3003	Surface pipe 8 3/8 Then e 323 feet
Aband. oil well, Gas well, Inp	out well, SWD, D & A _X
Plugging contractor: B.J. SERVICES	License#
Address:	
Company to plug at: Hour: PM Day:	25 Month: NOVEMBER Year: 1991
Plugging proposal received from: JERRY HELBERG	
Company: HELBERG OIL COMPANY	phone: (913)627-5665
Were: Spot plugs through drill pipe w/	heavy mud between all plugs.
1st plug @ 2570 feet with 25 sacks	<del></del>
2nd plug @ <u>1700</u> feet " 100 "	RECEIVED STATE COPPOSATION COMMISSION
3rd plug @ 380 feet " 40 "	
4th plug @ 40 feet " 10 "	with 8 5/8" wiper plug
Plugging Proposal Received by: <u>Marvir</u> Plugging operations attended by agent?	n L. Miller
Completed: Hour: 6:30 PM , Day: 25 , Mo	onth: NOVEMBER , Year: 1991
Actual plugging report: Hole reporte Order sx 60/40 pozmix w/ 6% gel an	ed plugged as above. nd 1/4# celloflake or flowcel per sk
Remarks:Elevation: 2997, Anhydrite: 2551 Bottom plug (in place): Yes X	- <u>2591</u> feet, Anhydrite plug: <u>YES</u> ,Calc <u>X</u> ,No Arbuckle: <u>NONE</u>
Did NOT penetrate Arbuckle, cemented b	y B.J. SERVICES
I did[ ] / did not[ X ] observe the plugging. Marvin & Muller	
INVUILED	Marvin L. Miller P.I.R.T.II
DATE 12-9-9/ Yel	(agent) Form CP-2/3
INV. NO. 34051	TOTAL OF 2/3