

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-163-30203-00-00
Spot: ^{SW} NESENWSE Sec/Twnshp/Rge: 7-10S-17W
¹⁶¹² ~~1725~~ feet from S Section Line, ~~1575~~ feet from E Section Line
Lease Name: KLEINSCHMIDT B ¹⁶⁹¹ Well #: 6
County: ROOKS Total Vertical Depth: 3588 feet

Operator License No.: 5552
Op Name: GORE OIL COMPANY
Address: 202 S ST FRANCIS PO BOX 2757
WICHITA, KS 67202

String	Size	Depth (ft)	Pulled (ft)	Comments
PROD	4.5	3588	0	w/150 sxs cmt
SURF	8.625	153	0	w/95 sxs cmt

116.61

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 11/12/2008 1:30 PM
Plug Co. License No.: 30606 Plug Co. Name: MURFIN DRILLING CO., INC.
Proposal Rcvd. from: CRAIG Company: MURFIN DRILLING CO., INC. Phone: (316) 267-3241

Proposed Plugging Method: Ordered 300 sxs 60/40 pozmix - 4% gel - 500# hulls.
Shoot perms at 840' - 1480' - 1800'.
1000' of 2 3/8" tubing and 1000' 5/8" sucker rods stuck in the hole.

Plugging Proposal Received By: RICHARD WILLIAMS WitnessType: COMPLETE (100%)
Date/Time Plugging Completed: 11/12/2008 4:30 PM KCC Agent: MARVIN MILLS

Actual Plugging Report:

Perfs:

Ran tubing to 2445' - pumped 80 sxs cement with 300# hulls.
Pulled tubing to 1220' - pumped 80 sxs cement with 200# hulls - good circulation of cement.
Pulled tubing out - tied onto backside - pumped 50 sxs cement. S.I.P. 200#.
Tied onto 4 1/2" - pumped 40 sxs cement. Shut in with 150# P.S.I. - cement fell. Let set over night.
11/13/2008 - pumped 40 sxs cement down the 4 1/2" - filled up - complete.

INVOICED
DATE 12-16-08
INV. NO. 2009060840


RECEIVED
KANSAS CORPORATION COMMISSION
NOV 19 2008
CONSERVATION DIVISION
WICHITA, KS

Remarks: ALLIED CEMENTING COMPANY-TICKET #32238.

Plugged through: TBG

District: 04

Signed _____



(TECHNICIAN)


CM

Form CP-2/3

NOV 14 2008

PKT

9-220 Map No. _____
 OPER DAVIS BROS. - TRANSIT CORP.
 TULSA, OKLA.
 WELL #6 KLEINSCHMIDT 'B'
 CONTR TRANSIT CORP.
 FIELD PLAINVILLE FIELD (LAN)
 I.P. CO P 100 BOPD + 20 BWPD LAN 3446-3532



S-T-R 7-10S-17W
 SPOT APP SE NW SE
 CO ROOKS, KS.
 ELEV 2113 KB

(SPL)

ANH 1393 + 720
 B/" 1431 + 682
 HB 3269 - 1156
 TOR 3288 - 1175
 LAN 3310 - 1197
 B/KC 3536 - 1423
 CGL 3555 - 1442
 RTD 3590 - 1477

SPUD 8-7-66 8" 153 W/95 SX.

SHO OIL IN LAN 3343-58, SLI SHO OIL 3365-80, SLI SHO OIL
 3469-73 & 3485-92, GOOD SHO OIL 3506-09. RTD 3590 NO LOG
 4 1/2" 3588 W/150 SX
 CO 3560, PF 8/3510-14, 6/3529-32 (LAN) 3500A, § LD, § 4 BFPH/
 90% OIL, 4 HRS, PB 3500, PF 12/3470-76, 16/3488-96 (LAN)
 750A + 3500A (15%), § LD, § 11 BOPH + 5% WTR, 4 HRS, PB
 3469, PF 6/3446-49, 8/3452-56 (LAN) 2500A, § LD
 § 12 1/2 BF = 85% OIL, 4 HRS, CO 3550, POP
 CO P 100 BOPD + 28 BWPD LAN 3446-3532
 COMPLETED 9-23-66

Dale Inc