KANSAS CORPORATION COMMISSION PIGNAL September 1999 OIL & GAS CONSERVATION DIVISION Form Must Be Typed MENDED

WELL HISTORY - DESCRIPTION OF WELL & LEASE

	Form ACO-1
	September 1999
Form	Must Be Typed

Operator: License # 5150	API No. 15 - 099-23,779 -00-00
Name: COLT ENERGY, INC	County: LABETTE
Address: P O BOX 388	S/2 _ SW_ Sw Sec. 31 Twp. 31 S. R. 17 V East West
City/State/Zip: IOLA, KS 66749	375 feet from (S) / N (circle one) Line of Section
Purchaser: ONE OK	660 feet from E (W)(circle one) Line of Section
Operator Contact Person: DENNIS KERSHNER	Footages Calculated from Nearest Outside Section Corner:
Phone: (620) 365-3111	(circle one) NE SE NW SW
Contractor: Name: WELL REFINED DRILLING CO, INC	Lease Name: WAGNER FARM TRUST Well #: 13-31
icense: 33072	Field Name: COFFEYVILLE-CHERRYVALE
Vellsite Geologist: JIM STEGEMAN	Producing Formation: PENNSYLVANIA COALS
	Elevation: Ground: UNKNOWN Kelly Bushing:
Designate Type of Completion:	Total Depth: 1078 Plug Back Total Depth: 1053.
New Well Re-Entry Workover	Amount of Surface Pipe Set and Cemented at 21.6 Feet
OilSWDTemp. Abd.	Multiple Stage Cementing Collar Used? ☐ Yes ✓ No
GasENHRSIGW	If yes, show depth setFeet
Dry Other (Core, WSW, Expl., Cathodic, etc)	If Alternate II completion, cement circulated from 1078
f Workover/Re-entry: Old Well Info as follows:	feet depth to SURFACE w/ 110 sx cmt.
Operator:	
Nell Name:	Drilling Fluid Management Plan ALTI NH7-11-08
Original Comp. Date: Original Total Depth:	(Data must be collected from the neserve Pit)
Deepening Re-perf Conv. to Enhr./SWD	Chloride content 1000 ppm Fluid volume 80 bbls
Plug BackPlug Back Total Depth	Dewatering method used PUMPED FLUID OUT - PUSHED PIT IN
Commingled Docket No.	Location of fluid disposal if hauled offsite:
Dual Completion Docket No	Operator Name: COLT ENERGY, INC.
Other (SWD or Enhr.?) Docket No	Lease Name: KING 4-25SWD License No.: 5150
10/19/05 10/20/05 2/6/07	Quarter NW Sec. 25 Twp. 31 S. R. 17 East West
Spud Date or Date Reached TD Completion Date or	County: LABETTE Docket No.: D-28,604
Recompletion Date Recompletion Date	County: Docket No.:
Kansas 67202, within 120 days of the spud date, recompletion, works	th the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, over or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. If 12 months if requested in writing and submitted with the form (see rule 82-3-105 and geologist well report shall be attached with this form. ALL CEMENTING III. Submit CP-111 form with all temporarily abandoned wells.
All requirements of the statutes, rules and regulations promulgates to regulation are complete and correct to the best of my knowledge.	ulate the oil and gas industry have been fully complied with and the statements
	KCC Office Use ONLY
Title: OFFICE MANAGER Date: 6/25/07	Letter of Confidentiality Received
-1h	If Denied, Yes Date:
Subscribed and sworn to before me this 25 day of	Wireline Log Received RECEIVED
2007.	Geologist Report Received S CORPORATION COMMISS
Notary Public: Sharley Attotler	IIIC Dietribution
1,00,000	JUN 2 9 2007
Date Commission Expires: 1/-J.U - 3-0 0 8	CONSERVATION DIVISION

perator Name: COL		✓ East	County: LA	e: WAGNER FA		Well #: 13-3		
ISTRUCTIONS: She isted, time tool open imperature, fluid reco	ow important tops a and closed, flowing overy, and flow rate	and base of formations p g and shut-in pressures, s if gas to surface test, a final geological well site	enetrated. Deta whether shut-in along with final c	l all cores. Repor	I static level, hydros	static pressure:	s, bottom hole	
Orill Stem Tests Taker (Attach Additional S		☐ Yes 📝 No	Ţ.	Log Format	tion (Top), Depth ar		Sample	
Samples Sent to Geological Survey		☐ Yes 🗸 No	Name			Тор	Datum	
Cores Taken		☐ Yes ☑ No DI		RILLERS LOG	ATTACHED			
Electric Log Run (Submit Copy)		✓ Yes ✓ No		•				
ist All E. Logs Run:								
	JAL INDUCTIO	ENSATED DENS ON SFL/GR, GAM	MA	New Used				
		Report all strings set-				# Sacks	Type and Percent	
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	Used	Additives	
SURFACE	12 1/4	8 5/8	24	21.6	PORTLAND	4		
PRODUCTION	l 6 3/4	4 1/2	10.5	1053	THICK SET	110		
		ADDITIONA	L CEMENTING /	SQUEEZE RECOP	RD			
Purpose: Perforate Protect Casing Plug Back TD Plug Off Zone	Depth Top Bottom	Type of Cement	#Sacks Used		Type and P	ercent Additives		
Shots Per Foot PERFORATION RECORD - Bridge Plugs Set/Type Shots Per Foot Sh				Acid, F	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used) Depth			
Specify Footage of Each microal Colorado				- 	250 GAL HCL 15% 10,000# 20/40 SAND 745-926			
4					250 GAL HCL 15% 6,600# 20/40 SAND 610-67			
4 518-521,548-552,584-587				250 GAL H	HCL 15% 10,000)# 20/40 SA	ND 518-587	
*		-					,	
				:				
TUBING RECORD	Size	Set At	Packer At	Liner Run	Yes No		1	
Date of First, Resumer	d Production, SWD or	Enhr. Producing Mo		owing 🗸 Pum	nping Gas Lif	it Othe	er (Explain)	
2/23/07	0.1	Bbls. Gas	Mcf	Water	Bbls.	Sas-Oil Ratio	Gravity	
Estimated Production Per 24 Hours	Oil	1.8	5	7.8				