

Notice: Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

KANSAS CORPORATION COMMISSION  
OIL & GAS CONSERVATION DIVISION  
**WELL PLUGGING RECORD**  
K.A.R. 82-3-117

Form CP-4  
December 2003  
Type or Print on this Form  
Form must be Signed  
All blanks must be Filled

Lease Operator: VESS OIL CORPORATION  
Address: 1700 Waterfront Parkway, Bldg. 500, Wichita, KS 67206  
Phone: (316) 682-1537 Operator License #: 5030  
Type of Well: oil Docket #: \_\_\_\_\_  
(Oil, Gas D&A, SWD, ENHR, Water Supply Well, Cathodic, Other) (If SWD or ENHR)  
The plugging proposal was approved on: verbal (Date)  
by: \_\_\_\_\_ (KCC District Agent's Name)  
Is ACO-1 filed?  Yes  No If not, is well log attached?  Yes  No  
Producing Formation(s): List All (If needed attach another sheet)  
Arbuckle Depth to Top: 3555 Bottom: 3561 T.D. 3561  
\_\_\_\_\_ Depth to Top: \_\_\_\_\_ Bottom: \_\_\_\_\_ T.D. \_\_\_\_\_  
\_\_\_\_\_ Depth to Top: \_\_\_\_\_ Bottom: \_\_\_\_\_ T.D. \_\_\_\_\_

API Number: 15-051-05906-00-00  
Lease Name: McCord A *KCC PLUG PER CP2/3*  
Well Number: 8  
Spot Location (QQQQ): \_\_\_\_\_ - SE - NW - SE  
1650 Feet from  North /  South Section Line  
1650 Feet from  East /  West Section Line  
Sec. 26 Twp. 11 S. R. 17  East  West  
County: Ellis  
Date Well Completed: 3/29/41  
Plugging Commenced: 12/3/08  
Plugging Completed: 12/3/08

Show depth and thickness of all water, oil and gas formations.

Oil, Gas or Water Records		Casing Record (Surface Conductor & Production)				
Formation	Content	From	To	Size	Put In	Pulled Out
				8-5/8"	1109	
				5-1/2"	3555	

Describe in detail the manner in which the well is plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same depth placed from (bottom), to (top) for each plug set.

MIRu. Perforated at 1650'; 1110'; 750' and 150'. Ran 2 3/8" tubing to 3007'. Spotted 60 sx 60/40 poz w/4% gel and 100# hulls w/7 sx gel on top. Pulled tbg to 1676'. Pumped 150 sx cement w/300# hulls and circulated cement to surface. TOH w/tubing. Pumped down 5 1/2" w/45 sx. Circulated cement out 8 5/8".


SI 8 5/8" and SI 5 1/2" w/250#. Approved by Pat Bedore w/KCC.

Name of Plugging Contractor: SMOKY HILLS Well Service License #: 5822  
Allied Cementing Co., Inc. License #: 32452  
Address: P.O. Box 31, Russell, KS 67665-0031  
Name of Party Responsible for Plugging Fees: Vess Oil Corporation  
State of Kansas County, Sedgwick, ss.

Pat Canaday (Employee of Operator) or (Operator) on above-described well, being first duly sworn on oath, says: That I have knowledge of the facts statements, and matters herein contained, and the log of the above-described well is as filed, and the same are true and correct, so help me God.

(Signature) [Signature]  
(Address) 1700 Waterfront Parkway, Bldg. 500, Wichita, KS 67206

SUBSCRIBED and SWORN TO before me this 19th day of December  
Michelle D. Henning My Commission Expires: \_\_\_\_\_  
Notary Public



WELL RECORD

Company Cities Service Oil Co. Well No. 8 Farm McCord  
 Location 900' south & 990' east of Center Sec. 26 T. 11 R. 17W  
 Elevation 2093 County Ellis State Kansas  
 Drig. Comm. March 11, 1941 Contractor Mabee Oil & Gas Company  
 Drig. Comp. March 29, 1941 Acid 500 gals. 4-4-41  
 T. D. 3561' Initial Prod. Barometer Potential: 14,999 oil, no water, 24 hours.

CASING RECORD:

8-5/8" @ 1109' con. 300 sx cement  
 & 8 sx Aquagel; resin.  
 top 80' of 8-5/8" cog.  
 with 35 sx cement.  
 5-1/2" @ 3555' con. 100 sx Ideal.

Corr. Top Erosional Arbuckle 3551  
 Corr. Top Solid Arbuckle 3555  
 Penetration 6'  
 Total Depth 3561

FORMATION RECORD:

rock	0-40
shale & shells	700
sand & shells	800
shale & shells	870
sand	930
shale & shells	1109
rod bed & shale	1253
lime	1310
shale & shells	1650
shale & salt	1760
shale & shells	1953
broken lime	2020
lime & shale	2130
lime	2156
lime & shale	2275
lime	2315
lime & shale	2664
shale & shells	2750
shale	2856
shale & lime	3014
lime	3279
Broken lime	3326
lime	3367
lime broken	3462
lime	3482
lime & shale	3553
lime cored (rec. 8")	3556
lime	3558

Fillup: 1275' oil in 40 mins.  
 1820' oil in 1 hr.  
 2850' oil in 2 hrs. 40 mins.

Syfo: 500' 0°  
 1000' 0°  
 1500' 0°  
 2000' 0°  
 2500' 0°  
 3000' 0°

RECEIVED  
 KANSAS CORPORATION COMMISSION

DEC 22 2008

CONSERVATION DIVISION  
 WICHITA, KS

3558 Rotary T. D. = 3561 S. L. M., T. D.

# ALLIED CEMENTING CO., LLC. 34817

REMIT TO P.O. BOX 31  
RUSSELL, KANSAS 67665

SERVICE POINT: Russell

DATE <u>12-3-08</u>	SEC. <u>26</u>	TWP. <u>11</u>	RANGE <u>17</u>	CALLED OUT	ON LOCATION <u>11:30 Am</u>	JOB START <u>12:00</u>	JOB FINISH <u>2:30 PM</u>
LEASE <u>McCord</u>		WELL # <u>A-8</u>		LOCATION <u>Cadell Rvr. Rd. Jct.</u>		COUNTY <u>Ellis</u>	STATE <u>Kansas</u>
<input checked="" type="radio"/> OLD OR NEW (Circle one)				<u>2 1/8 S. 1 E &amp; S INTO</u>			

CONTRACTOR Smokey Hill Well Service (Brian) OWNER \_\_\_\_\_

TYPE OF JOB PLUG ABANDONED Well

HOLE SIZE \_\_\_\_\_ T.D. \_\_\_\_\_

CASING SIZE 5 1/2 DEPTH \_\_\_\_\_

TUBING SIZE 2" DEPTH 3007

DRILL PIPE \_\_\_\_\_ DEPTH \_\_\_\_\_

TOOL \_\_\_\_\_ DEPTH \_\_\_\_\_

PRES. MAX 250# MINIMUM \_\_\_\_\_

MEAS. LINE \_\_\_\_\_ SHOE JOINT \_\_\_\_\_

CEMENT LEFT IN CSG. \_\_\_\_\_

PERFS. \_\_\_\_\_

DISPLACEMENT \_\_\_\_\_

CEMENT (USED 255 SK)

AMOUNT ORDERED 400 SK 60% 40% 4% GEL

7 Gel on Side

400# Hulls on Side

COMMON	<u>153 SK</u>	@	<u>13.50</u>	<u>2065.50</u>
POZMIX	<u>102 SK</u>	@	<u>7.55</u>	<u>770.10</u>
GEL	<u>16 SK</u>	@	<u>20.25</u>	<u>324.00</u>
CHLORIDE	_____	@	_____	_____
ASC	_____	@	_____	_____
Hulls	<u>4 SK</u>	@	<u>31.05</u>	<u>124.20</u>
RECEIVED KANSAS CORPORATION COMMISSION				
DEC 22 2008				
CONSERVATION DIVISION WICHITA, KS				
HANDLING	<u>400 Total SK</u>	@	<u>2.25</u>	<u>900.00</u>
MILEAGE	<u>20 Tax Mile</u>	@	<u>.10¢</u>	<u>800.00</u>
TOTAL				<u>4983.80</u>

**EQUIPMENT**

PUMP TRUCK CEMENTER G. Jean

# 398 HELPER MARY

BULK TRUCK

# 396 DRIVER BOB

BULK TRUCK

# \_\_\_\_\_ DRIVER \_\_\_\_\_

**REMARKS:**

2" Tubing @ 3007' spot 2 gel - 60 SK Cement w/ 100# Hulls. Pulled up to 1650 & circulated Cement to surface w/ 150 SK & 300# Hulls. Put on 5 1/2 Swage & mixed 45 SK Cement & Cement circulated around annulus. Shot in & squeezed to 250# on CSG.

**SERVICE**

DEPTH OF JOB \_\_\_\_\_

PUMP TRUCK CHARGE \_\_\_\_\_ 1045.00

EXTRA FOOTAGE \_\_\_\_\_ @ \_\_\_\_\_

MILEAGE 20 @ 7.00 140.00

MANIFOLD \_\_\_\_\_ @ \_\_\_\_\_

\_\_\_\_\_ @ \_\_\_\_\_

\_\_\_\_\_ @ \_\_\_\_\_

TOTAL 1185.00

CHARGE TO: Vess Oil Corporation

STREET \_\_\_\_\_

CITY \_\_\_\_\_ STATE \_\_\_\_\_ ZIP \_\_\_\_\_

**PLUG & FLOAT EQUIPMENT**

\_\_\_\_\_ @ \_\_\_\_\_

\_\_\_\_\_ @ \_\_\_\_\_

\_\_\_\_\_ @ \_\_\_\_\_

\_\_\_\_\_ @ \_\_\_\_\_

\_\_\_\_\_ @ \_\_\_\_\_

TOTAL \_\_\_\_\_

SALES TAX (If Any) \_\_\_\_\_

TOTAL CHARGES \_\_\_\_\_

DISCOUNT \_\_\_\_\_ IF PAID IN 30 DAYS

PRINTED NAME \_\_\_\_\_

SIGNATURE \_\_\_\_\_

