
15-065-21780-0000

NP 18321

			י ען	70-	
	TYPE AFFIDAVIT OF COMPLETION FO	RM	ACO-1 WELL	HISTORY Compt	· ·
	Two (2) copies of this form shall be filed with mission, 200 Colorado Derby Building, Wichita, Kansa				1
F	days after the completion of a well, regardless of he Attach separate letter of request if the inform. If confidential, only file one copy. Information on	ow the wation is	vell was com to be held	pleted. confidential	<u>.</u>
	record and <u>Side Two</u> will then be held confidential. Applications must be made on dual completion, c				
С	injection and temporarily abandoned wells. Attach one copy only wireline logs (i.e. electroneutron log, etc.). (Rules 82-2-105 & 82-2-125) KC	ical log C# (316)	g, sonic log 263-3238.	, gamma ray No Log	
	LICENSE # 5198 EXPIRATION DATE	6	/30/84		
	OPERATOR *A. Scott Ritchie (after csg. pt.)	API NO.	15-067-2	21,780	_
	ADDRESS 125 N. Market, Suite 950		Graham		
	Wichita, Kansas 67202	FIELD _	Unknown 2	VERGREE!	\underline{N} ω .
	** CONTACT PERSON Scott Ritchie PHONE (316) 267-4375	PROD. F	FORMATION	Lansing	
	PURCHASER Koch Oil Company	LEASE_	Goddard	(formerly R	<u>i</u> ffel)
	ADDRESS Box 2256	WELL NO). 1		
	Wichita, Kansas 67201	WELL LC	CATION C N	/2 S/2 N/2	
	DRILLING Murfin Drilling Company	<u>1650</u> Ft	. from <u>Nor</u>	th Line ar	nd
	CONTRACTOR ADDRESS 617 Union Center	<u>2640</u> Ft	. from Wes	t Line of	E (45)
	Wichita, Kansas 67202	the <u>N/2</u>	(Qkkx)SEC2	TWP9S RGE2	3_(W).
	PLUGGING N/A	-	WELL PLAT	(Offi	
	CONTRACTOR ADDRESS			ксс_	Only)
	<u> </u>	_		KGS_	<u></u>
	TOTAL DEPTH 4030' PBTD N/A	-	T	SWD/F PLG.	REP
	SPUD DATE 4/28/83 DATE COMPLETED 6/07/83	-	21	1.50	
	ELEV: GR 2431' DF KB 2436'				•
	DRILLED WITH (KANYAXX (ROTARY) XXXXX TOOLS.				
		ble me			
	Amount of surface pipe set and cemented 206' DV Tool Used? Yes THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil Gas, Shut-in Gas, Dry, Disposal, Injection, Temporarily Abandoned, OWWO. Other ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATIONS PROMULGATED TO REGULATE THE OIL AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH. * KIOWA EXPLORATION CO., 420 Heritage Park, 110 S. Main, Wichita, Ks. 67202				
	was operator up to casing point.				
A F F I D A V I T A. Scott Ritchie , being of lawful age, hereby certifies that:					
			Shell -	Malrie	, (*******
	(Name)				
	SUBSCRIBED AND SWORN TO BEFORE ME this 30th	1_day of	July	Y	 ,
	19 <u>83</u> .				
				•	

MY COMMISSION EXPIRES:



** The person who can be reached by phone regarding any questions concerning this information. $\begin{tabular}{ll} \hline \end{tabular} \begin{tabular}{ll} \hline \end{tabular} \ben$

SEC.21 TWP.9S RGE.2

FILL IN WELL INFORMATION AS REQUIRED:

WELL NO.

SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION. Show all important zones of porosity and contents thereof; cored intervals, and all drill-stern tests, in-cluding depth interval tasted, cushion used, time tool open, flowing and shut-in pressures, and recoveries. FORMATION DESCRIPTION, CONTENTS, ETC. DEPTH Check if no Drill Stem Tests Run. DST #1 from 3775'-3806'; 20,30,30, 45. Recovered 725'of froggy oil; IHP 1989#; IFP 74-117#; ISIP: 899#; FFP's:245-245#; FSIP:899#; FHP:1957#. DST #2 from 3827' to 3845'; 30,45,45,60.

Recovered 420' of muddy water with scum of oil. IFP:53-63#; ISIP:575#; FFP:181-181#; FSIP 575#. DST #3 from 3864'-3935'; 30,45,45,60. 200' of heavily oil cut mud, 60% oil. Recovered IFF:53-53#; ISIP:867#; FFP:138-138#; FSIP:742#. DST #4 from 3935'-4000'; 45,45,45,60. Recovered 5' of free oil & 360' of muddy water with a scum of oil. IFP:85-85#; ISIP:669#; FFP:202-202#; FHP: 2073#. ELECTRIC LOG TOPS Anhydrite 2033'(+ 403) 3718'(-1282) 3742'(-1306) Heebner Toronto Lansing 3756 (-1320) 3980'(-1544) B/KC LTD 4001' RTD4030' If additional space is needed use Page 2, Side 2 Report of all strings set - surface, intermediate, production, etc. CASING RECORD ((New)) or (Maxed) Size hole drilled Size casing set (in O.D.) Purpose of string Weight lbs/ft. Setting depth Type and percent additives Sacks Surface 12⅓" 8-5/8" 23# 206' 3% CC, 2% gel 10% salt + 10 common 150 60/40 poz 175 Production 7-7/8" 4½" 4024' bls. preflush 50/50 poz 450 6% gel LINER RECORD PERFORATION RECORD Top, ft. Bottom, ft. Sacks cement Shots per ft. Size & type Depth interval 2 DP jets 3947.5'-3951' TUBING RECORD 3/8" 3912 Siza Setting depth Packer set at 3/8" 1 3889.5' DP jet 3910'-13';3888 -91';3795'-3799'. ACID, FRACTURE, SHOT, CEMENT SQUEEZE RECORD Amount and kind of material used Depth interval treated Acidized w/600 gal. of 28% NE acid. 3947.5'-3951' Acidized with 1200 gal. of 28% NE acid. 3912' & 3889.5' 910'-13'; 3888'-91'; Acidized with 750 gal. of 28% NE acid. 3795**'-**3799' Date of first production Producing method (flowing, pumping, gas lift, etc.) Gravity 6/02/83 Swab test (will be pumping) Oil Est imated Water Gas-oil ratio % 85 ын. Production 15 bbls. CFPB Disposition of gas (vented, used on lease or sold) Perforations 3947.5'-51';3910'-13';3888'-91';