

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-163-23393-00-00
Spot: SESWSW Sec/Twnshp/Rge: 28-9S-20W
490 feet from S Section Line, 1080 feet from W Section Line
Lease Name: KERN A Well #: 1
County: ROOKS Total Vertical Depth: 3876 feet

Operator License No.: 8914
Op Name: H & C OIL OPERATING INC.
Address: PO BOX 86
PLAINVILLE, KS 67663

String	Size	Depth (ft)	Pulled (ft)	Comment
CIBP	5.5	3896		
PC		1836		
PROD	5.5	3914	0	175 SX
SURF	8.625	227	0	150 SX

125.97

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 12/29/2008 10:30 AM
Plug Co. License No.: 99996 Plug Co. Name: ALLIED CEMENT COMPANY
Proposal Rcvd. from: CHARLES RAMSEY Company: H&C OIL OPERATING, INC. Phone: (785) 434-7434

Proposed Plugging Method: Ordered out 250 sxs 60/40 pozmix - 4% gel - 400# hulls - 13 sxs gel.
Port collar at 1884' w/400 sxs cwc.
CIPB at 3680'.

Plugging Proposal Received By: RICHARD WILLIAMS Witness Type: COMPLETE (100%)
Date/Time Plugging Completed: 12/29/2008 12:30 PM KCC Agent: RICHARD WILLIAMS

Actual Plugging Report:

Allied pumped 50 sxs 60/40 pozmix - 4% gel with 200# hulls, followed with 13 sxs gel spacer with 200# hulls, followed with 165 sxs cement.
Max: P.S.I. 700#. S.I.P. 700#.
Backside Instant 500#.

Perfs:

Top	Bot	Thru	Comments
3890	3893		
3872	3876		
3654	3657		

INVOICED

DATE 1-23-09

INV. NO. 2009061071

RECEIVED
KANSAS CORPORATION COMMISSION

JAN 02 2009

CONSERVATION DIVISION
WICHITA, KS

Remarks: ALLIED CEMENTING COMPANY.

Plugged through: CSG

District: 04

Signed

Richard Williams

(TECHNICIAN)

CM

DEC 30 2008

PPT